

State of Hawaii 2023 Air Monitoring Network Plan

Submitted to the U.S. EPA Region 9

July 1, 2023

Prepared by:
State of Hawaii
Department of Health

Environmental Management Division Clean Air Branch

> Document Control Number HDOH – AMNP – 2023 - v01

This page intentionally left blank

Table of Contents

		es	
List o	of Figui	res	3
Acro	nyms a	and Definitions	4
Intro	duction	1	5
1.0	Netw	ork Purpose and Design	6
	1.1	Overview	
		1.1.1 State and Local Air Monitoring Stations (SLAMS)	
		1.1.2 Special Purpose Monitoring Stations (SPMS)	
	1.2	Network Design and Review Process	
	1.2	1.2.1 Monitoring Objectives and Site Types	
		1.2.2 PM _{2.5} Network Changes	
	1.3	Organizational Structure and Responsibilities	
	1.3	Organizational Structure and Responsibilities	9
2.0	Netw	ork Evaluation	10
	2.1	PM _{2.5} Network	
	2.2	PM ₁₀ Network	
	2.3	Pb Network	
	2.4	O ₃ Network	
	2.5	NO ₂ Network	
	2.6	CO Network	
	2.7	SO ₂ Network	
	2.8	NCore	
	2.9	H ₂ S Network	
	2.10	Site Closures	
		2.10.1 Pearl City SLAMS	
		2.10.2 Kihei SLAMS	
		2.10.3 Honaunau SPMS	
	2.11	Site Additions	
	2.12	Site Modifications	23
		2.12.1 Kapolei SLAMS/NCore	23
		2.12.2 Sand Island SLAMS	23
		2.12.3 Niumalu SPMS	23
		2.12.4 Naalehu SPMS	
		2.12.5 Waikoloa SPMS	23
		2.12.6 Keeau SPMS	
	2.13	Summary of Network and Changes	
		Summary of Hother and Shariges minimum.	
3.0	Detai	iled Site Descriptions	26
	(DH)	HONOLULU	27
		KAPOLEI SLAMS and NCORE	
		SAND ISLAND	
	` ,	KAHULUI	
	` '	NIUMALU	
	` ,	HILO	
		KONA	
	` ,	MOUNTAIN VIEW	
		OCEAN VIEW	
		PAHALA	
		KAILUA-KONA	
		KEAAU	
	(∟⊏)∣	LEILANI COMMUNITY ASSOCIATION CENTER	54

(NA) NAALEHU	56
(WL) WAIKOLOA	
(KE) KAHE	
Appendix A: Public Notice Documentation	62
Appendix B: Request to Close the Pearl City SLAMS Air Monitoring Station (150032004	
Appendix C: Request to Close the Kihei SLAMS Air Monitoring Station (150090006)	66
Appendix D: Request to Discontinue PM _{2.5} and NO ₂ Parameters at the Niumalu SPMS	;
Air Monitoring Station (150070007)	69
Appendix E: Request to Discontinue CO and SO ₂ Parameters at the Kapolei SLAMS	
Air Monitoring Station (150030010)	72
Appendix F: Request to Close the Honaunau SPMS Air Monitoring Station (150013032)	75
Appendix G: AQS Reports in Support of Requests for Closures and Discontinuations	s78

List of Tables

Table 2-1	PM _{2.5} Network and Concentrations for Each MSA	12
Table 2-2	PM _{2.5} Minimum Monitoring Requirements for Each MSA	12
Table 2-3	PM _{2.5} Collocated Network	12
Table 2-4	PM ₁₀ Network and Concentrations for the Honolulu MSA	14
Table 2-5	PM ₁₀ Minimum Monitoring Requirements for Each MSA	
Table 2-6	Minimum Pb Monitoring Requirement at NCore	16
Table 2-7	O ₃ Design Values for the Honolulu MSA	
Table 2-8	O ₃ Minimum Monitoring Requirements for Each MSA	
Table 2-9	Minimum Near-Road NO ₂ Monitoring Requirements for the MSA	18
Table 2-10	Minimum SO ₂ Monitoring Requirements	20
Table 2-11	Number of Monitors by Pollutant or Program	24
Table 2-12	Summary of Network Changes	
Table 3-1	State of Hawaii Ambient Air Monitoring Network	26
	List of Figures	
Figure 2-1	PM _{2.5} Network	13
Figure 2-2	PM ₁₀ Network	
Figure 2-3	O ₃ Network	
Figure 2-4	NO ₂ Network	18
Figure 2-5	CO Network	19
Figure 2-6	SO ₂ Network	

Acronyms and Definitions

AADT Annual Average Daily Traffic

AQI Air Quality Index

AQS Environmental Protection Agency Air Quality System

BAM Beta-Attenuation Mass Monitor

CAA Clean Air Act

CAB State of Hawaii Department of Health Clean Air Branch

CAB-IT Clean Air Branch Information Technology

CBSA Core-Based Statistical Areas
CFR Code of Federal Regulations

CO Carbon Monoxide

DOH Hawaii State Department of Health

DRR Data Requirements Rule

DWS Hawaii County Department of Water Supply

ECA (North American) Emissions Control Area (Maritime)
EPA United States Environmental Protection Agency

FEM Federal Equivalent Method FRM Federal Reference Method

H₂S Hydrogen Sulfide

HECO Hawaiian Electric Company

IMPROVE Integrated Monitoring of Protected Visual Environments

LERZ Kilauea Volcano Lower East Rift Zone

MSA Metropolitan Statistical Area

MSL Mean Sea Level

NAAQS National Ambient Air Quality Standards

NCore National Core Multi-Pollutant Monitoring Stations

NEI National Emissions Inventory

NO Nitrogen Oxide NO₂ Nitrogen Dioxide

NO_y Reactive Oxides of Nitrogen

O₃ Ozone

PAMS Photochemical Assessment Monitoring Station

Pb Lead

PGV Puna Geothermal Ventures

PM Particulate matter

PM_{2.5} Particulate matter less than or equal to 2.5 microns in aerodynamic diameter PM₁₀ Particulate matter less than or equal to 10 microns in aerodynamic diameter

PM_{10-2.5} Particulate matter coarse POC Parameter Occurrence Code

PQAO Primary Quality Assurance Organization

PPB Parts per billion
PPM Parts per million

PSD Prevention of Significant Deterioration PWEI Population Weighted Emissions Index

QC Quality Control

SLAMS State and Local Air Monitoring Stations

SO₂ Sulfur Dioxide

SPM(S) Special Purpose Monitoring (Stations)
VMAP Vog Measurement and Prediction Project

VOG Haze due to volcanic emissions

WD Wind direction WS Wind speed

µg/m³ micrograms per cubic meter of air

Introduction

The State of Hawaii Department of Health (DOH), Clean Air Branch (CAB) plans, operates, and maintains the statewide ambient air quality monitoring network. Ambient air monitoring data is submitted to the U.S. Environmental Protection Agency's (EPA) AirNow website which reports air quality using the Air Quality Index (AQI). This data is used to determine compliance with National Ambient Air Quality Standards (NAAQS), to track and characterize air quality trends, evaluate emission control strategies, and to support health studies.

The DOH manages the State and Local Air Monitoring Stations (SLAMS), Special Purpose Monitoring Stations (SPMS), and the National Core Multi-Pollutant Monitoring Station (NCore). DOH oversees an ambient air station on the island of Oahu that is operated by Hawaiian Electric Company (HECO) to meet the Data Requirements Rule (DRR). Additionally, Hawaii has two Interagency Monitoring of Protected Visual Environments (IMPROVE) stations located at Haleakala National Park on Maui and Volcanoes National Park on the island of Hawaii. The IMPROVE stations are operated and maintained by the National Park Service through their federal land management agency.

This annual review evaluates the state's existing ambient air monitoring network to determine adequacy in meeting monitoring objectives, optimizing the network by adding new, relocating, or discontinuing stations, ensuring that air quality issues important to the state are being addressed, and that the quality assured data meets the needs of stakeholders.

This plan encompasses the 18-month period from July 1, 2023 through December 31, 2024. During this period, modifications to this plan may occur due to changes of available resources, staff reductions, funding restrictions, unanticipated community concerns, site issues, or new EPA monitoring requirements. This plan is being submitted to the EPA Region 9 according to the Code of Federal Regulations (CFR), Title 40, Part 58, Section 58.10 Annual monitoring network plan and periodic network assessment.

Notification of the plan availability for public inspection and comment was provided through public notices published on May 17, 2023 in the daily newspapers of all counties. The plan was available for inspection on the Clean Air Branch website at http://health.hawaii.gov/cab, for 30 days from May 17, 2023 to June 15, 2023. Documentation of public notification is provided in **Appendix A**. Comments received will be addressed and included in this plan.

1.0 Network Purpose and Design

1.1 Overview

In 1970, the federal Clean Air Act (CAA) was promulgated as a comprehensive response to address air pollution and created the EPA as the agency responsible for carrying out the law. In 1990, the CAA was amended, Title 40 of the Code of Federal Regulations (CFR) Part 50 required the EPA to set National Ambient Air Quality Standards (NAAQS) for pollutants considered harmful to public health and the environment. This amendment identified six principal pollutants, which are called criteria air pollutants, they are: particulate matter (PM), sulfur dioxide (SO₂), carbon monoxide (CO), nitrogen dioxide (NO₂), ozone (O₃), and lead (Pb). Additionally, the CAA NAAQS defined two types of standards:

- Primary standards set limits to protect public health including protecting "sensitive" populations such as asthmatics, children, and the elderly.
- Secondary standards set limits to protect public welfare, including the protection against decreased visibility, damage to animals, crops, vegetation, and buildings.

These standards are reviewed periodically and are subject to revisions. Additionally, there is a state standard for hydrogen sulfide (H₂S) that was established primarily to monitor the ambient air effects of geothermal energy production activities on the island of Hawaii.

40 CFR Part 58 requires that states establish and operate active ambient air quality surveillance systems in a manner that assures the most applicable data of the highest quality is collected. Appendix A to 40 CFR Part 58 provides the quality assurance requirements that each monitoring organization must implement to ensure that the data produced will be of the type and quality needed and expected by the data user. The data is used, in part, to support regulatory, research, and health decisions and to provide air quality information to the general public.

The ambient air monitoring network is designed for the following purposes:

- To determine compliance with the NAAQS.
- To provide the public with timely air quality information.
- To support air pollution research and health studies.
- To track pollution trends throughout the region, including non-urban areas.
- To develop emissions control strategies.
- To prevent or alleviate air pollution episodes by activating emergency control procedures.

The State of Hawaii's monitoring network consists of three major categories of monitoring stations, State and Local Air Monitoring Stations (SLAMS), National Core (NCore), and Special Purpose Monitoring Stations (SPMS).

The annual network review ensures that Hawaii continues to meet monitoring and siting requirements, the three basic monitoring objectives, addresses the six site types in 40

CFR Part 58, Appendix D, provides information for non-regulatory data goals, and complies with requirements of 40 CFR Part 58, Appendices A, C, D, and E as follows:

- Appendix A: Quality Assurance Requirements for SLAMS, SPMS and PSD Air Monitoring
- Appendix C: Ambient Air Quality Monitoring Methodology
- Appendix D: Network Design Criteria for Ambient Air Quality Monitoring
- Appendix E: Probe and Monitoring Path Siting Criteria for Ambient Air Quality Monitoring

1.1.1 State and Local Air Monitoring Stations (SLAMS)

The **SLAMS** sites were established primarily to determine compliance with the NAAQS and to meet minimum monitoring requirements set forth in 40 CFR Part 58, Appendix D but may also serve other data purposes such as providing real-time air pollution data for the general public, for regulatory decision making and compliance.

One of the main objectives is to show whether the state is in attainment or non-attainment of the seven criteria pollutants. Non-attainment of any of the NAAQS may have regulatory consequences addressed through the air permitting program. Historically, Hawaii has been in attainment of the NAAQS. Summarized data is available at: https://health.hawaii.gov/cab/hawaii-air-quality-data-books.

All SLAMS must meet quality assurance, methodology, and siting requirements of 40 CFR 58 Appendix A, C and E, respectively. All data is submitted to EPA's Air Quality System (AQS) within 90 days at the end of each calendar quarter, as required in 40 CFR 58.16.

On October 17, 2006, as published in the Federal Register, the EPA provided final rule revisions to ambient monitoring regulations as contained in 40 CFR, Parts 53 and 58. Included in these revised rules are the requirements for establishing NCore sites. NCore stations are established to support the tracking of long-term trends of criteria and non-criteria pollutants, model evaluation, long-term health and ecosystem assessments, and other scientific and technological studies.

NCore site, to begin January 1, 2011, and measure, at a minimum, PM_{2.5} particulate matter (particles with an average aerodynamic diameter of 2.5 micrometers or less) using continuous and integrated/filter-based samplers, speciated PM_{2.5}, PM_{10-2.5} particulate matter, SO₂, CO, nitrogen oxide (NO), reactive oxides of nitrogen (NO_y), O₃, wind speed, wind direction, relative humidity and ambient temperature. Gas monitors at this site are more sensitive than the standard monitors used at the other sites. Concentrations measured are well below NAAQS but are important in the formation of ozone and particulate matter. Hawaii's SLAMS network includes a NCore site in Kapolei which became fully operational on January 1, 2011.

1.1.2 Special Purpose Monitoring Stations (SPMS)

The **SPMS** were established for specific areas of interest to the state and do not count in meeting the minimum monitoring requirements. However, all SPMS utilize

7

Federal Reference Methods (FRM), Federal Equivalent Methods (FEM), or Approved Regional Methods (ARM), and meet the requirements of 40 CFR Part 58, Appendix E, follow all the quality assurance criteria contained in 40 CFR Part 58, Appendix A as well as the data quality and measurement quality objectives and siting requirements. All data from SPMS which have operated for more than 24 months are eligible for comparison to respective NAAQS.

Areas of Interest for special purpose air monitoring are from sources that are natural and man-made. Hawaii's SPM network is established primarily to monitor air quality impacts of emissions from Kilauea volcano, hydrogen sulfide (H₂S) emissions from geothermal energy production and impacts from cruise ships on the island of Kauai.

1.2 Network Design and Review Process

The network review process is conducted to determine if any changes or modifications to the network are necessary. Changes such as meeting new NAAQS monitoring requirements, utilizing newer and better technology, reducing or eliminating redundancy and low value monitoring, ensuring that enough data is being collected using the best technology, and that all siting and quality assurance requirements are met.

Modification decisions are made using a variety of tools, including but not limited to: data trend analyses; performance and technical systems audits; regular site inspections; cost and value analyses; assessment of unfavorable site changes such as loss of lease or construction that adversely affect data collection; and the need to address special studies or new regulatory as well as non-regulatory monitoring objectives.

1.2.1 Monitoring Objectives and Site Types

Ambient air monitoring networks must be designed to meet three basic objectives as stated in 40 CFR Part 58, Appendix D:

- 1) Provide air pollution data to the general public in a timely manner.
- 2) Support compliance with NAAQS and emissions strategy development.
- 3) Support air pollution research studies.

The state's ambient air monitoring network achieves all three objectives as follows:

- 1) Air pollution data from all SLAMS and SPMS are exhibited near real-time on the DOH public website. Additionally, continuous PM_{2.5} and O₃ data is provided to EPA's AIRNow website for use in calculating the AQI, SO₂ data is provided for the Hawaii SO₂ Short Term Advisory, and PM_{2.5} and SO₂ data is provided to the Vog Measurement and Prediction Project (VMAP).
- 2) Data from SLAMS are used to demonstrate compliance with the NAAQS and in development and tracking of emissions control strategies. Similarly, data from the NCore station is used to demonstrate compliance with the NAAQS and to track long-term trends of criteria and non-criteria pollutants as well as support emissions control strategies.
- 3) All SLAMS, SPMS, and NCore monitoring provide valuable information in support of air pollution, health, and other scientific studies.

In order for the network to support the three basic objectives outlined above, it must be designed with a variety of monitoring site types. The six general site types are:

- 1) Determine the highest pollutant concentrations expected in the network.
- 2) Measure typical concentrations in areas of high population density.
- 3) Determine the impact of significant sources or source categories on air quality.
- 4) Determine general background concentrations.
- 5) Determine the extent of regional pollutant transport between populated areas.
- 6) Measure pollution impacts on visibility, vegetation, crops, animals, and buildings.

The site type for each station in the network is included in its detailed description in Section 3.0 of this plan.

1.2.2 PM_{2.5} Network Changes

According to 40 CFR 58.10 (c), this network plan must document how the state will provide for the review of changes to a PM_{2.5} monitoring network that impact the location of a violating PM_{2.5} monitor. The agency must document the process for obtaining public comment and include any comments received through the public notification process within the submitted plan. The state has in place a public notification procedure which includes posting a notice in the newspapers of all counties and on the agency web site allowing for public inspection and comments of the changes that are in the annual network plan document. Any comments received are reviewed and if appropriate provided a response.

1.3 Organizational Structure and Responsibilities

The CAB is the state agency responsible for air pollution control in Hawaii and includes planning, management, data collection, quality assurance, and regulatory activities. The DOH serves as the Primary Quality Assurance Organization (PQAO).

The CAB is responsible for the overall planning, siting, and quality assurance oversight of the ambient air monitoring program as well as all data collection activities including installing, operating, and maintaining ambient air monitoring equipment and stations, in order to provide valid quality assured, defensible data that meet EPA QA requirements. The CAB-IT provides the quality assured data to AQS. The DOH contracts out laboratory support for collocated $PM_{2.5}$ mass analyses.

2.0 Network Evaluation

The criteria ambient air quality network for the State of Hawaii is established according to the requirements of 40 CFR Part 58, Appendix D. The CAB is responsible for ensuring that the network meets or exceeds the minimum EPA monitoring requirements and locating stations to adequately address the purposes and objectives. The criteria and NCore pollutants covered in this document; CO, NO₂, O₃, SO₂, PM₁₀, and PM_{2.5} are currently monitored at sixteen (16) stations statewide as follows:

- one (1) SLAMS and one (1) NCore CO monitors.
- one (1) SLAMS NO₂ monitor.
- one (1) NCore NO/NO_v monitor.
- one (1) SLAMS and one (1) NCore O₃ monitors.
- four (4) SLAMS, eight (8) SPMS, and one (1) NCore SO₂ monitors.
- one (1) SPMS H₂S monitor.
- one (1) SLAMS and one (1) NCore PM₁₀ monitors.
- two (2) SLAMS, ten (10) SPMS, and one (1) NCore PM_{2.5} monitors.

40 CFR Part 58, Appendix D identifies the minimum monitoring requirements for criteria pollutants in the SLAMS network. The monitoring requirements are based on the latest census population in each Metropolitan Statistical Area (MSA). MSAs are defined by the Federal Office of Management and Budget (OMB) and the U.S. Census Bureau. According to the OMB, there are two MSAs in the state: Urban Honolulu with a 2022 census population of 995,638 and Kahului-Wailuku-Lahaina in Maui County with a 2022 census population of 164,351. The 2022 census population was estimated at 1,440,196 for the state, down 0.5% from the updated 2021 estimate of 1,447,154. There are five counties in the state: Kauai (islands of Niihau and Kauai); City & County of Honolulu (island of Oahu); Maui (islands of Maui, Molokai excluding Kalawao County, Lanai, and Kahoolawe); Kalawao (Kalaupapa Settlement on Molokai) and Hawaii (island of Hawaii). Hawaii's network meets the minimum monitoring requirements.

As the NAAQS are revised, the number of required monitors may also change, some of the tools that may be used to determine network adequacy are:

- Historical monitoring data.
- Maps of emissions densities.
- Dispersion modeling.
- Special studies.
- Best professional judgment.
- State Implementation Plan requirements.
- Monitoring strategies.
- Population density changes.
- Traffic counts.

The actual geographic location of monitors in the network is reviewed using maps, photographs, and GIS information. Plots of source emissions, historical monitoring data, population density, and other special study findings may also be used to evaluate the monitor locations.

The stated objective for each monitoring site is reconfirmed and the location's spatial scale is verified. If the site location does not support the stated objectives or the designated spatial scale, changes will be proposed to the EPA in the annual network plan to rectify the discrepancy.

An integral part of the network review is an in-depth determination of whether it meets the needs of specific state objectives as well as budgetary and staff limitations. This includes reviewing for:

- The need for new monitors or monitoring sites.
- The need to relocate existing monitors.
- Siting problems and solutions.
- Data submittal and completeness problems.
- Station maintenance issues.
- Quality assurance problems.
- The need for air quality studies and special monitoring programs.
- Other issues such as proposed regulations and funding.

The network review is documented in the annual network plan and is made available for public inspection at least thirty (30) days prior to submittal to EPA Region 9 on or before July 1 of each year. The most current network plan is posted on the CAB website at http://health.hawaii.gov/cab under "Reports".

2.1 PM_{2.5} Network

The state must operate a minimum number of required PM_{2.5} monitors based on population and the most recent 3-year design value in each MSA. There are three PM_{2.5} SLAMS in the Honolulu MSA and one SLAMS in the Maui MSA with complete design values. The design value for the annual PM_{2.5} standard is the most current 3-year average annual mean for each site. The design value for the 24-hour PM_{2.5} standard is the most current 3-year average of annual 98th percentile 24-hour values recorded at each monitoring site. Table 2-1 shows the annual and daily design values for complete data years 2020 to 2022.

The most recent 3-year design values in the Honolulu and Maui MSAs were less than 85% of any PM_{2.5} NAAQS. Table 2-2 shows that the state operates more than the minimum monitoring requirements for PM_{2.5} in each MSA. Additionally, in 2022, the state operated one SPMS in the Maui MSA and ten SPMS on the island of Hawaii for volcanic emissions. All stations use FEM monitors and follow the requirements of 40 CFR Part 58, Appendices A, D, and E. All SPMS except Keeau, Naalehu, and Waikoloa have been operating for more than 24 months and therefore are subject to NAAQS comparison; these three SPMS have been at their permanent location for less than 24 months.

To reduce the size of the PM_{2.5} network, some monitors were temporarily discontinued. See Section 2.12 for discussion on site modifications and Section 3.0 for detailed location information.

The IMPROVE monitoring station (HACR1) at Haleakala National Park on Maui, operated by the National Park Service, serves as the background/transport PM_{2.5} site

for the state's network. All primary $PM_{2.5}$ monitors operated by the state are continuous FEM. Figure 2-1 shows the map locations of all the $PM_{2.5}$ stations in the state.

Table 2-1. PM_{2.5} Network and Concentrations for Each MSA

Site	AQS No.	Sampling Frequency	Annual Design Value (µg/m³) 2020 – 2022	Percent of Annual NAAQS (12µg/m³)	Daily Design Value (µg/m³) 2020-2022	Percent of 24-Hour NAAQS (35 µg/m³)		
Honolulu MSA								
Honolulu	150031001	Continuous	3.1	26	6	17		
Kapolei	150030010	Continuous	3.7	31	8	23		
Pearl City ¹	150032004	Continuous	3.3	28	6	17		
Sand Island	150031004	Continuous	3.6	30	7	20		
Maui MSA								
Kihei ²	150090006	Continuous	2.6	22	7	20		

NOTE: Haleakala IMPROVE (150099001) is the PM_{2.5} background/transport site for Hawaii and is operated and maintained by the NPS

Table 2-2. PM_{2.5} Minimum Monitoring Requirements for Each MSA

rabio 2 21 1 m2.5 minimani mornio mg raban ombito tor 2 aon mort									
MSA Population Category (2022 Census) (40 CFR 58 Appendix D Table D-5)			Most recent 3-yea ≥85% of any P (≥29.75 μg/m³ for 2 ≥10.2 μg/m³ for an	M _{2.5} NAAQS 24-hr standard;	Most recent 3-year Design Value <85% of any PM _{2.5} NAAQS (<29.75 μg/m³ for 24-hour standard; <10.2 μg/m³ for annual standard)				
	>1,000,000				2	2			
	500,000-1,000,000				1				
	50,000-<500,000		1		0				
MSA	2022 Census Population (estimated)	Highest Annual Design Value 2020 – 2022	Highest Daily Design Value 2020-2022	Required No. of Monitors	Number of Active Monitors in the MSA	Number of Monitors Needed			
Honolulu	995,638	3.7	8	1	3	0			
Maui	164,351	2.6	7	0	1 SPMS	0			

Appendix A to 40 CFR Part 58 requires that 15 percent of each PM_{2.5} monitoring method be collocated. The state currently operates two SLAMS, one NCore and ten SPMS FEM monitors (thirteen total); eleven of which are using Method 209 and two that are using Method 238. Since the state is requesting temporary closures and modifications, the number of collocated monitors will be adjusted accordingly.

One collocated monitor is required for the stations using Method 238. One FRM collocated monitor is operating at the Kapolei NCore station to meet this requirement.

Two collocated monitors are currently required for the eleven stations using Method 209, one is the FRM collocated monitor operating at the Sand Island station. There is also a $PM_{2.5}$ FEM collocated at the Kona station. The state will adjust the number of collocated FRM and/or FEM monitors as needed, pending approvals for temporary site closures. Table 2-3 summarizes the $PM_{2.5}$ collocated network at the time of plan publication.


Table 2-3. PM_{2.5} Collocated Network

Method Code	# Primary Monitors	# Required Collocated	# Active Collocated FRM	# Active Collocated FEM (same method designation as primary)
209	11	2	1	1
238	2	1	1	0

¹ The Pearl City station discontinued operations on April 6, 2022.

² The Kihei station discontinued operations on March 30, 2022.

Figure 2-1. PM_{2.5} Network



2.2 PM₁₀ Network

The minimum number of required PM₁₀ monitoring stations for the MSA is dependent upon population and concentration measurements. High concentration areas are those for which the ambient PM₁₀ data show concentrations exceeding the PM₁₀ NAAQS by 20 percent or more. Medium and low concentration areas are those for which ambient PM₁₀ data show concentrations exceeding 80 percent of the NAAQS, and concentrations less than 80 percent of the NAAQS, respectively.

PM₁₀ data for 2022 showed the Honolulu MSA to be a low concentration area (Table 2-4) and, therefore, is required to have one to two PM₁₀ monitors (Table 2-5). In the absence of a PM₁₀ design value for the Maui MSA and with a population <250,000, no PM₁₀ monitoring is required in that MSA. The state meets the minimum PM₁₀ monitoring requirements with two PM₁₀ stations in the Honolulu MSA.

Table 2-4. PM₁₀ Network and Concentrations for the Honolulu MSA¹

Site Name	AQS No.	2022 Maximum 24-Hr Value (μg/m³)	Percent of 24-Hr NAAQS	Sampling Frequency
Honolulu	150031001	25	17	Continuous
Kapolei	150030010	51	34	Continuous
Pearl City ²	150032004	38	25	Continuous

¹ There is currently no PM₁₀ monitor operating in the Maui MSA.

Table 2-5. PM₁₀ Minimum Monitoring Requirements for Each MSA


MSA Population Category (2022 Census) (40 CFR 58 Appendix D Table D-4)		High Concentration ≥120% of NAAQS (≥180 μg/m³)		Medium Concentration >80% of NAAQS (>120 µg/m³)		Low Concentration <80% of NAAQS (<120 µg/m³)¹		
>1,000,000			6-10		2	1-8	2-4	
500,000-1,000,000			4-8		2-4		1-2	
250,000-500,000			3-4		1-2			0-1
100,000-250,000		1-2 0-)-1		0		
MSA	2022 Census Population (estimated)		lighest 24-hr Value (2022)		quired # of Monitors	# of Active Mo in the MS		# of Monitors Needed
Honolulu	995,638		51 μg/m ³		1-2	2		0
Maui	164,351	No	data available		O ¹	0		0

¹ 40 CFR Part 58, Appendix D, Section 4.6, Table D-4 states that in the absence of a design value, these minimum monitoring requirements apply.

Figure 2-2 is a map of the current PM_{10} sites in the state. All the PM_{10} stations are in the Honolulu MSA.

² The Pearl City station discontinued operations on April 6, 2022.

Figure 2-2. PM₁₀ Network



2.3 Pb Network

Pb monitoring was conducted from January 1, 2012, until discontinued on December 31, 2018 at the Kapolei/NCore site. Concentrations of Pb measured during this period were approximately one to two percent of the standard. The state has no sources emitting greater than 0.5 tons per year according to the most recent emissions inventory. EPA approved the discontinuation of Pb monitoring per letter dated October 29, 2018.

Table 2-6. Minimum Pb Monitoring Requirement at NCore

NCore	AQS ID	CBSA	2022 Census Population (estimated)	# Required Monitors	# Active Monitors	# Monitors Needed
KA	150030010	Honolulu	995,638	*0	*0	0

^{*} Per EPA letter dated October 29, 2018, the Pb monitoring at Kapolei NCore was approved to be discontinued.

2.4 O₃ Network

Depending upon MSA population and typical peak concentrations, the state must operate a minimum number of O₃ monitors. NCore sites are intended to complement O₃ data collection and can be used to meet the minimum monitoring requirements.

The O₃ monitoring season for the State of Hawaii is 12-months from January to December. The O₃ design value is the 3-year average of the fourth-highest daily maximum 8-hour concentrations measured at each monitor.

The most recent O_3 design value concentrations at the Sand Island and Kapolei NCore stations in the Honolulu MSA showed less than 85% of the O_3 NAAQS (Table 2-7). The Maui MSA does not have any O_3 monitoring. According to 40 CFR Part 58, Appendix D, Table D-2 and, as shown in Table 2-7 below, with a 2022 census population estimated at 164,351 and in the absence of a design value, no O_3 monitor is required in the Maui MSA. The state meets the minimum O_3 network monitoring requirements.

Table 2-7. O₃ Design Values for the Honolulu MSA

Stations in the MSA	8-Hour Design Value 2019 – 2021	2022 MSA Census Population	Required # of Monitors	# of Active Monitors in the MSA	# of Monitors Needed			
Sand Island (150031004)	0.047	995,638	1	2	0			
Kapolei (150030010)	0.048	(estimated)		2	O O			
There is no O ₃ mo	onitor in the Maui	164,351 (estimated)	0	0	0			

Table 2-8. O₃ Minimum Monitoring Requirements for Each MSA

-	<u> </u>	
MSA Population Category (40 CFR 58 Appendix D Table D-2)	Most recent 3-year design value ≥85% of any O₃ NAAQS (≥.064 ppm, 8-hr standard)	Most recent 3-year design value <85% of any O₃ NAAQS (<.064 ppm, 8-hr standard)¹
>10 million	4	2
4-10 million	3	1
350,000-<4 million	2	1
50,000-<350,000	1	0

¹ According to 40 CFR part 58 Appendix D, Table D-2, these minimum monitoring requirements apply in the absence of a design value.

Hawaii is in attainment with the 8-hour O₃ standard and is not required to submit an Enhanced Monitoring Plan (EMP). 40 CFR Part 58.10 requires that states with Moderate and above 8-hour O₃ nonattainment areas and states in the Ozone Transport Region as defined in 40 CFR 51.900 shall develop and implement an EMP.

Figure 2-3 shows the map locations of the SLAMS and NCore O₃ stations. Both stations are in the Honolulu MSA.




Figure 2-3. O₃ Network

2.5 NO₂ Network

40 CFR Part 58, Appendix D Section 4.3.3 requires area wide NO₂ monitoring in the location of highest expected concentration in Core-Based Statistical Areas (CBSA) with a population ≥1,000,000. The Honolulu MSA had a 2022 census population estimated at 995,638. The population and Annual Average Daily Traffic (AADT) for the Honolulu CBSA will be monitored, and when thresholds are reached, the near-road monitoring will be established.

The state currently has one SLAMS NO₂ station in the Honolulu MSA which measures typical concentration in areas of high population density. Additionally, this location would be suitable as the area-wide monitor because it is in the area of highest expected concentration. No NO₂ monitoring is required in the Maui MSA.

Table 2-9. Minimum Near-Road NO₂ Monitoring Requirements for the MSA

CBSA	2022 Census Population (estimated)	Max AADT Counts (2021) ¹	# Required Monitors	# Monitors to be operational by 1/1/2017
Honolulu	995,638	252,626	0	0

¹ 2021 estimated average AADT provided by the State of Hawaii Department of Transportation, calculated from a 4% drop in volume from the 2019 count of 263,152.




Figure 2-4. NO₂ Network

2.6 CO Network

The state operates two CO monitors, one SLAMS and one SLAMS/NCore, in the Honolulu MSA. Figure 2-5 shows the locations of the CO sites in the state. 40 CFR Part 58, Appendix D Section 4.2.2 requires one collocated CO monitor at near-road NO₂ sites in Core-based Statistical Areas (CBSA) with populations ≥1,000,000. The Honolulu MSA had a 2022 census population estimated at 995,638. The population and AADT for the Honolulu CBSA will be monitored, and when thresholds are reached, the near-road monitoring and the collocated CO monitor will be established. No CO monitoring is required in the Maui MSA.




Figure 2-5. CO Network

2.7 SO₂ Network

According to the Population Weighted Emissions Index (PWEI) calculation, established to determine SO₂ monitoring requirements, Hawaii is required to operate one SO₂ monitor in the Honolulu MSA and none in the Maui MSA (Table 2-10). The state currently operates one SLAMS SO₂ monitor in the Honolulu MSA, and one at the NCore station in Kapolei which meets the minimum number of required SO₂ stations. There are no requirements for a SO₂ monitor in the Maui MSA.

The SPM station on Kauai was established to measure SO₂ from cruise ship emissions and will continue. The FEM monitors SO₂, follows all requirements of 40 CFR Part 58, Appendices A, D, and E, and as of April 2, 2013, has been operating for more than 24 months and is eligible for comparison with the NAAQS.

Elevated levels of SO₂ in communities affected by volcanic emissions continue to be a concern on Hawaii island. In addition to eruptive episodes inside Halemaumau Crater at the summit of Kilauea volcano, on November 27, 2022, Mauna Loa erupted for the first time in forty years. Although the eruption lasted less than 2 weeks, there were concerns during that time that there was insufficient coverage of SO₂ monitoring on the north side of the island. Thus, an SO₂ monitor was added at the Waikoloa station.

To provide timely notification of SO₂ levels on Hawaii Island there are currently nine stations monitoring for SO₂, two are SLAMS (Hilo and Kona) and seven (Mountain View, Pahala, Ocean View, Keeau, Naalehu, Leilani, and Waikoloa) are SPMS. All stations use FEM monitors and follow the requirements of 40 CFR Part 58, Appendices A, D, and E. Mountain View, Pahala, Ocean View, and Leilani have been operating for more than 24 months and are eligible for NAAQS comparison. The probe at Naalehu does not meet siting requirements, and Keeau and Waikoloa have operated at their permanent location for less than 24 months, therefore these stations are not currently subject to NAAQS comparisons. See Section 2.12 for discussion on site modifications and Section 3.0 for detailed location information. Figure 2-6 shows the locations of the SLAMS and SPMS discussed.

The state is also required by 40 CFR Part 51, Subpart BB, Data Requirements Rule, to characterize maximum 1-hour ambient concentrations of SO₂ through either ambient air quality monitoring or air quality modeling analysis. Currently the state has one air station, Kahe, to monitor four sources that have been identified as having SO₂ emissions data of 2,000 tons or more (see detailed site description for more information). DRR monitoring at Waiau was discontinued on December 31, 2021 with EPA approval.


Table 2-10. Minimum SO₂ Monitoring Requirements

CBSA	County	2022 Census Population (estimated)	Total SO ₂ (tons/year) 2020 NEI	PWEI ¹	DRR ² Sources Using Monitoring	# Required Monitors	# Active Monitors	# Monitors Needed
Honolulu	City & County of Honolulu	995,638	11,446	11,396	4	1	1 SLAMS 1 NCore 1 DRR	0
Maui	Maui	164,351	2,353	387	0	0	0	0

¹ According to 40 CFR 58 Appendix D, if the PWEI for a CBSA is ≥ 5,000 but < 100,000, a minimum of one SO₂ monitor is required.

² Data Requirements Rule for the 2010 1-Hour SO₂ Primary NAAQS.

Figure 2-6. SO₂ Network



2.8 NCore

The Kapolei NCore station is located in the residential, commercial, and industrial community on the southwest side of Oahu. Kapolei is the "second city" next to Honolulu with county, state, and federal agencies having established offices in the area. The NCore parameters are: NO/NO_y, trace-level SO₂, trace-level CO, O₃, PM_{10-2.5}, PM_{2.5} speciation and the meteorological parameters wind speed, wind direction, temperature, and relative humidity.

By correspondence dated October 30, 2009, EPA approved Kapolei as the NCore station and it became fully operational on January 1, 2011.

40 CFR Part 58, Appendix D, Section 5 (a) requires the state to collect and report Photochemical Assessment Monitoring Station (PAMS) measurements at each NCore site located in a CBSA with a population ≥1,000,000. The Honolulu MSA had a 2022 census population estimated at 995,638 and therefore DOH will continue to work with EPA to determine the appropriate timeline to meet the requirement to operate a PAMS.

2.9 H₂S Network

There is a geothermal facility, Puna Geothermal Ventures (PGV), located on Hawaii Island in the lower east rift zone of the Kilauea volcano. PGV is permitted to operate a 41-megawatt geothermal power plant and to conduct geothermal energy exploration and production. The pollutant of concern emitted from the facility operations is hydrogen sulfide (H₂S). The state has a one-hour H₂S standard of 25 parts per billion (ppb).

DOH established and operates a station at the Leilani Community Association Center, downwind of the facility, to monitor ambient levels of H₂S due to activities from PGV. The Leilani station which began sampling on September 18, 2020 is operated and maintained according to EPA monitoring and quality assurance requirements.

2.10 Site Closures

40 CFR Part 58, Appendix A, Section 2.1.3 states: The PQAO/monitoring organization's quality system must have adequate resources both in personnel and funding to plan, implement, assess, and report on the achievement of the requirements of this appendix and its' approved Quality Assurance Project Plan (QAPP).

To address resource challenges, the following monitoring sites were closed within the past 18 months. All were mentioned in the 2022 air monitoring network plan and formal closure requests to EPA are attached in the appendices of this year's plan:

2.10.1 Pearl City (150032004) SLAMS

Pearl City, Oahu, Hawaii

Parameters: PM₁₀, PM_{2.5} and PM_{2.5} Collocated

This site was shut down on April 6, 2022. DOH is requesting formal approval from EPA to permanently shut down this station; the request and supporting information is attached in Appendix B of this plan.

2.10.2 Kihei (150090006) SLAMS

Kihei, Maui, Hawaii Parameter: PM_{2.5}

This site was shut down on March 30, 2022. DOH is requesting formal approval from EPA to permanently shut down this station; the request and supporting information is attached in Appendix C of this plan.

2.10.3 Honaunau (150013032) SPMS

Honaunau, Hawaii Parameter: PM_{2.5}

This temporary site was shut down on January 5, 2022. DOH is requesting formal approval from EPA to permanently shut down this station; the request and supporting information is attached in Appendix F of this plan.

2.11 Site Additions

There are no plans to add any sites in the next 18 months.

2.12 Site Modifications

2.12.1 Kapolei (150030010) SLAMS/NCore

Kapolei, Oahu, Hawaii Parameters: CO and SO₂

The CO and SO₂ monitors at the Kapolei SLAMS site were discontinued on March 31, 2022 and February 28, 2022, respectively. DOH is requesting formal approval from EPA to permanently discontinue monitoring for these parameters at the Kapolei SLAMS site; the request and supporting information is attached in Appendix E of this plan.

2.12.2 Sand Island (150031004) SLAMS

Honolulu, Oahu, Hawaii

Parameters: PM_{2.5} FRM Collocated

An E-SEQ-FRM was collocated at this site for the BAM 1022 PM_{2.5} samplers in the network (Method 209). The sampler will run on a one-in-twelve day schedule with the first sample collected on April 13, 2023.

2.12.3 Niumalu (150070007) SPMS

Niumalu, Kauai, Hawaii Parameters: NO₂ and PM_{2.5}

Monitoring for NO₂ and PM_{2.5} was discontinued at the site on March 31, 2022. DOH is requesting formal approval from EPA to permanently discontinue monitoring for these parameters; the request and supporting information is attached in Appendix D of this plan.

2.12.4 Naalehu (150013033) SPMS

Naalehu Elementary School, Naalehu, Hawaii

Parameters: PM_{2.5}

On December 2, 2022, the temporary SPMS PM_{2.5} monitor that was previously located at the Naalehu Volunteer fire station was re-established at the elementary school, adjacent to the SO₂ monitor.

2.12.5 Waikoloa (150012021) SPMS

DWS Lalamilo (Parker 610), TMK 3-6-8-002-019, Waikoloa, Hawaii

Parameter: SO₂

Partly in response to the November 27, 2022 Mauna Loa eruption, SO₂ monitoring was added to this site, to provide better coverage for Hawaii Island. Sampling began on December 8, 2022.

2.12.6 Keaau (150013027) SPMS

Kamehameha Schools Hawaii, Keaau, Hawaii

Parameters: PM_{2.5} and SO₂

This SPMS station was moved to its permanent site in an open area near the Switch Gear Building on the school campus on June 30, 2022.

There are no plans to modify any of the other current sites in the next 18 months.

2.13 Summary of Network and Changes

Table 2-11 summarizes the state's 2023 network monitors and planned changes. Since it has been determined that no criteria monitors are currently required in the Maui MSA, only monitors required for the Honolulu MSA are addressed in the table. Sections 2.10 to 2.12 detail station closures, additions, and equipment or network modifications, and is summarized in Table 2-12.

As indicated in table 2-11, the monitors used for all criteria pollutants are FRM or FEM and follow the requirements of 40 CFR 58, Appendices A, C, D, E and G. Hawaii's air monitoring network meets or exceeds the minimum required monitoring for each parameter.

Table 2-11. Number of Monitors by Pollutant or Program

N/A = Not applicable

					Total	Total	Total	Meets EPA		
Pollutant/	SLAMS			No. of	in	in	Required	Required	Planned	Planned
Program	Only	SPMS	SLAMS/NCore	Collocated	MSA ^{1,2}	State ²	in MSA ¹	Minimum?	Additions	Closures
CO (FRM)	1	0	1	N/A	2	2	N/A	N/A	0	0
NO ₂ (FRM)	1	0		N/A	1	1	N/A	N/A	0	0
SO ₂ (FEM)	4	8	1	N/A	3	13	1	YES	0	0
O ₃ (FEM)	1	0	1	N/A	2	2	1	YES	0	0
NO/NO _y	N/A	N/A	1 (NCore)	N/A	1	1	1	YES	0	0
PM ₁₀ (FEM)	1	0	1	N/A	2	2	1-2	YES	0	0
PM _{2.5} (all are FEM)	2	10	1	2 FRM 1 FEM	3	13 ³	1	YES	0	0
PM _{2.5} Speciation	0	0	1 (NCore/ Supplemental Speciation)	N/A	1	1	1 (NCore)	YES	0	0
PM _{10-2.5}				N/A			1			
F IVI10-2.5	N/A	N/A	1 (NCore)		1	1	(NCore)	YES	0	0
H ₂ S	N/A	1	N/A	N/A	0	1	N/A	N/A	0	0

¹ As promulgated in 40 CFR 58 Appendix D, the minimum monitoring requirements apply to Metropolitan Statistical Areas (MSA). Currently, only the Honolulu MSA has requirements for minimum criteria pollutant monitoring.

² Total refers to the number of primary monitors only and does not count collocated monitors.

³ Eleven of the thirteen are using Method 209 and two are using Method 238.

Table 2-12. Summary of Network Changes

Site	AQS ID	Site Type	Affected Parameters	Reason for Closure/Addition/Modification
City and Count	y of Honolulu	.,,,,,,	i aramotoro	Ologaio// (dailion/incamodation
Pearl City	150032004	SLAMS	PM ₁₀ , PM _{2.5}	Site closure: This site was shut down on April 6, 2022. DOH is requesting formal approval from EPA to permanently shut down this station; the request and supporting information is attached in Appendix B of this plan.
Kapolei/ NCore	150030010	SLAMS/ NCore	CO, SO ₂	Site modification: Since trace CO and trace SO ₂ are required to be monitored at the NCore station, the CO and SO ₂ monitors at the SLAMS site were discontinued on March 31, 2022 and February 28, 2022, respectively. The formal request for closure to EPA is attached in Appendix E of this plan.
Sand Island	150031004	SLAMS	PM _{2.5} FRM collocated	Site modification: An E-SEQ-FRM was collocated at this site for the BAM 1022 PM _{2.5} samplers in the network (Method 209). The sampler will run on a one-intwelve day schedule with the first sample scheduled on April 6, 2023.
Maui County				
Kihei	150090006	SLAMS	PM _{2.5}	Site closure: This site was shut down on March 30, 2022. DOH is requesting formal approval from EPA to permanently shut down this station; the request and supporting information is attached in Appendix C of this plan.
Hawaii County			_	
Honaunau	150013032	SPMS	PM _{2.5}	Site closure: This temporary site was shut down on January 5, 2022. DOH is requesting formal approval from EPA to permanently shut down this station; the request and supporting information is attached in Appendix F of this plan.
Naalehu	150013033	SPMS	PM _{2.5}	Site modification: On December 2, 2022, the temporary SPMS PM _{2.5} monitor that was previously located at the Naalehu Volunteer fire station was re-established at the elementary school, adjacent to the SO ₂ monitor.
Waikoloa	150012021	SPMS	SO ₂	Site modification: Partly in response to the November 27, 2022 Mauna Loa eruption, SO ₂ monitoring was added to this site, to provide better coverage for Hawaii Island. Sampling began on December 8, 2022.
Keeau	150013027	SPMS	PM _{2.5} , SO ₂	Site modification: This SPMS station was moved to its permanent site in an open area near the Switch Gear Building on the school campus on June 30, 2022.
Kauai County				
Niumalu	150070007	SPMS	NO2, PM2.5	Site modification: Monitoring for NO ₂ and PM _{2.5} were discontinued at the site on March 31, 2022. DOH is requesting formal approval from EPA to permanently discontinue monitoring for these parameters; the request and supporting information is attached in Appendix D of this plan.

The operation of each monitor meets the requirements of appendices A, C, D, E and G of 40 CFR Part 58, where applicable.

3.0 Detailed Site Descriptions

The following are descriptions and photos of each station in the state's current ambient air monitoring network. The descriptions include area location, traffic, probe siting, monitor information and adherence to quality assurance.

DOH Clean Air Branch is the collecting and reporting agency for all stations and monitors operating in the state.

Table 3-1. State of Hawaii Ambient Air Monitoring Network

	<u> </u>			torning Hothronk
ID	AQS No.	Site Name	Basic Monitoring Objective(s) ¹	Parameters
DH	150031001	Honolulu	1,2	PM _{2.5} , PM ₁₀ , SO ₂ , CO
KA SLAMS/ NCore	150030010	Kapolei	1,2,3	PM _{2.5} , PM _{2.5} collocated FRM, PM ₁₀ , (PM _{10-2.5}), trace SO ₂ , NO ₂ , NO/NO _y , trace CO, O ₃ , PM _{2.5} speciation, WS, WD, RH, Ambient Temperature
SI	150031004	Sand Island	1,2	PM _{2.5} , PM _{2.5} collocated FRM, O ₃
KL	150090025	Kahului	1, 2	PM _{2.5}
NI	150070007	Niumalu	1,2,3	SO ₂
HL (SLAMS)	150011006	Hilo	1,2,3	SO ₂
HL (SPMS)	150011006	Hilo	1,2,3	PM _{2.5}
KN SLAMS)	150011012	Kona	1,2,3	SO ₂
KN (SPMS)	150011012	Kona	1,2,3	PM _{2.5} , PM _{2.5} collocated FEM
MV	150012023	Mt. View	1,2,3	PM _{2.5} , SO ₂
OV	150012020	Ocean View	1,2,3	PM _{2.5} , SO ₂
PA	150012016	Pahala	1,2,3	PM _{2.5} , SO ₂
LE	150012035	Leilani	1,3	H ₂ S, SO ₂
KK	150013028	Kailua-Kona	1,2,3	PM _{2.5}
KS	150013027	Keaau	1,2,3	PM _{2.5} , SO ₂
NA	150013033	Naalehu	1,2,3	PM _{2.5} , SO ₂
WL	150012021	Waikoloa	1,2,3	PM _{2.5} , SO ₂
KE	150034001	Kahe	1,2,3	SO ₂

¹ Basic Monitoring Objectives:

- 1) Public information
- 2) NAAQS compliance
- 3) Support research

(DH) HONOLULU							
AQS: 150031001	Type: SLAMS	County: Honolulu		MSA: Honolulu			
Address: 1250 Punchbowl St., Honolulu, HI 96813							
Latitude: 21.30758	Longitude: -157.85542		Elevation	n: 20 m MSL			

Location Description:

This station is located on the roof of the state Department of Health building in downtown Honolulu. The surrounding streets are busy thoroughfares serving the downtown area. The area includes a major hospital (Queen's Medical Center), the state capitol, other state, county, commercial and business buildings as well as residential condominiums. This station has been operating since 1972.





DH TRAFFIC DESCRIPTION			
Type of Roadway	Punchbowl	S. Beretania	Vineyard
Freeway			
Major Street or Highway	X	X	X
Distance from air intake (m)	30	122	610
Direction from air inlet	E	S	N
Composition of roadway	asphalt	asphalt	asphalt
Number of traffic lanes	5	6	6
Average daily traffic	19,800 ¹	20,100 ¹	34,800 ¹
Average vehicle speed (est. mph)	20	25	25
Traffic one way or two	2	1	2
Street parking?	No	No	No
Source: State of Hawaii Department of	f Transportation (201	6 count)	

For "Site Representativeness" in the following table:

¹Site Types:1) Located to determine the highest concentrations;

- 2) Located to measure typical concentrations in areas of high population density;
- 3) Located to determine the impact of significant sources or source categories on air quality;
- 4) Located to determine general background concentration levels;
- 5) Located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
- 6) Located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts.
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures:
 - 4) Support for air pollution research.

(DH) Honolulu continued

DH MONITOR INFORMATION (N/A = Not Appli	PM ₁₀	PM _{2.5}	SO ₂	СО
DOC/FDM ov FFM	-	3/FEM	6/FEM	1/FRM
POC/FRM or FEM	1/FEM			
Type of monitor	SLAMS	SLAMS	SLAMS	SLAMS
AQS parameter code	81102	88101	42401	42101
Manufacturer	TAPI	TAPI	Thermo	TAPI
Model no.	T640X	T640X	43iQ	T300
AQS method code	239	238	060	093
Monitoring start date	8/17/2022	1/1/2023	9/27/2019	10/15/2019
Monitoring frequency	Continuous	Continuous	Continuous	Continuous
Probe material	N/A	N/A	Glass	Glass
Residence time (sec)	N/A	N/A	14.0	8.7
Distance between collocated monitors	N/A	N/A	N/A	N/A
Analytical laboratory	N/A	N/A	N/A	N/A
Location of probe	building roof	building roof	building roof	building roof
Building dimensions (H) (m)	12	12	12	12
Horizontal distance from supporting structure (m)	9	9	9	9
Vertical distance above supporting structure (m)	2.5	2.5	1.2	1.2
Height of probe above ground (m)	14.5	14.5	13.2	13.2
Distance (m) & direction from drip line of tree(s)	24 E	24 E	27 E	27 E
Horizontal distance from edge of nearest traffic lane (m)	27	27	30	30
Horizontal distance from nearest parking lot (m)	24	24	24	24
Distance (m) & direction from obstructions on	9 ESE,	9 ESE,	9 ESE,	9 ESE
roof, vertical height above probe (m)	2.7	2.7	2.7	2.7
Distance (m) & direction from possible obstructions not on roof, vertical height (m)	N/A	N/A	N/A	N/A
Distance (m) & direction from furnace or incineration flues	234 S/SW	234 S/SW	238 S/SW	238 S/SW
Unrestricted airflow	360°	360°	360°	360°
Located in paved (P) or vegetative (V) ground?	Р	Р	Р	Р
SITE REPRESENTATIVENESS				
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Middle
Applicable NAAQS averaging time(s)	24-hr	24-hr, annual	1-hr, 3-hr, annual	1-hr, 8-hr
Sampling season	12 months	12 months	12 months	12 months
Site type ¹	2	2	2	1
Purpose of monitor ²	1, 2	1, 2	1, 2	1, 2
Suitable for comparison against the annual PM _{2.5} NAAQS?	N/A	Yes	N/A	N/A
DATA QUALITY				
Last PEP	N/A	N/A	N/A	N/A
Last NPAP (2017 NPAP done for O ₃ only in SI site)	N/A	N/A	6/27/18	6/27/18
	N/A	N/A	11/7/22	11/7/22
audit Frequency of flow rate verification (automated	N/A Monthly	N/A Monthly	11/7/22 N/A	11/7/22 N/A
audit Frequency of flow rate verification (automated PM)	Monthly	Monthly	N/A	N/A
audit Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM _{2.5})	Monthly N/A	Monthly N/A	N/A N/A	N/A N/A
audit Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM)	Monthly N/A 12/8/22	Monthly N/A N/A	N/A N/A N/A	N/A N/A N/A
audit Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb)	Monthly N/A 12/8/22 N/A	Monthly N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A
audit Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb)	Monthly N/A 12/8/22 N/A N/A	Monthly N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A
Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb) Precision & accuracy submitted to AQS	Monthly N/A 12/8/22 N/A N/A Quarterly	Monthly N/A N/A N/A N/A N/A Quarterly	N/A N/A N/A N/A N/A N/A Quarterly	N/A N/A N/A N/A N/A Quarterly
audit Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb) Precision & accuracy submitted to AQS Frequency of 1-pt. QC check (gases)	Monthly N/A 12/8/22 N/A N/A Quarterly N/A	Monthly N/A N/A N/A N/A N/A Quarterly N/A	N/A N/A N/A N/A N/A Quarterly Weekly	N/A N/A N/A N/A N/A N/A Weekly
audit Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb)	Monthly N/A 12/8/22 N/A N/A Quarterly	Monthly N/A N/A N/A N/A N/A Quarterly	N/A N/A N/A N/A N/A N/A Quarterly	N/A N/A N/A N/A N/A Quarterly

(KA) KAPOLEI SLAMS and NCORE							
AQS: 150030010 Type: SLAMS	County: Honolulu	MSA: Honolulu					
Address: 2052 Lauwiliwili St., Kapolei, HI 96707							
Latitude: 21.32374 Longitude: -158.08861	1 F	Elevation: 17.9 m MSI					

Location Description: Located in the Kapolei Business Park in the city of Kapolei, the area is a mix of business, commercial, and government activities surrounded by an ever-expanding residential community. The site is also approximately 1.25 km northeast (upwind) of the state's largest industrial park on the southwest coast of Oahu. The station has been operating as a SLAMS station since 2002. On October 30, 2009, EPA approved the Kapolei station as the state's NCore site, and in addition to the SLAMS parameters, the station began collecting the required NCore parameters on January 1, 2011. There are plans to replace the station shelters with new ones.





KA TRAFFIC DESCRIPTION		
Type of Roadway	Kalaeloa Blvd.	Lauwiliwili St.
Freeway		
Major Street or Highway	X	
Local Street or Road		X
Distance from air intake (m)	379	167
Direction from air inlet	NW	W
Composition of roadway	Asphalt	Asphalt
Number of traffic lanes	4	2
Average daily traffic	36,607 ¹	² Estimated: <5,000
Average vehicle speed (est. mph)	35	30
Traffic one way or two	2	2
Street parking?	No	Yes
¹ Source: State of Hawaii Department of	Transportation (2016) ² Estimate o	nly, no data available, local road

For "Site Representativeness" in the following table:

¹Site Types:1) located to determine the highest concentrations;

- 2) located to measure typical concentrations in areas of high population density;
- 3) located to determine the impact of significant sources or source categories on air quality;
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures;
 - 4) Support for air pollution research

	cable) PM ₁₀	PM _{2.5} Primary	PM _{2.5} Co-loc	PM _{10-2.5}
POC/FRM or FEM	3/FEM	1/FEM	2/FRM	7/FEM
Type of monitor	SLAMS/NCore	SLAMS/NCore	SLAMS/NCore	NCore
AQS parameter code	81102	88101	88101	86101
Manufacturer	TAPI	TAPI	Met One	TAPI
	T640X	T640X	E-SEQ-FRM	T640X
Model no.				
AQS method code	239	238	142	240 1/7/2022
Monitoring start date	1/7/2022	1/7/2022	9/4/21	
Monitoring frequency	Continuous	Continuous	1/3 days	Continuous
Probe material	N/A	N/A	N/A	N/A
Residence time (sec)	N/A	N/A	N/A	N/A
Manual PM instrument flow rate (liters per minute)	N/A	N/A	16.7	N/A
Distance between collocated monitors (m)	N/A	2.1	2.1	N/A
Analytical laboratory	N/A	N/A	Pace Analytical	N/A
Location of probe	shelter roof	shelter roof	shelter roof	shelter roof
Shelter dimensions (H x W x D) (m)	2.7x2.4x4.9	2.7x2.4x4.9	2.7x2.4x4.9	2.7x2.4x4.9
Horizontal distance from supporting structure (m)	N/A	N/A	N/A	N/A
Vertical distance above supporting structure (m)	2.2	2.2	1.9	2.2
Height of probe above ground (m)	4.9	4.9	4.6	4.9
Distance (m) & direction from drip line of tree(s)	17 NW	17 NW	18 NW	18 NW
Horizontal distance from edge of nearest traffic lane (m)	167	167	169	167
Horizontal distance from nearest parking lot (m)	87	87	87	87
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A	N/A	N/A	N/A
Distance (m) & direction from possible	170 E,	170 E,	170 E,	170 E,
obstructions not on roof, vertical height (m)	9	9	9	9
Distance (m) & direction from furnace or incineration flues	None	N/A	None	None
Unrestricted airflow	360°	360°	360°	360°
Located in paved (P) or vegetative (V) ground?	gravel	gravel	gravel	gravel
SITE REPRESENTATIVENESS				
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Applicable NAAQS averaging time(s)	24-hr	24-hr, annual	24-hr, annual	N/A
Sampling season	12 months	12 months	12 months	12 months
Site type ¹	2	2	QC	2
Purpose of monitor ²	1, 2	1, 2	QC	4
Suitable for comparison against the annual PM _{2.5} NAAQS?	N/A	Yes	Yes	N/A
DATA QUALITY				
Last PEP	N/A	10/12/22	N/A	N/A
Last NPAP	N/A	N/A	N/A	N/A
Date of last annual independent performance audit (CAB)	N/A	N/A	N/A	N/A
Frequency of flow rate verification (automated PM)	Monthly	Monthly	N/A	Monthly
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	Monthly	N/A
Dates of last 2 semi-annual flow rate audits (PM)	6/14/22, 12/21/22	6/14/22, 12/21/22	6/14/22, 12/21/22	6/14/22, 12/21/22
Frequency of 1-point flow rate verification (Pb)	N/A	N/A	N/A	N/A
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A	N/A	N/A
Precision & accuracy submitted to AQS	Quarterly	Quarterly	Quarterly	Quarterly
Frequency of 1-pt. QC check (gases)	N/A	N/A	N/A	N/A
Frequency of multi-point gas calibration	N/A	N/A	N/A	N/A
Annual data certification submitted	5/1/23	5/1/23	5/1/23	5/1/23
Changes in the next 18 months?	None	None	None	None

KA MONITOR INFORMATION (N/A = Not Appl	icable)		
	O ₃	NO ₂	
POC/FRM or FEM	1/FRM	1/FRM	
Type of monitor	SLAMS/NCore	SLAMS	
AQS parameter code	44201	42602	
Manufacturer	Thermo	TAPI	
Model no.	49i	T500U	
AQS method code	047	212	
Monitoring start date	1/9/2014	10/5/2006	
Monitoring start date Monitoring frequency	Continuous	Continuous	
Probe material	Teflon	Teflon	
Residence time (sec)	2.8	3.4	
Distance between collocated monitors (m)	N/A	N/A	
	N/A		
Analytical laboratory		N/A	
Location of probe	shelter roof	shelter roof	
Shelter dimensions (H x W x D) (m)	2.7x2.4x4.9	2.7x2.4x4.9	<u> </u>
Horizontal distance from supporting structure (m)	N/A	N/A	
Vertical distance above supporting structure (m)	1.1	1.1	
Height of probe above ground (m)	3.8	3.8	
Distance (m) & direction from drip line of tree(s)	12 N	12 N	
Horizontal distance from edge of nearest traffic lane (m)	162	167	
Horizontal distance from nearest parking lot (m)	82	87	
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A	N/A	
Distance (m) & direction from possible	165 E,	170 E,	
obstructions not on roof, vertical height (m)	9	9	
Distance (m) & direction from furnace or incineration flues	None	None	
Unrestricted airflow	360°	360°	
Located in paved (P) or vegetative (V) ground?	gravel	gravel	
SITE REPRESENTATIVENESS	gravor	giavoi	
Spatial scale	Neighborhood	Neighborhood	
Applicable NAAQS averaging time(s)	8-hr	1-hr, annual	
Sampling season	12 months	12 months	
Site type ¹		2	
	2		
Purpose of monitor ²	1, 2	1, 2	
Suitable for comparison against the annual PM _{2.5} NAAQS?	N/A	N/A	
DATA QUALITY			
Last PEP	N/A	N/A	
Last NPAP	6/23/21	6/23/21	
Date of last annual independent performance audit (CAB)	12/21/22	12/16/22	
Frequency of flow rate verification (automated PM)	N/A	N/A	
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (PM)	N/A	N/A	
Frequency of 1-point flow rate verification (Pb)	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A	
Precision & accuracy submitted to AQS	Quarterly	Quarterly	
Frequency of 1-pt. QC check (gases)	14 days	Weekly	
	•	6 months	
Frequency of multi-point gas calibration Annual data certification submitted	6 months 5/1/23	5/1/23	
Changes in the next 18 months?	None	None	

KA MONITOR INFORMATION (N/A = Not Appli		Tross SO	NO/NO:	DM Cons
200/2014	Trace CO	Trace SO ₂	NO/NOy	PM _{2.5} Spec.
POC/FRM or FEM	2/FRM	2/FEM	1/FRM	N/A
Type of monitor	SLAMS/NCore	SLAMS/NCore	NCore	NCore/Supp. Speciation
AQS parameter code	42101	42401	42601/42600	Various
Manufacturer	API	API	API	Met-One/URG
Model no.	M300EU	M100EU	T200U	SASS/3000N
AQS method code	093	600	099	811/136
Monitoring start date	9/30/2014	1/1/2011	1/14/2016	7/24/2019
Monitoring frequency	Continuous	Continuous	Continuous	1/3 days
Probe material	Teflon	Teflon	Teflon	N/A
Residence time (sec)	14.7	16.1	13.2	N/A
Distance between collocated monitors	N/A	N/A	N/A	N/A
Analytical laboratory	N/A	N/A	N/A	EPA contract
Location of probe	shelter roof	shelter roof	shelter roof	shelter roof
Shelter dimensions (H x W x D) (m)	4 x 2.4 x 5	4 x 2.4 x 5	4 x 2.4 x 5	4 x 2.4 x 5
Horizontal distance from supporting structure (m)	N/A	N/A	N/A	N/A
Vertical distance above supporting structure (m)	1	1	1	1.7/1.6
Height of probe above ground (m)	5	5	5	5.7/5.6
Distance (m) & direction from drip line of tree(s)	12 N	12 N	12 N	13N/11N
Horizontal distance from edge of nearest traffic				
lane (m)	162	162	162	165
Horizontal distance from nearest parking lot (m)	82	82	82	85
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A	N/A	N/A	N/A
Distance (m) & direction from possible	165 E,	165 E,	165 E,	168 E,
obstructions not on roof, vertical height (m)	9	9	9	9
Distance (m) & direction from furnace or	N/A	N/A	N/A	N/A
incineration flues	360°			
Unrestricted airflow		360°	360°	360°
Located in paved (P) or vegetative (V) ground?	gravel	gravel	gravel	gravel
SITE REPRESENTATIVENESS	Market and a set	Nie Selek enderend	Ni a Carlo la carlo a carl	N I a Carlo la carlo ca cal
Spatial scale	Neighborhood	Neighborhood	Neighborhood	Neighborhood
Applicable NAAQS averaging time(s)	1-hr; 8-hr	1-hr; 3-hr; annual	N/A	N/A
Sampling season	12 months	12 months	12 months	12 months
Site type ¹	2	2	2	2
Purpose of monitor ²	1,2,4	1,2,4	4	4
Suitable for comparison against the annual PM _{2.5} NAAQS?	N/A	N/A	N/A	N/A
DATA QUALITY				
Last PEP	N/A	N/A	N/A	N/A
Last NPAP	6/23/21	6/23/21	6/23/21	N/A
Date of last annual independent performance audit (CAB)	12/23/22	12/23/22	Not conducted	N/A
Frequency of flow rate verification (automated PM)	N/A	N/A	N/A	N/A
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	N/A	Monthly
Dates of last 2 semi-annual flow rate audits (manual PM _{2.5})	N/A	N/A	N/A	6/14/22, 12/21/22
Frequency of 1-point flow rate verification (Pb)	N/A	N/A	N/A	N/A
	N/A	N/A N/A	N/A	N/A
Dates of last 2 semi annual flow rate audita (Dh)	IN/A		Quarterly	Quarterly
Dates of last 2 semi-annual flow rate audits (Pb)	Quartarly			
Precision & accuracy submitted to AQS	Quarterly	Quarterly	-	
Precision & accuracy submitted to AQS Frequency of 1-pt. QC check (gases)	14 days	14 days	14 days	N/A
Precision & accuracy submitted to AQS		•	-	

KA MONITOR INFORMATION (N/A = Not Appli		\A/O	N/D	A T
DOO/FDM FEM	RH	WS	WD	AT
POC/FRM or FEM	POC 1	POC 1	POC 1	POC 1
Type of monitor	NCore	NCore	NCore	NCore
AQS parameter code	62201	61103	61104	62101
Manufacturer	RM Young	RM Young	RM Young	RM Young
Model no.	05103VP	05103VP	05103VP	05103VP
AQS method code	014	020	020	020
Monitoring start date	1/1/2011	1/1/2011	1/1/2011	1/1/2011
Monitoring frequency	Continuous	Continuous	Continuous	Continuous
Probe material	N/A	N/A	N/A	N/A
Residence time (sec)	N/A	N/A	N/A	N/A
Distance between collocated monitors	N/A	N/A	N/A	N/A
Analytical laboratory	N/A	N/A	N/A	N/A
Location of probe	10m tower	10m tower	10m tower	10m tower
Shelter dimensions (H x W x D) (m)	4 x 2.4 x 5			
Horizontal distance from supporting structure (m)	N/A	N/A	N/A	N/A
Vertical distance above supporting structure (m)	N/A	N/A	N/A	N/A
Height of probe above ground (m)	N/A	N/A	N/A	N/A
Distance (m) & direction from drip line of tree(s)	N/A	N/A	N/A	N/A
Horizontal distance from edge of nearest traffic lane (m)	N/A	N/A	N/A	N/A
Horizontal distance from nearest parking lot (m)	N/A	N/A	N/A	N/A
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A	N/A	N/A	N/A
Distance (m) & direction from possible obstructions not on roof, vertical height (m)	N/A	N/A	N/A	N/A
Distance (m) & direction from furnace or incineration flues	N/A	N/A	N/A	N/A
Unrestricted airflow	360°	360°	360°	360°
Located in paved (P) or vegetative (V) ground?	gravel	gravel	gravel	gravel
SITE REPRESENTATIVENESS				
Spatial scale	N/A	N/A	N/A	N/A
Applicable NAAQS averaging time(s)	N/A	N/A	N/A	N/A
Sampling season	12 months	12 months	12 months	12 months
Site type ¹	N/A	N/A	N/A	N/A
Purpose of monitor ²	N/A	N/A	N/A	N/A
Suitable for comparison against the annual PM _{2.5} NAAQS?	N/A	N/A	N/A	N/A
DATA QUALITY				
Last PEP	N/A	N/A	N/A	N/A
Last NPAP	N/A	N/A	N/A	N/A
Date of last annual independent performance audit (CAB)	12/21/22	12/21/22	12/21/22	12/21/22
Frequency of flow rate verification (automated PM)	N/A	N/A	N/A	N/A
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	N/A	N/A
Dates of last 2 semi-annual flow rate audits (manual PM _{2.5})	N/A	N/A	N/A	N/A
Frequency of 1-point flow rate verification (Pb)	N/A	N/A	N/A	N/A
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A	N/A	N/A
Precision & accuracy submitted to AQS	N/A	N/A	N/A	N/A
Frequency of 1-pt. QC check (gases)	N/A	N/A	N/A	N/A
Frequency of multi-point gas calibration	N/A	N/A	N/A	N/A
Annual data certification submitted	5/1/23	5/1/23	5/1/23	5/1/23
Changes in the next 18 months?	None	None	None	None

(SI) SAND ISLAND						
AQS: 150031004	Type: SLAMS	County: Honolulu		MSA: Honolulu		
Address: 1039 Sand Island Parkway, Honolulu, HI 96819						
Latitude: 21.30384	Longitude: -157.87117		Elevation:	5.3 m MSL		

Location Description:

Station is located in the University of Hawaii's Anuenue Fisheries near the entrance to the Sand Island Recreational Area. Sand Island is downwind of downtown Honolulu, across from Honolulu Harbor. This station has been operating since 1980.





SI TRAFFIC DESCRIPTION				
Type of Roadway	Type of Roadway Sand Island Parkway			
Freeway				
Major Street or Highway	X			
Local Street or Road				
Distance from air intake (m)	37			
Direction from air inlet	W			
Composition of roadway	asphalt			
Number of traffic lanes	2			
Average daily traffic	14,000 ¹			
Average vehicle speed (est. mph)	30			
Traffic one way or two	2			
Street parking?	No			
¹ Source: State of Hawaii Department of Transportation (2016 count)				

For "Site Representativeness" in the following table:

¹Site Types:1) located to determine the highest concentrations;

- 2) located to measure typical concentrations in areas of high population density;
- located to determine the impact of significant sources or source categories on air quality:
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures;
 - 4) Support for air pollution research

(SI) Sand Island continued

(SI) Sand Island continued SI MONITOR INFORMATION (N/A = Not Applicable)				
(тот фр	PM _{2.5}	O ₃	PM _{2.5} Co-loc	
POC/FRM or FEM	2/FEM	2/FRM	1/FRM	
Type of monitor	SLAMS	SLAMS	SLAMS/NCore	
AQS parameter code	88101	44201	88101	
Manufacturer	Met One	Thermo	BGI	
Model no.	BAM1022	49iQ	E-SEQ-FRM	
AQS method code	209	047	142	
Monitoring start date	2/13/2019	1/1/1980	4/6/23	
Monitoring frequency	Continuous	Continuous	1/12 days	
Probe material	N/A	Glass	N/A	
Residence time (sec)	N/A	1.8	N/A	
Distance between collocated monitors	2	N/A	2	
Manual PM instrument flow rate (liters per minute)	N/A	N/A	16.7	
Analytical laboratory	N/A	N/A	Pace Analytical	
_ocation of probe	shelter roof	shelter roof	shelter roof	
Shelter dimensions (H x W x D) (m)	2.5x2.5x4.9	2.5x2.5x4.9	2.5x2.5x4.9	
Horizontal distance from supporting structure (m)	N/A	N/A	N/A	
Vertical distance above supporting structure (m)	2.2	1.1	2.2	
Height of probe above ground (m)	4.7	3.6	4.7	
Distance (m) & direction from drip line of tree(s)	15 E	15 E	15 E	
Horizontal distance from edge of nearest traffic	15 E	10 E	15 E	
ane (m)	37	37	37	
Horizontal distance from nearest parking lot (m)	40	40	40	
Distance (m) & direction from obstructions on roof,			-	
vertical height above probe (m)	N/A	N/A	N/A	
Distance (m) & direction from possible obstructions	14 N,	14 N,	14 N,	
not on roof, vertical height (m)	5.5	5.5	5.5	
Distance (m) & direction from furnace or	N/A	N/A	N/A	
ncineration flues	-			
Unrestricted airflow	360°	360°	360°	
Located in paved (P) or vegetative (V) ground?	gravel	gravel	gravel	
SITE REPRESENTATIVENESS				
Spatial scale	Neighborhood	Neighborhood	Neighborhood	
Applicable NAAQS averaging time(s)	24-hr, annual	8-hr	24-hr, annual	
Sampling season	12 months	12 months	12 months	
Site type ¹	5	1	QC	
Purpose of monitor ²	1, 2	1, 2, 3	QC	
Suitable for comparison against the annual PM _{2.5}	Υ	N/A	Υ	
DATA QUALITY				
_ast PEP	10/13/22	N/A	N/A	
_ast NPAP	N/A	6/24/21	N/A	
Date of last annual independent performance audit (CAB)	N/A	12/15/22	Newly installed	
Frequency of flow rate verification (automated PM)	Monthly	N/A	N/A	
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	Monthly	
Dates of last 2 semi-annual flow rate audits (PM)	6/14/22, 12/15/22	N/A	Newly installed	
requency of 1-point flow rate verification (Pb)	N/A	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A	N/A	
Precision & accuracy submitted to AQS	Quarterly	Quarterly	Quarterly	
Frequency of 1-pt. QC check (gases)	N/A	Weekly	N/A	
Frequency of multi-point gas calibration	N/A	6 months	N/A	
Annual data certification submitted	5/1/23	5/1/23	N/A	
Changes in the next 18 months?	None	None	None	

(KL) KAHULUI				
AQS: 150090025	Type: SPMS	County: Maui		MSA: Maui
Address: TMK 2-3-	8-007-153 Maui Lani Parkway,	Kahului, HI 96732		
Latitude: 20.869444	Longitude: -156.492417	,	Elevation	: 55.5 m MSL

This station is located off of Maui Lani Parkway in Kahului and surrounded primarily by residential land. The station was established to measure typical concentrations of air pollutants in areas of high population density. This station began monitoring for PM_{2.5} on January 13, 2015.





KL TRAFFIC DESCRIPTION	
Type of Roadway	Maui Lani Parkway
Freeway	
Major Street or Highway	
Local Street or Road	X
Distance from air intake (m)	80
Direction from air inlet	S
Composition of roadway	asphalt
Number of traffic lanes	2
Average daily traffic	<1500 ¹
Average vehicle speed (est. mph)	30
Traffic one way or two	2
Street parking?	No
¹ Estimate only, no data available, local	road

For "Site Representativeness" in the following table:

- 2) located to measure typical concentrations in areas of high population density;
- located to determine the impact of significant sources or source categories on air quality:
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures;
 - 4) Support for air pollution research

(KL) Kahului continued

PM _{2.5} 1/FEM			
1/FEM			
SPMS			
88101			
Met One			
stand-alone shelter on ground			
N/A			
N/A			
N/A			
2.7			
15.2 NE			
70			
N/A			
N/A			
15.2 NE, 6.1			
N/A			
360°			
'			
Neighborhood			
res			
N/A			
N/A			
Monthly			
N/A			
3/30/22, 12/14/22			
N/A			
N/A			
•			
_	+	+	
	BAM 1022 209 2/11/2019 Continuous N/A N/A N/A N/A N/A Stand-alone shelter on ground N/A N/A N/A 2.7 15.2 NE 70 N/A N/A N/A 15.2 NE, 6.1 N/A 360° P Neighborhood 24-hr, annual 12 months 2, 3 1, 2, 4 Yes 10/23/19 N/A N/A Monthly N/A 3/30/22, 12/14/22 N/A	BAM 1022 209 2/11/2019 Continuous N/A N/A N/A N/A N/A N/A N/A N/A Stand-alone shelter on ground N/A N/A N/A N/A N/A N/A N/A 15.2 NE 70 N/A N/A 15.2 NE, 6.1 N/A 360° P Neighborhood 24-hr, annual 12 months 2, 3 1, 2, 4 Yes 10/23/19 N/A N/A N/A N/A N/A N/A N/A N/A Quarterly N/A	BAM 1022 209 2/11/2019 Continuous N/A N/A N/A N/A N/A N/A Stand-alone shelter on ground N/A N/A N/A N/A N/A N/A N/A N/A 15.2 NE 70 N/A N/A N/A N/A 15.2 NE, 6.1 N/A N/A 360° P Neighborhood 24-hr, annual 12 months 2, 3 1, 2, 4 Yes 10/23/19 N/A

(NI) N	IIUMALU	
AQS: 150070007 Type: SPMS	County: Kauai	MSA: Not in an MSA
Address: 2342 Hulemalu Rd., Lihue, HI 96766		
Latitude: 21.9495 Longitude: -159.365	Ele	evation: 11 m MSL

Located on a private residential property approximately 1 mile downwind of Nawiliwili Harbor, this station was established to monitor the impact of cruise ship emissions on nearby communities. With the lower ECA fuel sulfur requirements for cruise ships, this station provides information on the effects of lowered fuel sulfur on ambient SO₂. This station began operating in April 2011.





NI TRAFFIC DESCRIPTION		
Type of Roadway	Hulemalu Rd.	Niumalu Rd.
Freeway		
Major Street or Highway		
Local Street or Road	X	X
Distance from air intake (m)	44.4	309.7
Direction from air inlet	NW	NE
Composition of roadway	asphalt	Asphalt
Number of traffic lanes	2	1
Average daily traffic	100 ¹	30 ¹
Average vehicle speed (est. mph)	15	20
Traffic one way or two	2	2
Street parking?	No	No
¹ Estimated only, no data available, road	ls are for local residential access	

For "Site Representativeness" in the following table:

- 2) located to measure typical concentrations in areas of high population density;
- 3) located to determine the impact of significant sources or source categories on air quality;
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures:
 - 4) Support for air pollution research

(NI) Niumalu continued

POC/FRM or FEM	(NI) Niumalu continued NI MONITOR INFORMATION (N/A = Not Appli	cable)		
POC/FRM or FEM	THE MODELL ON THE CHARACTER (MA - NOT APPH	1		
Type of monitor	POC/FRM or FFM			
AGS parameter code #AGN parameter code #AGN method code #AGN me				
Manufacturer TECO Model no. 43iQ ACS method code 060 Monitoring start date 8/29/2019 Monitoring requency Continuous Probe material Glass Residence time (sec) 13.2 Distance between collocated monitors N/A Analytical laboratory N/A Location of probe shelter roof Shelter dimensions (H x W x D) (m) 3x5x2.4 Horizontal distance from supporting structure (m) N/A Vertical distance above supporting structure (m) 1 Height of probe above ground (m) 4 Distance (m) & direction from drip line of tree(s) 17.8 ESE Horizontal distance from edge of nearest traffic lane (m) 44.4 Iane (m) 44.4.4 Horizontal distance from nearest parking lot (m) N/A Distance (m) & direction from between control or	* *			
Model no. 43IQ AGS method code 660 Monitoring start date 8/29/2019 Monitoring frequency Continuous Probe material Glass Residence time (sec) 13.2 Distance between collocated monitors N/A Analytical laboratory N/A Location of probe shelter roof Shetter dimensions (H x W x D) (m) 3x5x2.4 Horizontal distance above supporting structure (m) 1 Height of probe above ground (m) 4 Vertical distance above supporting structure (m) 1 Height of probe above ground (m) 4 Distance (m) & direction from drip line of tree(s) 17.8 ESE Horizontal distance from edge of nearest traffic lane (m) 44.4 Individual distance from earest parking lot (m) N/A Distance (m) & direction from possible obstructions on roof, vertical height above probe (m) N/A Distance (m) & direction from possible obstructions not on vertical height (m) 7.2 Distance (m) & direction from possible obstructions not only vertical height (m) 7.2 Distance (m) & direction from possible obstructions (manufactu	•	-		
AGS method code Monitoring start date Monitoring requency Continuous Probe material Residence time (sec) Distance between collocated monitors N/A Analytical laboratory Location of probe Shelter dimensions (H x W x D) (m) Vertical distance shove supporting structure (m) Vertical distance above supporting structure (m) Vertical distance above ground (m) Distance (m) & direction from drip line of tree(s) Horizontal distance from edge of nearest traffic lane (m) Horizontal distance from edge of nearest traffic lane (m) Horizontal distance from bestructions on roof, vertical height above probe (m) Distance (m) & direction from bestructions on roof, vertical height above probe (m) Distance (m) & direction from furnace or incineration liues Unrestricted airliow Located in paved (P) or vegetative (V) ground? STE REPRESENTATIVENESS Spatial scale Neighborhood Applicable NAAQS averaging time(s) 1-hr, 3-hr, annual Sampling season 1 2 months Site type 1 3 Purpose of monitor 3 N/A DATA QUALITY Last PEP Last NPAP Data of last annual independent performance audit (CAB) Frequency of flow rate verification (gutomated PM) Frequency of flow rate verification (manual PM _{2.5}) N/A Dates of last 2 semi-annual flow rate audits (Pb) N/A Precision & accuracy submitted to AQS Quarterly Frequency of 1-pcin flow rate verification (Pb) N/A Precision & accuracy submitted to AQS Quarterly Frequency of 1-pcin flow rate verification (Pb) N/A Precision & accuracy submitted to AQS Quarterly Frequency of 1-pcin flow rate verification (Pb) N/A Precision & accuracy submitted of AQS Quarterly Frequency of 1-pcin flow rate verification (Pb) N/A Precision & accuracy submitted of AQS Quarterly Frequency of 1-pcin flow rate verification of Monthis Frequency of 1-pcin flow rate verification of Monthis Frequency of 1-p				
Monitoring start date 8/29/2019 Monitoring frequency Continuous Probe material Glass Residence time (sec) 13.2 Distance between collocated monitors N/A Analytical laboratory N/A Location of probe shelter of Shelter dimensions (H x W x D) (m) 3x5x2.4 Horizontal distance from supporting structure (m) N/A Vertical distance from supporting structure (m) 1 Helight of probe above ground (m) 4 Vertical distance from edge of nearest traffic lane (m) 4.4 Horizontal distance from edge of nearest traffic lane (m) 4.4.4 Horizontal distance from nearest parking lot (m) N/A Distance (m) & direction from obstructions on roof, vertical height above probe (m) N/A Distance (m) & direction from obstructions on roof, vertical height above probe (m) 7.2 Distance (m) & direction from furnace or incineration flues N/A Located in paved (P) or vegetative (V) ground? Y STIE REPRESENTATIVENESS Neighborhood Spatial scale Neighborhood Applicable NAGS averaging time(s)				
Monitoring frequency				
Probe material Glass Residence time (sec) 13.2				
Residence time (sec) 13.2				
Distance between collocated monitors N/A Analytical laboratory N/A Analytical laboratory N/A Shelter froof Shelter dimensions (H x W x D) (m) Horizontal distance from supporting structure (m) Vertical distance above supporting structure (m) Vertical distance above supporting structure (m) Height of probe above ground (m) 1 Height of probe above ground (m) 1 Horizontal distance from edge of nearest traffic lane (m) Horizontal distance from nearest parking lot (m) Distance (m) & direction from obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from furnace or incineration flues Uncrestricted airflow Located in paved (P) or vegetative (V) ground? V SITE REPRESENTATIVENESS Spatial scale Applicable NAAQS averaging time(s) Applicable NAAQS averaging time(s) Applicable for comparison against the annual PM2s N/A NAAQS? Purpose of monitor² 1, 2, 4 Suitable for comparison against the annual PM2s NAAQS? DATA QUALITY Last PEP Last NPAP Date of last annual independent performance audit (CAB) C(CAB) Frequency of flow rate verification (automated PM) N/A Prequency of flow rate verification (manual PM2s) N/A Dates of last 2 semi-annual flow rate audits (PM) Prequency of 1-point flow rate verification (Pb) N/A Dates of last 2 semi-annual flow rate audits (PM) Prequency of 1-point flow rate verification (Pb) N/A Precision & accuracy submitted to AOS Quarterly Frequency of 1-point Gov calibration Annual data certification submitted 5/1/23				
Analytical laboratory	. ,			
Location of probe Shelter dimensions (H x W x D) (m) N/A Vertical distance above supporting structure (m) Vertical distance above supporting structure (m) Height of probe above ground (m) 4 Bistance (m) Substance (m) & direction from drip line of tree(s) Introduction distance from edge of nearest traffic lane (m) Vertical height above probe (m) Distance (m) & direction from obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions on roof, vertical height (m) Distance (m) & direction from possible obstructions on roof, vertical height (m) Distance (m) & direction from furnace or locations on roof, vertical height (m) Distance (m) & direction from furnace or locations on roof, vertical height (m) Distance (m) & direction from furnace or locations on roof, vertical height (m) Distance (m) & direction from furnace or locations on roof, vertical height (m) Distance (m) & direction from furnace or locations on roof, vertical height (m) Distance (m) & direction from furnace or locations on roof, vertical height (m) Distance (m) & direction from possible obstructions on roof, vertical height (m) Distance (m) & direction from possible obstructions on roof, vertical height (m) Distance (m) & direction from possible obstructions on roof, vertical height (m) Distance (m) & direction from possible obstructions on roof, vertical height (m) Distance (m) & direction from possible obstructions on roof, vertical height (m) Distance (m) & direction from roof, vertical height (m) Distance (m) & direction from roof, vertical height (m) Distance (m) & direction from roof, vertical height (m) Distance (m) & direction from roof, vertical height (m) Distance (m) & direction from roof, vertical height (m) Distance (m) & direction from roof, vertical height (m) Distance (m) & direction from roof, vertical height (m) Distance (m) & direction from roof,				
Shelter dimensions (H x W x D) (m) Horizontal distance from supporting structure (m) Vertical distance from supporting structure (m) Height of probe above ground (m) 1 Height of probe above ground (m) A Distance (m) & direction from drip line of tree(s) Horizontal distance from edge of nearest traffic lane (m) Horizontal distance from nearest parking lot (m) Distance (m) & direction from obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from possible obstructions 14.6 W, not on roof, vertical height (m) 7.2 Distance (m) & direction from furnace or incineration flues Unrestricted airflow 360° Unrestricted airflow 360° Located in paved (P) or vegetative (V) ground? V STE REPRESENTATIVENESS Spatial scale Neighborhood Applicable NAAQS averaging time(s) Sampling season 12 months Site type¹ 3 a Purpose of monitor² N/A NAAQS? DATA QUALITY Last PEP N/A Last NPAP 6/19/18 DATA QUALITY Last PEP N/A Last NPAP 6/19/18 DATA GUALITY Last Septimenual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Frequency of flow rate verification (automated PM) Frequency of flow rate verification (nanual PM _{2.5}) N/A Precision & accuracy submitted to AQS Quarterly Frequency of 1-pc int flow rate audits (Pb) N/A Annual data certification submitted 5/11/23				
Horizontal distance from supporting structure (m)				
Vertical distance above supporting structure (m) Height of probe above ground (m) Stratene (m) Horizontal distance from edge of nearest traffic lane (m) Horizontal distance from edge of nearest traffic lane (m) Horizontal distance from nearest parking lot (m) Distance (m) & direction from obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions not of, vertical height (m) Distance (m) & direction from possible obstructions not of, vertical height (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from furnace or incineration flues Unrestricted airflow Located in paved (P) or vegetative (V) ground? V SITE REPRESENTATIVENESS Spatial scale Neighborhood Applicable NAAQS averaging time(s) 1-hr, 3-hr, annual Sampling season 12 months Site type¹ 3				
Height of probe above ground (m) Distance (m) & direction from drip line of tree(s) Horizontal distance from edge of nearest traffic lane (m) Horizontal distance from nearest parking lot (m) Distance (m) & direction from obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions not nor loof, vertical height above probe (m) Distance (m) & direction from possible obstructions not nor loof, vertical height above probe (m) Distance (m) & direction from possible obstructions not nor loof, vertical height (m) T.2 Distance (m) & direction from furnace or incineration flues Unrestricted airflow 360° Unrest				
Distance (m) & direction from drip line of tree(s) Horizontal distance from edge of nearest traffic lane (m) Horizontal distance from edge of nearest traffic lane (m) Horizontal distance from nearest parking lot (m) Distance (m) & direction from obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from form form form form form form form	•			
Horizontal distance from edge of nearest traffic lane (m) Horizontal distance from nearest parking lot (m) Distance (m) & direction from obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from furnace or incineration flues Unrestricted airflow Soo° Located in paved (P) or vegetative (V) ground? STER REPRESENTATIVENESS Spatial scale Applicable NAAQS averaging time(s) Site type¹ 3 Purpose of monitor² 11, 2, 4 Suitable for comparison against the annual PM2.5 N/A NAAQS? DATA QUALITY Last PEP Last PEP Abra G/19/18 Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM2.5) Dates of last 2 semi-annual flow rate audits (PM) Precision & accuracy submitted to AQS Prequency of 1-point flow rate audits (Pb) Precision & accuracy submitted to AQS Annual data certification submitted		-		
Iane (m)	()			
Horizontal distance from nearest parking lot (m) Distance (m) & direction from obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from furnace or N/A Incineration flues Unrestricted airflow Located in paved (P) or vegetative (V) ground? STE REPRESENTATIVENESS Spatial scale Neighborhood Applicable NAAQS averaging time(s) Applicable NAAQS averaging time(s) Site type¹ 3 Purpose of monitor² 1, 2, 4 Suitable for comparison against the annual PM2.5 NAAQS? DATA QUALITY Last PEP Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM2.5) Dates of last 2 semi-annual flow rate audits (PM) Precision & accuracy submitted to AQS Prequency of -p-t. QC check (gases) Frequency of monting scalibration Annual data certification submitted PN/A Frequency of multi-point gas calibration Annual data certification submitted Follows PI/A N/A PA/A		44.4		
Distance (m) & direction from obstructions on roof, vertical height above probe (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from furnace or incinceration flues Unrestricted airflow Unrestricted airflow Unrestricted airflow Uncated in paved (P) or vegetative (V) ground? STIE REPRESENTATIVENES Spatial scale Neighborhood Applicable NAAQS averaging time(s) In-hr, 3-hr, annual Sampling season In-hr, 3-hr, annual In-	3 7	N/A	1	
Distance (m) & direction from possible obstructions not on roof, vertical height (m) Distance (m) & direction from furnace or incineration flues Unrestricted airflow Located in paved (P) or vegetative (V) ground? SITE REPRESENTATIVENESS Spatial scale Applicable NAAQS averaging time(s) Sampling season Site type¹ 3 Purpose of monitor² Suitable for comparison against the annual PM2.5 NAAQS? DATA QUALITY Last PEP Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Frequency of 1-point flow rate audits (PM) Precision & accuracy submitted to AQS Quarterly Frequency of 1-pt. QC check (gases) Annual data certification submitted 14.6 W, 7.2 14.6 W, 7.2 N/A N/A 14.6 W, 7.2 N/A N/A N/A 15.9 N/A Neighborhood 1-point flow rate audits (Pb) N/A N/A N/A N/A N/A N/A N/A N/A	Distance (m) & direction from obstructions on roof,	N/A		
not on roof, vertical height (m) Distance (m) & direction from furnace or incineration flues Unrestricted airflow Located in paved (P) or vegetative (V) ground? SITE REPRESENTATIVENESS Spatial scale Applicable NAAQS averaging time(s) Sampling season 12 months Site type¹ 3 Purpose of monitor² Suitable for comparison against the annual PM2.5 NAAQS? DATA QUALITY Last PEP Abra Date of last annual independent performance audit (CAB) Prequency of flow rate verification (automated PM) Prequency of flow rate verification (manual PM2.5) NAA Dates of last 2 semi-annual flow rate audits (PM) Prequency of 1-point flow rate audits (Pb) Dates of last 2 semi-annual flow rate audits (Pb) Prequency of 1-point flow rate vale incincing a control of months Prequency of 1-point flow rate audits (Pb) Prequency of 1-point gas calibration Annual data certification submitted Annual data certification submitted Annual data certification submitted 7.2 N/A N/A N/A N/A N/A N/A N/A Precipiency of multi-point gas calibration 6 months Annual data certification submitted		14.6 W.		
incineration flues Unrestricted airflow Located in paved (P) or vegetative (V) ground? STIE REPRESENTATIVENESS Spatial scale Applicable NAAQS averaging time(s) Sampling season 12 months Site type¹ 3 Purpose of monitor² 1, 2, 4 Suitable for comparison against the annual PM2.5 NAAQS? DATA QUALITY Last PEP Last NPAP Date of last annual independent performance audit (CAB) Prequency of flow rate verification (automated PM) Prequency of flow rate verification (manual PM2.5) N/A Dates of last 2 semi-annual flow rate audits (PM) Prequency of 1-point flow rate verification (Pb) N/A Precision & accuracy submitted to AQS Prequency of formulti-point gas calibration Annual data certification submitted N/A Prequency of multi-point gas calibration Annual data certification submitted N/A PISTAGE ASSOCIATION Safe Prequency of 1-point gas calibration Annual data certification submitted	not on roof, vertical height (m)			
Unrestricted airflow Located in paved (P) or vegetative (V) ground? V SITE REPRESENTATIVENESS Spatial scale Neighborhood Applicable NAAQS averaging time(s) 1-hr, 3-hr, annual Sampling season 12 months Site type¹ 3 Purpose of monitor² 1, 2, 4 Suitable for comparison against the annual PM25 NAAQS? DATA QUALITY Last PEP N/A Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Prequency of flow rate verification (manual PM2.5) N/A Prequency of 1-point flow rate verification (Pb) N/A Precision & accuracy submitted to AQS Prequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted Selection Neighborhood Neighborhood Neighborhood NA N/A NA	Distance (m) & direction from furnace or	N/A		
SITE REPRESENTATIVENESS Spatial scale Applicable NAAQS averaging time(s) Sampling season 12 months Site type¹ 3 Purpose of monitor² Suitable for comparison against the annual PM2.5 NAAQS? DATA QUALITY Last PEP Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM2.5) Dates of last 2 semi-annual flow rate audits (PM) Dates of last 2 semi-annual flow rate audits (PM) Dates of last 2 semi-annual flow rate audits (Pb) Dates of last 2 semi-annual flow rate audits (Pb) Precision & accuracy submitted to AQS Frequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted Neighborhood 1-thr, 3-hr, annual	Unrestricted airflow	360°		
SITE REPRESENTATIVENESS Spatial scale Applicable NAAQS averaging time(s) Sampling season 12 months Site type¹ 3 Purpose of monitor² 1, 2, 4 Suitable for comparison against the annual PM2.5 NAAQS? DATA QUALITY Last PEP Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Frequency of 1-point flow rate audits (PM) Dates of last 2 semi-annual flow rate audits (PM) Precision & accuracy submitted to AQS Frequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted Neighborhood 1-hr, 3-hr, annual NA N/A N/A N/A N/A N/A N/A Dates of last 2 semi-annual flow rate audits (PM) N/A Precision & accuracy submitted to AQS Quarterly Frequency of 1-pt. QC check (gases) Weekly Frequency of multi-point gas calibration Annual data certification submitted	Located in paved (P) or vegetative (V) ground?	V		
Applicable NAAQS averaging time(s) Sampling season 12 months Site type¹ 3 Purpose of monitor² 1, 2, 4 Suitable for comparison against the annual PM2.5 N/A NAAQS? DATA QUALITY Last PEP Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Dates of last 2 semi-annual flow rate audits (PM) Pates of last 2 semi-annual flow rate audits (PM) Dates of last 2 semi-annual flow rate audits (PM) Precision & accuracy submitted to AQS Frequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted	SITE REPRESENTATIVENESS			
Applicable NAAQS averaging time(s) Sampling season 12 months Site type¹ 3 Purpose of monitor² 1, 2, 4 Suitable for comparison against the annual PM2.5 N/A NAAQS? DATA QUALITY Last PEP Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Dates of last 2 semi-annual flow rate audits (PM) Pates of last 2 semi-annual flow rate audits (PM) Dates of last 2 semi-annual flow rate audits (PM) Precision & accuracy submitted to AQS Frequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted	Spatial scale	Neighborhood		
Sampling season Site type¹ 3 Purpose of monitor² Suitable for comparison against the annual PM2.5 NAAQS? DATA QUALITY Last PEP Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Dates of last 2 semi-annual flow rate audits (PM) Prequency of 1-point flow rate verification (Pb) N/A Precision & accuracy submitted to AQS Frequency of multi-point gas calibration Annual data certification submitted 12 months 3	Applicable NAAQS averaging time(s)			
Site type¹ 3 Purpose of monitor² 1, 2, 4 Suitable for comparison against the annual PM₂.5 NAAQS? N/A DATA QUALITY Last PEP N/A Last NPAP 6/19/18 Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) N/A Prequency of flow rate verification (manual PM₂.5) N/A Dates of last 2 semi-annual flow rate audits (PM) N/A Precision & accuracy submitted to AQS Prequency of 1-pt. QC check (gases) Weekly Frequency of multi-point gas calibration 6 months Annual data certification submitted 3 / 23 / 22	Sampling season			
Purpose of monitor ² Suitable for comparison against the annual PM _{2.5} N/A NAAQS? DATA QUALITY Last PEP Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Dates of last 2 semi-annual flow rate audits (PM) Dates of last 2 semi-annual flow rate audits (PM) Dates of last 2 semi-annual flow rate audits (PM) Dates of last 2 semi-annual flow rate audits (PM) Prequency of 1-point flow rate verification (Pb) N/A Dates of last 2 semi-annual flow rate audits (Pb) N/A Precision & accuracy submitted to AQS Prequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted	Site type ¹	3		
Suitable for comparison against the annual PM _{2.5} N/A NAAQS? DATA QUALITY Last PEP N/A Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) N/A Prequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) N/A Dates of last 2 semi-annual flow rate audits (PM) N/A Precision & accuracy submitted to AQS Frequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted		1, 2, 4		
DATA QUALITY Last PEP Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) N/A Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) N/A Dates of last 2 semi-annual flow rate audits (PM) Precision & accuracy submitted to AQS Prequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted	Suitable for comparison against the annual PM _{2.5} NAAQS?	N/A		
Last NPAP Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (PM) Precision & accuracy submitted to AQS Prequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted	DATA QUALITY			
Date of last annual independent performance audit (CAB) Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb) N/A Dates of last 2 semi-annual flow rate audits (Pb) N/A Precision & accuracy submitted to AQS Quarterly Frequency of 1-pt. QC check (gases) Weekly Frequency of multi-point gas calibration Annual data certification submitted	Last PEP	N/A		
(CAB) Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb) N/A Dates of last 2 semi-annual flow rate audits (Pb) N/A Precision & accuracy submitted to AQS Quarterly Frequency of 1-pt. QC check (gases) Weekly Frequency of multi-point gas calibration Annual data certification submitted 5/1/23	Last NPAP	6/19/18		
Frequency of flow rate verification (automated PM) Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb) N/A Precision & accuracy submitted to AQS Quarterly Frequency of 1-pt. QC check (gases) Weekly Frequency of multi-point gas calibration Annual data certification submitted	Date of last annual independent performance audit (CAB)	3/23/22		
Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb) Precision & accuracy submitted to AQS Prequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted N/A Quarterly Weekly Frequency of multi-point gas calibration 5/1/23	Frequency of flow rate verification (automated PM)	N/A		
Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb) Precision & accuracy submitted to AQS Prequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted N/A Quarterly Weekly Frequency of multi-point gas calibration 5/1/23	Frequency of flow rate verification (manual PM _{2.5})	N/A		
Dates of last 2 semi-annual flow rate audits (Pb) Precision & accuracy submitted to AQS Frequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted N/A Quarterly Weekly 6 months 5/1/23	Dates of last 2 semi-annual flow rate audits (PM)	N/A		
Dates of last 2 semi-annual flow rate audits (Pb) Precision & accuracy submitted to AQS Prequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted N/A Quarterly Weekly 6 months 5/1/23	Frequency of 1-point flow rate verification (Pb)	N/A		
Precision & accuracy submitted to AQS Frequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted Quarterly Weekly 6 months 5/1/23	Dates of last 2 semi-annual flow rate audits (Pb)	N/A		
Frequency of 1-pt. QC check (gases) Frequency of multi-point gas calibration Annual data certification submitted Weekly 6 months 5/1/23	Precision & accuracy submitted to AQS	Quarterly		
Frequency of multi-point gas calibration 6 months Annual data certification submitted 5/1/23	Frequency of 1-pt. QC check (gases)			
Annual data certification submitted 5/1/23	Frequency of multi-point gas calibration	•		
	Annual data certification submitted			
	Changes in the next 18 months?	None		

	(HL)	HILO	
AQS: 150011006	Type: SLAMS (SO ₂); SPMS (PM _{2.5})	County: Hawaii	MSA: Not in an MSA
Address: 1099 Wa	aianuenue Ave., Hilo, HI 96720		
Latitude: 19.71756	Longitude: -155.11053	Ele	evation: 136.8 m MSL

Located on the grounds of the Adult Rehabilitation Center of Hilo, near the Hilo Medical Center, this site was originally established to monitor volcanic emissions during non-prevalent wind conditions. This station has been operating since 1997. The shelter was replaced on March 31, 2023.





HL TRAFFIC DESCRIPTION		
Type of Roadway	Waianuenue Ave.	
Freeway		
Major Street or Highway	X	
Local Street or Road		
Distance from air intake (m)	18	
Direction from air inlet	N	
Composition of roadway	Asphalt	
Number of traffic lanes	2	
Average daily traffic	8,400 ¹	
Average vehicle speed (est. mph)	35	
Traffic one way or two	2	
Street parking?	No	
¹ Source: State of Hawaii Department of T	ransportation (2016 count)	

For "Site Representativeness" in the following table:

- 2) located to measure typical concentrations in areas of high population density;
- 3) located to determine the impact of significant sources or source categories on air quality;
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures:
 - 4) Support for air pollution research

(HL) Hilo continued

(HL) Hilo continued HL MONITOR INFORMATION (N/A = Not Applicable)			
, ,,	PM _{2.5}	SO ₂	
POC/FRM or FEM	1/FEM	1/FEM	
Type of monitor	SPMS	SLAMS	
AQS parameter code	88101	42401	
Manufacturer	Met-One	TECO	
Model no.	BAM 1022	43iQ	
AQS method code	209	060	
Monitoring start date	1/1/2018	1/1/2007	
Monitoring frequency	Continuous	Continuous	
Probe material	N/A	Teflon	
Residence time (sec)	N/A	11.0	
Distance between collocated monitors	N/A	N/A	
Analytical laboratory	N/A	N/A	
Location of probe	stand-alone shelter on ground	shelter roof	
Shelter dimensions (H x W x D) (m)	N/A	2.7x2.3x3.7	
Horizontal distance from supporting structure (m)	N/A	N/A	
Vertical distance above supporting structure (m)	2.2	1	
Height of probe above ground (m)	5.5	4	
Distance (m) & direction from drip line of tree(s)	16 NW	19 NW	
Horizontal distance from edge of nearest traffic lane (m)	19	18	
Horizontal distance from nearest parking lot (m)	28	30	
Distance (m) & direction from obstructions on	N/A	N/A	
roof, vertical height above probe (m) Distance (m) & direction from possible	N/A	N/A	
obstructions not on roof, vertical height (m)			
Distance (m) & direction from furnace or	29 NNW	29 NNW	
incineration flues	(10m stack height)	(10m stack height)	
Unrestricted airflow	360°	360°	
Located in paved (P) or vegetative (V) ground?	V	V	
SITE REPRESENTATIVENESS			
Spatial scale	Neighborhood	Neighborhood	
Applicable NAAQS averaging time(s)	24-hr, annual	1-hr, 3-hr, annual	
Sampling season	12 months	12 months	
Site type ¹	3	3	
Purpose of monitor ²	1, 2, 4	1, 2, 4	
Suitable for comparison against the annual PM _{2.5} NAAQS?	Y	N/A	
DATA QUALITY			
Last PEP	10/4/22	N/A	
Last NPAP	N/A	7/27/22	
Date of last annual independent performance	N/A	6/15/22	
audit (CAB)			
Frequency of flow rate verification (automated PM)	Monthly	N/A	
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (PM)	6/15/22,12/2/22	N/A	
Frequency of 1-point flow rate verification (Pb)	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A	
Precision & accuracy submitted to AQS	Quarterly	Quarterly	
Frequency of 1-pt. QC check (gases)	N/A	Weekly	
Frequency of multi-point gas calibration	N/A	6 months	
Annual data certification submitted	5/1/23	5/1/23	
Changes in the next 18 months?	None	None	

State of Hawaii

	(KN)	KONA	
AQS: 150011012	Type: SLAMS (SO ₂) SPMS (PM _{2.5})	County: Hawaii	MSA: Not in an MSA
Address: 81-1043	Konawaena School Rd., Kona,	HI 96750	
Latitude: 19.50978	Longitude: -155.91342	Eleva	tion: 517.2 m MSL
Landing December			

This station is located on the upper campus of Konawaena High School. It was established to measure impacts from volcanic emissions. The station has been operating at this site since 2005. The shelter is scheduled to be replaced; the date is to be determined.





Type of Roadway	Konawaena School Rd.	Mamalahoa Highway
Freeway		
Major Street or Highway		X
Local Street or Road	X	
Distance from air intake (m)	17	702
Direction from air inlet	N	W
Composition of roadway	asphalt	Asphalt
Number of traffic lanes	1	2
Average daily traffic	500 ¹	16,300 ²
Average vehicle speed (est. mph)	10	55
Traffic one way or two	2	2
Street parking?	No	No

For "Site Representativeness" in the following table:

- ¹Site Types:1) located to determine the highest concentrations;
 - 2) located to measure typical concentrations in areas of high population density;
 - 3) located to determine the impact of significant sources or source categories on air quality;
 - 4) located to determine general background concentration levels;
 - 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
 - located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures:
 - 4) Support for air pollution research

² Source: State of Hawaii Department of Transportation (2016 count)

(KN) Kona continued

(KN) Kona continued KN MONITOR INFORMATION (N/A = Not Applicable)				
` ''	PM _{2.5} Primary	PM _{2.5} Co-Lo	SO ₂	
POC/FRM or FEM	1/FEM	2/FEM	1/FEM	
Type of monitor	SPMS	SPMS	SLAMS	
AQS parameter code	88101	88101	42401	
Manufacturer	Met-One	Met-One	TECO	
Model no.	BAM 1022	BAM 1022	43iQ	
AQS method code	209	209	060	
Monitoring start date	3/5/2019	3/5/2019	9/13/2005	
Monitoring frequency	Continuous	Continuous	Continuous	
Probe material	N/A	N/A	Teflon	
Residence time (sec)	N/A	N/A	16.7	
Distance between collocated monitors (m)	2.5	2.5	N/A	
Analytical laboratory	N/A	N/A	N/A	
Location of probe	stand-alone shelter on ground	stand-alone shelter on ground	shelter roof	
Shelter dimensions (H x W x D) (m)	N/A	N/A	3x2.4x5	
Horizontal distance from supporting structure (m)	N/A	N/A	N/A	
Vertical distance above supporting structure (m)	N/A	N/A	1.1	
Height of probe above ground (m)	2.1	2.1	4.1	
Distance (m) & direction from drip line of tree(s)	15.2 W	15.2 W	38 NE	
Horizontal distance from edge of nearest traffic lane (m)	30	30	30	
Horizontal distance from nearest parking lot (m)	N/A	N/A	N/A	
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A	N/A	N/A	
Distance (m) & direction from possible	3.4 S,	3.4 S,	21 SSW,	
obstructions not on roof, vertical height (m)	3	3	9	
Distance (m) & direction from furnace or	N/A	N/A	N/A	
incineration flues				
Unrestricted airflow	270°	270°	360°	
Located in paved (P) or vegetative (V) ground?	V	V	V	
SITE REPRESENTATIVENESS			N	
Spatial scale	Neighborhood	Neighborhood	Neighborhood	
Applicable NAAQS averaging time(s)	24-hr, annual	24-hr, annual	1-hr, 3-hr; annual	
Sampling season	12 months	12 months	12 months	
Site type ¹	3	QC	3	
Purpose of monitor ²	1, 2, 4	1, 2, 4	1, 2, 4	
Suitable for comparison against the annual PM _{2.5} NAAQS?	Y	Y	N/A	
DATA QUALITY				
Last PEP	10/6/22	10/6/22	N/A	
Last NPAP	N/A	N/A	6/28/22	
Date of last annual independent performance audit (CAB)	N/A	N/A	4/27/22	
Frequency of flow rate verification (automated PM)	Monthly	Monthly	N/A	
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (PM)	4/27/22, 12/27/22	4/27/22, 12/27/22	N/A	
Frequency of 1-point flow rate verification (Pb)	N/A	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A	N/A	
Precision & accuracy submitted to AQS	Quarterly	Quarterly	Quarterly	_
Frequency of 1-pt. QC check (gases)	N/A	N/A	Weekly	
Frequency of multi-point gas calibration	N/A	N/A	6 months	
Annual data certification submitted	5/1/23	5/1/23	5/1/23	
Changes in the next 18 months?	None	None	Replace shelter	

(MV) MOUNTAIN VIEW					
AQS: 150012023 Type: SPMS	County: Hawaii		MSA: Not in an MSA		
Address: 18-1235 Volcano Rd., Mt. View, HI 96771					
Latitude: 19.57002 Longitude: -155.08046 Elevation: 436.5 m MSL					

This station is located on the grounds of the Mountain View Elementary School. The original Mountain View station, which began in December 2007, was moved at the ending of 2010 approximately 1.8 miles southwest to this current location. Due to the proximity of this community to the Kilauea volcano, it was established to monitor volcanic emissions during non-trade wind days.





MV TRAFFIC DESCRIF			
Type of Roadway	Volcano Rd.		
Freeway			
Major Street or Highway	X		
Local Street or Road			
Distance from air intake (m)	21		
Direction from air inlet	N		
Composition of roadway	asphalt		
Number of traffic lanes	2		
Average daily traffic	13,400 ¹		
Average vehicle speed (est. mph)	40		
Traffic one way or two	2		
Street parking?	No		
¹ Source: State of Hawaii Department of Transportation (2016 count)			

For "Site Representativeness" in the following table:

- 2) located to measure typical concentrations in areas of high population density;
- 3) located to determine the impact of significant sources or source categories on air quality;
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards:
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - Support emissions strategy development and track trends in air pollution abatement control measures;
 - 4) Support for air pollution research

(MV) Mt. View continued

(MV) Mt. View continued				
MV MONITOR INFORMATION (N/A = Not Applicable)				
D00/ED14 EE14	PM _{2.5}	SO ₂		
POC/FRM or FEM	1/FEM	1/FEM		
Type of monitor	SPMS	SPMS		
AQS parameter code	88101	42401		
Manufacturer	Met-One	TECO		
Model no.	BAM 1022	43iQ		
AQS method code	209	060		
Monitoring start date	5/29/2019	12/8/2010		
Monitoring frequency	Continuous	Continuous		
Probe material	N/A	Teflon		
Residence time (sec)	N/A	11.7		
Distance between collocated monitors	N/A	N/A		
Analytical laboratory	N/A	N/A		
Location of probe	stand-alone shelter on ground	shelter roof		
Shelter dimensions (H x W x D) (m)	N/A	3x2.4x5		
Horizontal distance from supporting structure (m)	N/A	N/A		
Vertical distance above supporting structure (m)	N/A	1		
Height of probe above ground (m)	2.2	4		
Distance (m) & direction from drip line of tree(s)	4 SW	2 SW		
Horizontal distance from edge of nearest traffic lane (m)	21	23		
Horizontal distance from nearest parking lot (m)	46.5	46.5		
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A	N/A		
Distance (m) & direction from possible obstructions not on roof, vertical height (m)	N/A	N/A		
Distance (m) & direction from furnace or incineration flues	N/A	N/A		
Unrestricted airflow	360°	360°		
Located in paved (P) or vegetative (V) ground?	V	V		
SITE REPRESENTATIVENESS				
Spatial scale	Neighborhood	Neighborhood		
Applicable NAAQS averaging time(s)	24-hr, annual	1-hr, 3-hr; annual		
Sampling season	12 months	12 months		
Site type ¹	3	3		
Purpose of monitor ²	1, 2, 4	1, 2, 4		
Suitable for comparison against the annual PM _{2.5} NAAQS?	Y	N/A		
DATA QUALITY				
Last PEP	10/4/22	N/A		
Last NPAP	N/A	6/23/22		
Date of last annual independent performance audit (CAB)	N/A	5/18/22		
Frequency of flow rate verification (automated PM)	Monthly	N/A		
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A		
Dates of last 2 semi-annual flow rate audits (PM)	5/4/22, 12/9/22	N/A		
Frequency of 1-point flow rate verification (Pb)	N/A	N/A		
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A		
Precision & accuracy submitted to AQS	Quarterly	Quarterly		
Frequency of 1-pt. QC check (gases)	N/A	Weekly		
the state of the s	N/A N/A			
Frequency of multi-point gas calibration	5/1/23	60 days 5/1/23		
Annual data certification submitted				
Changes in the next 18 months?	None	Replace shelter		

(OV) OCEAN VIEW					
AQS: 150012020	Type: SPMS		County: Hawaii		MSA: Not in an MSA
Address: 92-6091 Orchid Mauka Circle, Ocean View, HI 96737					
Latitude: 19.11756 Longitude: -155.77814 Elevation: 862.6 m MSL					

This station was established in 2010 and is located on the grounds of the Ocean View Fire Station. During normal trade-winds, volcanic emissions are carried into this residential/agricultural community. This shelter is scheduled to be replaced; the date is to be determined.





OV TRAFFIC DESCRIPTION				
Type of Roadway	Orchid Mauka Circ.			
Freeway				
Major Street or Highway				
Local Street or Road	X			
Distance from air intake (m)	13.6			
Direction from air inlet	ENE			
Composition of roadway	asphalt			
Number of traffic lanes	2			
Average daily traffic	< 3,000 ¹			
Average vehicle speed (est. mph)	25			
Traffic one way or two	2			
Street parking?	No			
¹ Estimated only, local residential street, no data available				

For "Site Representativeness" in the following table:

- 2) located to measure typical concentrations in areas of high population density;
- located to determine the impact of significant sources or source categories on air quality:
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures;
 - 4) Support for air pollution research

(OV) Ocean View continued

(OV) Ocean View continued			
OV MONITOR INFORMATION (N/A = Not Appl			
	PM _{2.5}	SO ₂	
POC/FRM or FEM	1/FEM	1/FEM	
Type of monitor	SPMS	SPMS	
AQS parameter code	88101	42401	
Manufacturer	Met-One	TECO	
Model no.	BAM 1022	43iQ	
AQS method code	209	060	
Monitoring start date	5/1/2019	4/1/2010	
Monitoring frequency	Continuous	Continuous	
Probe material	N/A	Teflon	
Residence time (sec)	N/A	15.3	
Distance between collocated monitors	N/A	N/A	
Analytical laboratory	N/A	N/A	
Location of probe	Stand-alone PM shelter on station stairs platform	shelter roof	
Shelter dimensions (H x W x D) (m)	N/A	3x2.4x5	
Horizontal distance from supporting structure (m)	N/A	N/A	
Vertical distance above supporting structure (m)	2.1	1.1	
Height of probe above ground (m)	3.1	4.1	
Distance (m) & direction from drip line of tree(s)	3.7 N	5.5 NE	
Horizontal distance from edge of nearest traffic lane (m)	13.6	13.6	
Horizontal distance from nearest parking lot (m)	6.4	6.4	
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A	N/A	
Distance (m) & direction from possible obstructions not on roof, vertical height (m)	1.1 W/ 3.4 (station shelter)	N/A	
Distance (m) & direction from furnace or incineration flues	N/A	N/A	
Unrestricted airflow	270°	360°	
Located in paved (P) or vegetative (V) ground?	gravel	gravel	
SITE REPRESENTATIVENESS			
Spatial scale	Neighborhood	Neighborhood	
Applicable NAAQS averaging time(s)	24-hr, annual	1-hr, 3-hr; annual	
Sampling season	12 months	12 months	
Site type ¹	3, 6	3, 6	
Purpose of monitor ²	1, 2, 4	1, 2, 4	
Suitable for comparison against the annual PM _{2.5} NAAQS?	Υ Υ	N/A	
DATA QUALITY			
Last PEP	10/6/22	N/A	
Last NPAP	N/A	6/28/22	
Date of last annual independent performance audit (CAB)	N/A	5/25/22	
Frequency of flow rate verification (automated PM)	Monthly	N/A	
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (PM)	5/25/22, 12/7/22	N/A	
Frequency of 1-point flow rate verification (Pb)	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A	
Precision & accuracy submitted to AQS	Quarterly	Quarterly	
Frequency of 1-pt. QC check (gases)	N/A	Weekly	
Frequency of multi-point gas calibration	N/A	6 months	
	_	5/1/23	+ + + + + + + + + + + + + + + + + + + +
Annual data certification submitted	5/1/23	D/ 1/23	

(PA) PAHALA				
AQS: 150012016 Type: SPMS	County: Hawaii	MSA: Not in an MSA		
Address: 96-3150 Pikake St., Pahala, HI 96777				
Latitude: 19.2039 Longitude: -155.48018		Elevation: 320 m MSL		

This station is located on the grounds of the Ka'u High/Pahala Elementary School. During normal tradewinds, volcanic emissions are carried into this rural community. The station began operating in 2007. The shelter was replaced on December 29, 2022.





PA TRAFFIC DESCRIPTION				
Type of Roadway	Puahala	Pumeli		
Freeway				
Major Street or Highway				
Local Street or Road	Χ	X		
Distance from air intake (m)	226	61		
Direction from air inlet	Е	N		
Composition of roadway	Asphalt	Asphalt		
Number of traffic lanes	2	2		
Average daily traffic	< 3,000 ¹	< 3,000 ¹		
Average vehicle speed (est. mph)	25 mph	25 mph		
Traffic one way or two	2	2		
Street parking?	No	No		

For "Site Representativeness" in the following table:

- 2) located to measure typical concentrations in areas of high population density;
- located to determine the impact of significant sources or source categories on air quality:
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures;
 - 4) Support for air pollution research

	icable)	80.	
DOO/FDM FEM	PM _{2.5}	SO ₂	
POC/FRM or FEM	1/FEM	1/FEM	
Type of monitor	SPMS	SPMS	
AQS parameter code	88101	42401	
Manufacturer	Met-One	TECO	
Model no.	BAM 1022	43iQ	
AQS method code	209	060	
Monitoring start date	2/26/2019	8/10/2007	
Monitoring frequency	Continuous	Continuous	
Probe material	N/A	Teflon	
Residence time (sec)	N/A	11.0	
Distance between collocated monitors	N/A	N/A	
Analytical laboratory	N/A stand-alone	N/A	
Location of probe	shelter on ground	shelter roof	
Shelter dimensions (H x W x D) (m)	N/A	2.7x2x3.7	
Horizontal distance from supporting structure (m)	N/A	N/A	
Vertical distance above supporting structure (m)	N/A	1	
Height of probe above ground (m)	2.1	4	
Distance (m) & direction from drip line of tree(s)	11 S	13 SW	
Horizontal distance from edge of nearest traffic lane (m)	48	48	
Horizontal distance from nearest parking lot (m)	40	40	
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A	N/A	
Distance (m) & direction from possible	N/A	N/A	
obstructions not on roof, vertical height (m)			
Distance (m) & direction from furnace or incineration flues	N/A	N/A	
Unrestricted airflow	270°	360°	
Located in paved (P) or vegetative (V) ground?	V	V	
SITE REPRESENTATIVENESS			
Spatial scale	Neighborhood	Neighborhood	
Applicable NAAQS averaging time(s)	24-hr, annual	1-hr, 3-hr;	
···	12 months	annual 12 months	
Sampling season Site type ¹		3	
	3		
Purpose of monitor ² Suitable for comparison against the annual PM _{2.5}	1, 2, 4	1, 2, 4	
Suitable for comparison against the annual Pivi _{2.5} NAAQS?	Υ	N/A	
DATA QUALITY			
Last PEP	6/23/22	N/A	
Last NPAP	N/A	6/22/16	
Date of last annual independent performance audit (CAB)	N/A	5/4/22	
Frequency of flow rate verification (automated PM)	Monthly	N/A	
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (PM)	5/4/22, 12/9/22	N/A	
Frequency of 1-point flow rate verification (Pb)	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A	
Precision & accuracy submitted to AQS	Quarterly	Quarterly	
Frequency of 1-pt. QC check (gases)	N/A	Weekly	
Frequency of multi-point gas calibration	N/A	6 months	
Annual data certification submitted	5/1/23	5/1/23	
Changes in the next 18 months?	None	None	+

(KK) KAILUA-KONA				
AQS: 150013028 Type: SPMS County: Hawaii MSA: Not in an MSA				
Address: Department of Water Supply Puapua'a Reservoir, Kailua-Kona, HI 96740				
Latitude: 19.61815833 Longitude: -155.9711111 Elevation: 92.4 m MSL				

This station is located in the middle Kailua-Kona town within a fenced area that contains a County of Hawaii water reservoir and pump house. The station was established to monitor the effects of volcanic emissions and has been operating since November 21, 2018 monitoring for PM_{2.5}.





Type of Roadway	Kuakini Highway	Walua Road	Queen Kaahumanu Hwy
Freeway			-
Major Street or Highway	X		X
Local Street or Road		X (no through traffic)	
Distance from air intake (m)	125	42	145
Direction from air inlet	NW	S	E
Composition of roadway	asphalt	asphalt	Asphalt
Number of traffic lanes	2	2	2
Average daily traffic	8,200 ¹	² Estimated <50	22,900 ¹
Average vehicle speed (est. mph)	45	25	45
Traffic one way or two	2	2	2
Street parking?	No	No	No

Source. State of Hawaii Department of Transportation (2016 count)

For "Site Representativeness" in the following table:

- 2) located to measure typical concentrations in areas of high population density;
- 3) located to determine the impact of significant sources or source categories on air quality:
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures:
 - 4) Support for air pollution research

² Estimated only, no data available, road is for local business access

(KK) Kailua-Kona continued

(KK) Kailua-Kona continued				
KK MONITOR INFORMATION (N/A = Not Appl	licable)			
	PM _{2.5}			
POC/FRM or FEM	1/FEM			
Type of monitor	SPMS			
AQS parameter code	88101			
Manufacturer	Met One			
Model no.	BAM1022			
AQS method code	209			
Monitoring start date	11/15/2018			
Monitoring frequency	Continuous			
Probe material	N/A			
Residence time (sec)	N/A			
Distance between collocated monitors	N/A			
Analytical laboratory	N/A			
Location of probe	stand-alone shelter on ground			
Shelter dimensions (H x W x D) (m)	N/A			
Horizontal distance from supporting structure (m)	N/A			
Vertical distance above supporting structure (m)	2.2			
Height of probe above ground (m)	2.2			
Distance (m) & direction from drip line of tree(s)	19.8 SE			
Horizontal distance from edge of nearest traffic lane (m)	42			
Horizontal distance from nearest parking lot (m)	25			
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A			
Distance (m) & direction from possible obstructions not on roof, vertical height (m)	3 NE/3			
Distance (m) & direction from furnace or incineration flues	N/A			
Unrestricted airflow	180°			
Located in paved (P) or vegetative (V) ground?	gravel			
SITE REPRESENTATIVENESS	Ğ.			
Spatial scale	Neighborhood			
Applicable NAAQS averaging time(s)	24-hr, annual			
Sampling season	12 months			
Site type ¹	3	-		
Purpose of monitor ²	1, 2, 4	-		
Suitable for comparison against the annual PM _{2.5} NAAQS?	N			
DATA QUALITY				
Last PEP	None			
Last NPAP	N/A			
Date of last annual independent performance audit (CAB)	N/A			
Frequency of flow rate verification (automated PM)	Monthly			
Frequency of flow rate verification (manual PM _{2.5})	N/A			
Dates of last 2 semi-annual flow rate audits (PM)	4/27/22, 12/27/22			
Frequency of 1-point flow rate verification (Pb)	N/A		-	
Dates of last 2 semi-annual flow rate audits (Pb)	N/A			
Precision & accuracy submitted to AQS	Quarterly			
Frequency of 1-pt. QC check (gases)	N/A		_	
Frequency of multi-point gas calibration	N/A			
Annual data certification submitted	5/1/23		-	

	(KS) I	KEAAU	
AQS: 150013027 Type:	SPMS	County: Hawaii	MSA: Not in an MSA
Address: Kamehameha S	Schools Hawaii Campus, 1	16-714 Volcano Road, Keaau	, HI 96749
Latitude: 19.605424	Longitude: -155.051379	Elevation	: 179.8 m MSL

This temporary station is located in the town of Keaau on the Kamehameha Schools Hawaii campus. The station began monitoring for PM_{2.5} and SO₂ on June 14, 2018 at a temporary location elsewhere on campus and was relocated to it's permanent location on June 30, 2023.





KS TRAFFIC DESCRIPTION	
Type of Roadway	Volcano Road/Mamalahoa Highway
Freeway	
Major Street or Highway	X
Local Street or Road	
Distance from air intake (m)	40
Direction from air inlet	S
Composition of roadway	asphalt
Number of traffic lanes	2
Average daily traffic	13,400 ¹
Average vehicle speed (est. mph)	45
Traffic one way or two	2
Street parking?	No
¹ Source: State of Hawaii Department	of Transportation (2016 count)

For "Site Representativeness" in the following table:

- 2) located to measure typical concentrations in areas of high population density;
- located to determine the impact of significant sources or source categories on air quality;
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures;
 - 4) Support for air pollution research

(KS) Keaau continued

(KS) Keaau continued			
KS MONITOR INFORMATION (N/A = Not App			
	PM _{2.5}	SO ₂	
POC/FRM or FEM	1/FEM	1/FEM	
Type of monitor	SPMS	SPMS	
AQS parameter code	88101	42401	
Manufacturer	Met One	TECO	
Model no.	BAM1022	43iQ	
AQS method code	209	060	
Monitoring start date	6/14/2018	6/14/2018	
Monitoring frequency	Continuous	Continuous	
Probe material	N/A	Teflon	
Residence time (sec)	N/A	11.5	
Distance between collocated monitors	N/A	N/A	
Analytical laboratory	N/A	N/A	
•	stand-alone		
Location of probe	shelter on ground	shelter roof	
Shelter dimensions (H x W x D) (m)	N/A	2.7x2x3.7	
Horizontal distance from supporting structure (m)	N/A	N/A	
Vertical distance above supporting structure (m)	N/A	1	
Height of probe above ground (m)	2.2	4	
Distance (m) & direction from drip line of tree(s)	50 NE	55 NE	
Horizontal distance from edge of nearest traffic lane (m)	40	40	
Horizontal distance from nearest parking lot (m)	330	330	
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A	N/A	
Distance (m) & direction from possible obstructions not on roof, vertical height (m)	N/A	N/A	
Distance (m) & direction from furnace or incineration flues	N/A	N/A	
Unrestricted airflow	360°	360°	
Located in paved (P) or vegetative (V) ground?	V	V	
SITE REPRESENTATIVENESS			
Spatial scale	Neighborhood	Neighborhood	
Applicable NAAQS averaging time(s)	24-hr, annual	1-hr, 3-hr; annual	
Sampling season	12 months	12 months	
Site type ¹	3	3	
Purpose of monitor ²	1, 2, 4	1, 2, 4	
Suitable for comparison against the annual PM _{2.5} NAAQS?	N	N/A	
DATA QUALITY			
Last PEP	None	N/A	
Last NPAP	N/A	None	
Date of last annual independent performance audit (CAB)	N/A	5/18/22	
Frequency of flow rate verification (automated PM)	Monthly	N/A	
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (PM)	5/4/22, 12/2/22	N/A	
Frequency of 1-point flow rate verification (Pb)	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A	
Precision & accuracy submitted to AQS	Quarterly	Quarterly	
Frequency of 1-pt. QC check (gases)	N/A	Weekly	
Frequency of multi-point gas calibration	N/A	6 months	
Annual data certification submitted	5/1/23	5/1/23	
Changes in the next 18 months?	+		
Changes in the next to months?	None	None	

	(LE) LEILANI	
AQS: 150012035 Type: SPMS	County: Hawaii	MSA: Not in an MSA
Address: Leilani Community Association (Center, 13-3441 Moku Street, Paho	a, Hawaii 96778
Latitude: 19.46566667 Longitude: - 15	54.91444444 Elevat	ion: 243 m MSL

This station is located in a residential subdivision within a fenced area that contains the Leilani Community Association Center. The station was established to monitor emissions from the nearby geothermal energy facility and has been monitoring for H_2S since September 17, 2019. The shelter was moved to a more suitable location at the center on September 20, 2020.





Type of Roadway	Leilani Avenue	Kupono Street
Freeway		-
Major Street or Highway		
Local Street or Road	X	X
Distance from air intake (m)	130	45
Direction from air inlet	S	Е
Composition of roadway	asphalt	asphalt
Number of traffic lanes	2	2
Average daily traffic	¹ Estimated <2,000	¹ Estimated <200
Average vehicle speed (est. mph)	25	20
Traffic one way or two	2	2
Street parking?	No	No

For "Site Representativeness" in the following table:

- 2) located to measure typical concentrations in areas of high population density;
- 3) located to determine the impact of significant sources or source categories on air quality;
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards:
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures;
 - 4) Support for air pollution research

(LE) Leilani continued

(LE) Leilani continued			
LE MONITOR INFORMATION (N/A = Not Applie	cable)		
	H₂S	SO ₂	
POC/FRM or FEM	N/A	1/FEM	
Type of monitor	SPMS	SPMS	
AQS parameter code	N/A	42401	
Manufacturer	TECO	TECO	
Model no.	450IQ	43IQ	
AQS method code	N/A	060	
Monitoring start date	9/17/2019	9/12/2019	
Monitoring frequency	Continuous	Continuous	
Probe material	Teflon	Teflon	
Residence time (sec)	4.9	11.2	
Distance between collocated monitors	N/A	N/A	
Analytical laboratory	N/A	N/A	
Location of probe	shelter roof	shelter roof	
Shelter dimensions (H x W x D) (m)	2.7x2x3.7	2.7x2x3.7	
Horizontal distance from supporting structure (m)	N/A	N/A	
Vertical distance above supporting structure (m)	1.0	1.0	
Height of probe above ground (m)	4	4	+
Distance (m) & direction from drip line of tree(s)	10 W	10 W	
Horizontal distance from edge of nearest traffic	_		
lane (m)	45	45	
Horizontal distance from nearest parking lot (m)	175	175	
Distance (m) & direction from obstructions on			
roof, vertical height above probe (m)	N/A	N/A	
Distance (m) & direction from possible	N/A	N/A	
obstructions not on roof, vertical height (m)	14/71	14/71	
Distance (m) & direction from furnace or	N/A	N/A	
incineration flues Unrestricted airflow	360°	360°	
Located in paved (P) or vegetative (V) ground?	gravel	gravel	+
SITE REPRESENTATIVENESS	graver	giavei	
Spatial scale	Neighborhood	Neighborhood	
•	1-hour state		+
Applicable NAAQS averaging time(s)	standard 25 ppb	1-hour	
Sampling season	12 months	12 months	
Site type ¹	3	3	
Purpose of monitor ²	1, 4	1, 4	
Suitable for comparison against the annual PM _{2.5}	N/A	N/A	
NAAQS? DATA QUALITY			
	NI/A	NI/A	
Last PEP	N/A	N/A	
Last NPAP	N/A	None	
Date of last annual independent performance audit (CAB)	5/11/2022	5/11/2022	
Frequency of flow rate verification (automated PM)	N/A	N/A	
	N/A	N/A	
Frequency of flow rate verification (manual PM _{2.5})		N 1 / A	
Frequency of flow rate verification (manual PM _{2.5}) Dates of last 2 semi-annual flow rate audits (PM)	N/A	N/A	
	+	N/A N/A	
Dates of last 2 semi-annual flow rate audits (PM)	N/A		
Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb)	N/A N/A	N/A	
Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb) Precision & accuracy submitted to AQS	N/A N/A N/A	N/A N/A	
Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb) Precision & accuracy submitted to AQS Frequency of 1-pt. QC check (gases)	N/A N/A N/A Quarterly	N/A N/A Quarterly	
Dates of last 2 semi-annual flow rate audits (PM) Frequency of 1-point flow rate verification (Pb) Dates of last 2 semi-annual flow rate audits (Pb) Precision & accuracy submitted to AQS	N/A N/A N/A Quarterly Weekly	N/A N/A Quarterly Weekly	

	(NA) NA	AALEHU	
AQS: 150013033	Type: SPMS	County: Hawaii	MSA: Not in an MSA
Address: Naalehu	Elementary School, 95-5547 Ma	amalahoa Hwy., Naalehu, HI	96772
Latitude: 19.060656	Longitude: -155.579167	Elevation	n: 196.3 m MSL
1 C D			

This station is located at the USGS Seismograph building on the campus of Naalehu Elementary School. The SO₂ monitor has been operating since September 6, 2018. A PM_{2.5} sampler was installed at the station on December 2, 2022.





NA TRAFFIC DESCRIPTION	
Type of Roadway	Mamalahoa HIghway
Freeway	-
Major Street or Highway	X
Local Street or Road	
Distance from air intake (m)	180
Direction from air inlet	N
Composition of roadway	asphalt
Number of traffic lanes	2
Average daily traffic	3,700 ¹
Average vehicle speed (est. mph)	25
Traffic one way or two	2
Street parking?	No
¹ Source: State of Hawaii Department of Tra	ansportation (2016 count)

For "Site Representativeness" in the following table:

- 2) located to measure typical concentrations in areas of high population density;
- 3) located to determine the impact of significant sources or source categories on air quality;
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures;
 - 4) Support for air pollution research

(NA) Naalehu continued

(NA) Naalehu continued	inahla)		
NA MONITOR INFORMATION (N/A = Not Appl		DNA	T T
DOO/FDM FFM	SO ₂	PM _{2.5}	
POC/FRM or FEM	1/FEM	1/FEM	
Type of monitor	SPMS	SPMS	
AQS parameter code Manufacturer	42401	88101	
	TECO	Met One	
Model no.	43iQ	BAM1022	
AQS method code	060	209	
Monitoring start date	9/6/2018	12/2/2022	
Monitoring frequency	Continuous	Continuous	
Probe material	Teflon	N/A	
Residence time (sec)	11.0	N/A	
Distance between collocated monitors	N/A	N/A	
Analytical laboratory	N/A	N/A	
Location of probe	building wall	stand-alone shelter on ground	
Shelter dimensions (H x W x D) (m)	2.4 x 3.7 x 3.1	N/A	
Horizontal distance from supporting structure (m)	1	N/A	
Vertical distance above supporting structure (m)	N/A	2.2	
Height of probe above ground (m)	1.9	2.2	
Distance (m) & direction from drip line of tree(s)	20 NW	20 NW	
Horizontal distance from edge of nearest traffic lane (m)	114	114	
Horizontal distance from nearest parking lot (m)	114	114	
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A	N/A	
Distance (m) & direction from possible obstructions not on roof, vertical height (m)	N/A	1 E/2.4	
Distance (m) & direction from furnace or incineration flues	N/A	N/A	
Unrestricted airflow	180°	360°	
Located in paved (P) or vegetative (V) ground?	V	V	
SITE REPRESENTATIVENESS	V	V	
Spatial scale	Neighborhood	Neighborhood	
•	1-hr, 3-hr;		
Applicable NAAQS averaging time(s)	annual	24-hr, annual	
Sampling season	12 months	12 months	
Site type ¹	3	3	
Purpose of monitor ²	1, 2, 4	1, 2, 4	
Suitable for comparison against the annual PM _{2.5} NAAQS?	N/A	N	
DATA QUALITY			
Last PEP	N/A	N/A	
Last NPAP	Not Done	N/A	
Date of last annual independent performance audit (CAB)	5/25/22	N/A	
Frequency of flow rate verification (automated PM)	N/A	Monthly	
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (PM)	N/A	12/7/22	
Frequency of 1-point flow rate verification (Pb)	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A	
Precision & accuracy submitted to AQS	Quarterly	Quarterly	
Frequency of 1-pt. QC check (gases)	Weekly	N/A	
Frequency of multi-point gas calibration	6 months	N/A	
Annual data certification submitted	5/1/23	5/1/23	
Changes in the next 18 months?	None	None	

	(WL) V	VAIKOLOA		
AQS: 150012021 Type	e: SPMS	County: Hawaii	N	MSA: Not in an MSA
Address: TMK 3-6-8-002	2-019, Waikoloa, HI 967	38		
Latitude: 19.977500	Longitude: -155.7980	56	Elevation:	182.9 m MSL

This station is located within a fenced area that contains a County of Hawaii water tank and pump house, approximately 3 km northeast of Waikoloa. The PM_{2.5} monitor for this station was relocated from Waikoloa E.S. on July 28, 2021. An SO₂ monitor and shelter was added to the station on December 8, 2022.





Type of Roadway	Queen Kaahumanu Hwy.	Waikoloa Road
Freeway		
Major Street or Highway	X	
Local Street or Road		Х
Distance from air intake (m)	2,143	4,580
Direction from air inlet	W	N
Composition of roadway	asphalt	asphalt
Number of traffic lanes	2	2
Average daily traffic	11,900 ¹	8,200 ¹
Average vehicle speed (est. mph)	55	55
Traffic one way or two	2	2
Street parking?	No	No

For "Site Representativeness" in the following table:

- 2) located to measure typical concentrations in areas of high population density;
- 3) located to determine the impact of significant sources or source categories on air quality;
- 4) located to determine general background concentration levels;
- 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards:
- 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - Support emissions strategy development and track trends in air pollution abatement control measures;
 - 4) Support for air pollution research

(WL) Waikoloa continued

(WL) Waikoloa continued WL MONITOR INFORMATION (N/A = Not Appl	icablo)		
WE MONITOR INFORMATION (N/A = NOt Appl		00	T
DOG/FDM FFM	PM _{2.5}	SO ₂	
POC/FRM or FEM	1/FEM	1/FEM	
Type of monitor	SPMS	SPMS	
AQS parameter code	88101	42401	
Manufacturer	Met One	TECO	
Model no.	BAM1022	43iQ	
AQS method code	209	060	
Monitoring start date	7/28/2021	12/8/2022	
Monitoring frequency	Continuous	Continuous	
Probe material	N/A	Teflon	
Residence time (sec)	N/A	10.93	
Distance between collocated monitors	N/A	N/A	
Analytical laboratory	N/A	N/A	
Location of probe	stand-alone shelter on ground	shelter roof	
Shelter dimensions (H x W x D) (m)	N/A	2.7 x 2.0 x 3.7	
Horizontal distance from supporting structure (m)	N/A	N/A	
Vertical distance above supporting structure (m)	2.2	1	
Height of probe above ground (m)	2.2	4	
Distance (m) & direction from drip line of tree(s)	15W	15W	
Horizontal distance from edge of nearest traffic lane (m)	2143	2143	
Horizontal distance from nearest parking lot (m)	2590	2590	
Distance (m) & direction from obstructions on roof, vertical height above probe (m)	N/A	N/A	
Distance (m) & direction from possible obstructions not on roof, vertical height (m)	3 NE/3	N/A	
Distance (m) & direction from furnace or incineration flues	N/A	N/A	
Unrestricted airflow	360°	360°	
Located in paved (P) or vegetative (V) ground?	gravel	gravel	
SITE REPRESENTATIVENESS	giavei	giavei	
Spatial scale	Neighborhood	Neighborhood	
Applicable NAAQS averaging time(s)	24-hr, annual	1-hr, 3-hr; annual	
Sampling season	12 months	12 months	+
Site type ¹	3	3	
Purpose of monitor ²	1, 2, 4	1, 2, 4	
Suitable for comparison against the annual PM _{2.5}	N	N/A	
NAAQS?			
DATA QUALITY	NI/A	N1/A	
Last PEP	N/A	N/A	
Last NPAP	N/A	None - new	
Date of last annual independent performance audit (CAB)	N/A	None - new	
Frequency of flow rate verification (automated PM)	Monthly	N/A	
Frequency of flow rate verification (manual PM _{2.5})	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (PM)	4/27/22, 12/27/22	N/A	
Frequency of 1-point flow rate verification (Pb)	N/A	N/A	
Dates of last 2 semi-annual flow rate audits (Pb)	N/A	N/A	
Precision & accuracy submitted to AQS	Quarterly	Quarterly	
Frequency of 1-pt. QC check (gases)	N/A	Weekly	
Frequency of multi-point gas calibration	N/A	6 months	
Annual data certification submitted	5/1/23	5/1/23	

KAHE (Data Requirements Rule)							
AQS: 150034001 Type: SLAMS County: Honolulu MSA: Honolulu							
Address: Palehua Road, Makakilo, Oahu							
Latitude:	21.3678	Longitude: -	158.1053	Eleva	ation: 388 m MSL		

Location Description: This station is located on the hillside south of Palehua Road and overlooks the Pacific Ocean. The area around the station is undeveloped and is currently used for cattle grazing. The station is approximately 2.7 kilometers northeast of the Kahe Generating Station. The city of Makakilo is located to the east and southeast. The areas immediately to the west through north are undeveloped.





TRAFFIC DESCRIPTION			
Type of Roadway	Palehua Road	Farrington Highway	
Freeway			
Major Street or Highway	X	X	
Distance from air intake (m)	12.8	2,750	
Direction from air inlet	N	SW	
Composition of roadway	asphalt	asphalt	
Number of traffic lanes	1	4	
Average daily traffic	20 (estimate)	52,300 ¹	
Average vehicle speed (est. mph)	15	40	
Traffic one way or two	2	2	
Street parking?	No	No	
¹ Source: State of Hawaii Department of ⁻	Fransportation 2015	count	

For "Site Representativeness" in the following table:

- ¹Site Types:1) located to determine the highest concentrations;
 - 2) located to measure typical concentrations in areas of high population density;
 - located to determine the impact of significant sources or source categories on air quality;
 - 4) located to determine general background concentration levels;
 - 5) located to determine extent of regional pollutant transport among populated areas and in support of secondary standards;
 - 6) located to measure air pollution impacts on visibility, vegetation damage, or other welfare-based impacts
- ² Purposes: 1) Provide air pollution data to the general public in a timely manner;
 - 2) Support compliance with ambient air quality standards;
 - 3) Support emissions strategy development and track trends in air pollution abatement control measures:
 - 4) Support for air pollution research

(KE) Kahe continued

(KE) Kahe continued					
KAHE MONITOR INFORMATION (N/A = Not A	pplicable)				
	SO ₂				
POC/FRM or FEM	1/FEM				
Type of monitor	SLAMS				
AQS parameter code	42401				
Manufacturer	Thermo Scientific				
Model no.	43i-TLE				
AQS method code	560				
Monitoring start date	12/16/2016				
Monitoring frequency	Continuous				
Probe material	Borosilicate glass				
Residence time (sec)	12.2				
Distance between collocated monitors	N/A				
Analytical laboratory	N/A				
Location of probe	Shelter roof				
Building dimensions (H) (m)	3.3				
Horizontal distance from supporting structure (m)	0				
Vertical distance above supporting structure (m)	1.0				
Height of probe above ground (m)	4.3				
Distance (m) & direction from drip line of tree(s))	N/A				
Horizontal distance from edge of nearest traffic					
lane (m)	12.8				
Horizontal distance from nearest parking lot (m)	N/A				
Distance (m) & direction from obstructions on roof,	N/A				
vertical height above probe (m)	IN/A				
Distance (m) & direction from possible obstructions	N/A				
not on roof, vertical height (m)	13/71				
Distance (m) & direction from furnace or incineration flues	2,740 SW				
Unrestricted airflow	360°				
Located in paved (P) or vegetative (V) ground?	V				
SITE REPRESENTATIVENESS	V				
Spatial scale	Neighborhood				
Applicable NAAQS averaging time(s)	1-hr				
Sampling season	12 months				
Site type ¹	3				
Purpose of monitor ²					
Suitable for comparison against the annual PM _{2.5}	2, 3				
NAAQS?	N/A				
DATA QUALITY					
Last PEP	N/A				
Last NPAP	6/22/21				
Date of last annual independent performance audit	12/22/22				
Frequency of flow rate verification (automated PM)	N/A				
Frequency of flow rate verification (manual PM _{2.5})	N/A				
Dates of last 2 semi-annual flow rate audits (PM)	N/A				
Frequency of 1-point flow rate verification (Pb)	N/A				
Dates of last 2 semi-annual flow rate audits (Pb)	N/A				
Precision & accuracy submitted to AQS	N/A				
Frequency of 1-pt. QC check (gases)	Biweekly				
	•				
Frequency of multi-point gas calibration Annual data certification submitted	Quarterly				
	5/1/23				
Changes in the next 18 months?	None				

Appendix A

Public Notice Documentation

The 2023 Air Monitoring Network Plan, based on 40 CFR 58.10, documents, and describes the establishment and maintenance of Hawaii's ambient air monitoring network. This document was made available for public viewing on the Clean Air Branch website and at the following Department of Health locations:

- Clean Air Branch, 2827 Waimano Home Road, Room 130, Pearl City, Oahu
- Kauai District Health Office, 3040 Umi Street, Lihue, Kauai
- Maui District Health Office, 54 High Street, Room 300, Wailuku, Maui
- Hawaii District Health Office, 1582 Kamehameha Avenue, Hilo, Hawaii
- Clean Air Branch-Kona, Keakealani Building, 79-1020 Haukapila Street, Room 115, Kealakekua, Hawaii

Public notification of the availability of the Plan for public inspection was published in the major newspapers on all counties. The public comment period was for 30 days from May 17, 2023 to June 15, 2023.

The public notice was published in the following newspapers for the following counties:

- Kauai County: The Garden Island
- City and County of Honolulu: The Star Advertiser
- Maui County: The Maui News
- Hawaii County: West Hawaii Today and Hawaii Tribune Herald

Documentations of the public notice are attached.

Comments received will be addressed and included in this plan.

IN THE MATTER OF PUBLIC NOTICE

NOTARY PUBLIC O. 90-263 FOF HANN ahthrumation in
PUBLIC o. 90-263 FOF HANN ahthronin
PUBLIC o. 90-263 FOF HANN ahthronin
E OF HANNA ahttr
E OF HANNA ahttr
times on:
matter.
• -
_{D. 20} ンタ

PUBLIC NOTICE (Docket No. 23-CA-PA-08)

The Department of Health, State of Hawaii, is notifying all interested persons of the report, "2023 Air Monitoring Network Plan." This report, based on 40 CFR 58.10, documents, and describes the establishment and maintenance of Hawaii's ambient air monitoring network.

The report is available for public review during regular office hours, Monday through Friday, 7:45 a.m. to 4:15 p.m., at the following locations:

}

Clean Air Branch, Department of Health 2827 Walmano Home Road, Room 130 Pearl City, HI 96782

- Hawaii District Health Office, Department of Health
 1582 Kamehameha Ave., Hilo, Hawaii 96720
 Clean Air Branch Kona, Keakealani Building, Department of Health
 79-1020 Haukapila Street, Room 115, Kealakekua, Hawaii 96750

Kauai:

Kauai District Health Office, Department of Health 3040 Umi St., Lihue, Kauai 96766

Maui:

Maui District Health Office, Department of Health (Environmental Health) 54 High St., Room 300, Wailuku, Maui 96793

The network plan is also available for inspection on the Hawaii Department of Health, Clean Air Branch website at http://health.hawaii.gov/cab. Interested persons may submit written comments addressed to the Department of Health at:

Clean Air Branch, Department of Health 2827 Waimano Home Road, Room 130 Pearl City, HI 96782

The comments must be postmarked or received by June 15, 2023. For additional information, contact Ms. Lisa Young of the Clean Air Branch in Honolulu at (808)

(TGI1416031 5/17/23)

ICSP.NO.: _

IN THE MATTER OF

	PUBLIC NOTICE (Docket No. 23-CA-PA-0	08)
STATE OF HAWAII City and County of Honolulu	} } ss. }	
Doc. Date:	MAY 1 7 2023	# Pages:1
Notary Name: COLLEEN	N E. SORANAKA	First Judicial Circuit
Doc. Description: Publication	Affidavit of	E. SO
Comme .	MAY 1 8 2023	O NOTARY PUBLIC D
Notary Signature	Date	*\ No. 90-263 *\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
Kimberly Masu being duly swor authorized to execute this affida Honolulu Star-Advertiser, MidV Hawaii Tribune-Herald, that said the State of Hawaii, and that the	vit of Oahu Publications, Inc. p Veek, The Garden Island, West d newspapers are newspapers o	oublisher of The Hawaii Today, and f general circulation in
Honolulu Star-Advertiser	1 times on:	
05/17/2023		
MidWeek	times on:	
The Garden Island	0times on:	
Hawaii Tribune-Herald	0 times on:	
West Hawaii Today	times on:	
Other Publications:		0 times on:
And that affiant is not a party to	or in any way interested in the	above entitled matter.
Kimberly Masu		AND AND ADDRESS OF THE CONTRACT OF THE CONTRAC
Subscribed to and eworn before	me this 18th day of Neu	A.D. 20 23
ann		
Colleen E. Sofanaka, Notary Pul My commission expires: Jan 06	olic of the First Judicial Circuit 2024	State of Hawaii
Ad# 0001416015		ALOTADY : DE

PUBLIC

PUBLIC NOTICE (Docket No. 23-CA-PA-08)

The Department of Health, State of Hawaii, is notifying all interested persons of the report, "2023 Air Monitoring Network Plan." This report, based on 40 CFR 58.10, documents, and describes the establishment and maintenance of Hawaii's ambient

The report is available for public review during regular office hours, Monday through Friday, 7:45 a.m. to 4:15 p.m., at the following locations:

Clean Air Branch, Department of Health 2827 Waimano Home Road, Room 130 Pearl City, HI 96782

Hawaii.

- Hawaii District Health Office, Department of Health
- 1582 Kamehameha Ave., Hilo, Hawaii 96720 Clean Air Branch Kona, Keakealani Building, Department of Health 79-1020 Haukapila Street, Room 115, Kealakekua, Hawaii 96750

Kauai:

Kauai District Health Office, Department of Health 3040 Umi St., Lihue, Kauai 96766

Maui District Health Office, Department of Health (Environmental Health) 54 High St., Room 300, Wailuku, Maui 96793

The network plan is also available for inspection on the Hawaii Department of Health, Clean Air Branch website at http://health.hawaii.gov/cab. Interested persons may submit written comments addressed to the Department of Health at:

Clean Air Branch, Department of Health 2827 Waimano Home Road, Room 130 Pearl City, HI 96782

The comments must be postmarked or received by June 15, 2023. For additional information, contact Ms. Lisa Young of the Clean Air Branch in Honolulu at (808)

(SA1416015

ICSP.NO.:

STATE OF HAWAII, County of Maui. ss.

Commission exp: 07/02/2026

Brandy Emmanuel	being duly sworn
deposes and says, that she is in	Advertising Sales of
the Maui Publishing Co., Ltd., publ	
newspaper published in Wailuku, C	ounty of Maui, State of Hawaii;
that the ordered publication as toPUBLIC No	
of which the annexed is a true as	nd correct printed notice, was
published 1 time in THE MAUI on the 17th day of	
on the17th day ofM	
inclusive), to-wit: on	
May 17,	2023
and that affiant is not a party to or in entitled matter.	-
This 1 page PUB	LIC NOTICE dated
This _ ' page May 17,	, dated
was subscribed and sworn to be	10+1
by Brandy Emmanuel	Munimum.
Dymory Chasem	O6-397 O6-397 OBLIC WALLING OF HAMILIAN OF TARY OF TARY OF HAMILIAN OF TARY O
Notary Public, Second Judicial Circuit, State of Hawaii	PUBLIC A
Kimberly Uradomo Commission exp: 07/02/2026	THE OF HAMMIN

PUBLIC NOTICE (Docket No. 23-CA-PA-08)

The Department of Health, State of Hawaii, is notifying all interested persons of the report, "2023 Air Monitoring Network Plan." This report, based on 40 CFR 58.10, documents, and describes the establishment and main-tenance of Hawaii's ambient air monitoring network.

The report is available for public review during regular office hours, Monday through Friday, 7:45 a.m. to 4:15 p.m., at the following

Oahu:

• Clean Air Branch, Department of Health 2827 Waimano Home Road, Room 130 Pearl City, HI 96782

- · Hawaii District Health Office, Department of Health 1582 Kamehameha Ave., Hilo Hawaii 96720
- Clean Air Branch Kona, Keakealani Building, Department of Health 79-1020 Haukapila Street, Room 115 Kealakekua, Hawaii 96750

· Kauai District Health Office, Department of Health 3040 Umi St., Lihue, Kauai 96766

Maui:

· Maui District Health Office, Department of Health (Environmental Health)

54 High St., Room 300, Wailuku Maui 96793

The network plan is also available for inspection on the Hawaii Department of Health, Clean Air Branch website at http:// health.hawaii.gov/cab. Interested persons may submit written comments addressed to the Department of Health at:

Clean Air Branch, Department of Health 2827 Waimano Home Road, Room 130 Pearl City, HI 96782

The comments must be postmarked or received by June 15, 2023. For additional information, contact Ms. Lisa Young of the Clean Air Branch in Honolulu at (808)

(MN: May 17, 2023)

IN THE MATTER OF PUBLIC NOTICE

STATE OF HAWAII SS. City and County of Honolulu MAY 1 7 2023 Doc. Date: # Pages:_ Notary Name: COLLEEN E. SORANAKA First Judicial Circuit Affidavit of Doc. Description: Publication NOTARY **PUBLIC** Notary Signature Kimberly Masu being duly sworn, deposes and says that she is a clerk, duly authorized to execute this affidavit of Oahu Publications, Inc. publisher of The Honolulu Star-Advertiser, MidWeek, The Garden Island, West Hawaii Today, and Hawaii Tribune-Herald, that said newspapers are newspapers of general circulation in the State of Hawaii, and that the attached notice is true notice as was published in the Honolulu Star-Advertiser times on: MidWeek times on: The Garden Island times on: Hawaii Tribune-Herald times on: West Hawaii Today times on: 05/17/2023 Other Publications: times on:

PUBLIC NOTICE (Docket No. 23-CA-PA-08)

The Department of Health, State of Hawaii, is notifying all interested persons of the report, "2023 Air Monitoring Network Plan." This report, based on 40 CFR 58.10, documents, and describes the establishment and maintenance of Hawaii's ambient air monitoring network.

The report is available for public review during regular office hours, Monday through Friday, 7:45 a.m. to 4:15 p.m., at the following locations:

Clean Air Branch, Department of Health 2827 Waimano Home Road, Room 130 Pearl City, HI 96782

Hawaii:

- Hawali District Health Office, Department of Health 1582 Kamehameha Ave., Hilo, Hawaii 96720
- Clean Air Branch Kona, Keakealani Building, Department of Health 79-1020 Haukapila Street, Room 115, Kealakekua, Hawaii 96750

Kauai:

Kauai District Health Office, Department of Health 3040 Umi St., Lihue, Kauai 96766

Maui:

Maui District Health Office, Department of Health (Environmental Health) 54 High St., Room 300, Wailuku, Maui 96793

The network plan is also available for inspection on the Hawaii Department of Health, Clean Air Branch website at http://health.hawaii.gov/cab. Interested persons may submit written comments addressed to the Department of Health at:

> Clean Air Branch, Department of Health 2827 Waimano Home Road, Room 130 Pearl City, HI 96782

The comments must be postmarked or received by June 15, 2023. For additional information, contact Ms. Lisa Young of the Clean Air Branch in Honolulu at (808)

(WHT1416030 5/17/23)

And that affian	t is not a party to	or in any way	interested in	the above entitle	ed matter
00					

Kimberly Masu

Subscribed to and sworn before me this

EOFH

Colleen E. Soranaka, Notary Public of the First Judicial Circuit, State of Hawaii My commission expires: Jan 06 2024

0001416030 Ad#

NOTARY ICSP.NO.: **PUBLIC**

IN THE MATTER OF
PUBLIC NOTICE

}
}
SS.

Doc. Date:MAY 1 7 2023	# Pages:1
Notary Name: COLLEEN E. SORANAKA	First Judicial Circuit
Doc. Description: Affidavit of	LE SOP
Publication 153V 1 0 2022	NOTARY PUBLIC A
Notary Signature MAI 10 29 ate	OF HAWAIL

Kimberly Masu being duly sworn, deposes and says that she is a clerk, duly authorized to execute this affidavit of Oahu Publications, Inc. publisher of The Honolulu Star-Advertiser, MidWeek, The Garden Island, West Hawaii Today, and Hawaii Tribune-Herald, that said newspapers are newspapers of general circulation in the State of Hawaii, and that the attached notice is true notice as was published in the

Honolulu Star-Advertiser 0 times on:

MidWeek 0 times on:

The Garden Island 0 times on:

Hawaii Tribune-Herald 1 times on:

05/17/2023

West Hawaii Today 0 times on:

Other Publications: 0 times on:

And that affiant is not a party to or in any way interested in the above entitled matter.

9 Man

Kimberly Masu

STATE OF HAWAII

City and County of Honolulu

Subscribed to and sworn before me this May of Way A.D. 202

Colleen E. Soranaka, Notary Public of the First Judicial Circuit, State of Hawaii My commission expires: Jan 06 2024

Ad# 0001416028

NOTARY PUBLIC No. 90-263

PUBLIC NOTICE (Docket No. 23-CA-PA-08)

The Department of Health, State of Hawaii, is notifying all interested persons of the report, "2023 Air Monitoring Network Plan." This report, based on 40 CFR 58.10, documents, and describes the establishment and maintenance of Hawaii's ambient air monitoring network.

The report is available for public review during regular office hours, Monday through Friday, 7:45 a.m. to 4:15 p.m., at the following locations:

Oahu:

 Clean Air Branch, Department of Health 2827 Walmano Home Road, Room 130 Pearl City, HI 96782

Hawaii:

- Hawaii District Health Office, Department of Health 1582 Kamehameha Ave., Hilo, Hawaii 96720
- Clean Air Branch Kona, Keakealani Building, Department of Health 79-1020 Haukapila Street, Room 115, Kealakekua, Hawaii 96750

Kauai:

 Kauai District Health Office, Department of Health 3040 Umi St., Lihue, Kauai 96766

Maui:

Maul District Health Office, Department of Health (Environmental Health)
 54 High St., Room 300, Walluku, Maui 96793

The network plan is also available for inspection on the Hawaii Department of Health, Clean Air Branch website at http://health.hawaii.gov/cab. Interested persons may submit written comments addressed to the Department of Health at:

Clean Air Branch, Department of Health 2827 Waimano Home Road, Room 130 Pearl City, HI 96782

The comments must be postmarked or received by June 15, 2023. For additional information, contact Ms. Lisa Young of the Clean Air Branch in Honolulu at (808) 586-4200.

(HTH1416028 5/17/23)

ICSP.NO.:

Appendix B

Request to Close the Pearl City SLAMS Air Monitoring Station (150032004)

The State of Hawaii is requesting EPA approval to permanently discontinue the Pearl City (PC) ambient air monitoring station (150032004). The station was initially established to measure neighborhood concentrations in a commercial and residential area and has been in operation since 1994.

 PM_{10} data for 2022 showed the Honolulu MSA to be a low concentration area and is required to have one to two PM_{10} monitors. With this station's closure, there are two PM_{10} stations remaining in the Honolulu MSA, which meets the minimum PM_{10} monitoring requirements.

For PM_{2.5} the most recent 3-year design values in the Honolulu MSA were less than 85% of any PM_{2.5} NAAQS. The state currently operates three PM_{2.5} monitors in the MSA, which meets the minimum requirement of one monitor for the Honolulu MSA. The PC site was shut down on April 6, 2022, and the sampling equipment has been removed from the roof of the building and placed into storage, including the collocated PM_{2.5} FRM. DOH is requesting approval from EPA to permanently shut down this station.

According to 40 CFR 58.14, the state may request for discontinuance of a SLAMS station if any of the stated criteria are met and if requirements of Appendix D to Part 58 continues to be met. The PC station meets the following requirement for shutdown:

Any criteria SLAMS monitor which has been in attainment during the previous five years, has a probability of less than 10 percent of exceeding 80 percent of the applicable NAAQS during the next three years, and which is not specifically required by an attainment or maintenance plan.

II. Data in Support of Discontinuing the PC Station

To comply with the removal requirements based on past and future expected attainment for all applicable NAAQS, the following tests must be met:

- 1) The PM₁₀ and PM_{2.5} monitors are currently in attainment and have been in attainment during the previous five years;
- The probability is less than 10% that the monitors will exceed 80% of the applicable NAAQS during the next three years based on past concentrations, trends, and variability;
- 3) The monitors are not required by an attainment or maintenance plan; and
- 4) The monitors are not the last monitors in a nonattainment or maintenance area plan.

The State of Hawaii is in attainment for all NAAQS and therefore, PC is not specifically required for any attainment, non-attainment, or maintenance plan.

The following data is presented in support of station shutdown based on past compliance with, and the expectation that the monitors would not exceed all applicable NAAQS in the future.

Table AB-1. 2017-2021 Attainment of PM₁₀ and PM_{2.5} NAAQS at PC

	20	17	20	18	20	19	20	20	20	21
Pollutant Standard	Max	2 nd Max								
PM ₁₀ 24-hr Ave. (<150 μg/m³)	39	38	34	31	36	29	26	24	25	24
PM _{2.5} 24-hr Ave. (<35 μg/m³)	18	16	21	11	15	10	11	7	8	7
PM _{2.5} Annual Ave. (<12 μg/m ³)	4	.4	3	.0	3	.3	3	.2	3.	.2

To demonstrate a less than 10% probability that the monitors would exceed 80% of the applicable NAAQS, the following equation^a was applied:

$$\overline{X} + \frac{t * s}{\sqrt{n}} < 0.8 * NAAQS$$

Where: \bar{X} = the average design value for the last 5 years

t = student's t value for n-1 degrees of freedom at the 90%

confidence level

s = standard deviation of the design values

n = number of records

NAAQS = applicable standard

Table AB-2. Applicable NAAQS

Pollutant	Form of NAAQS	NAAQS	80% of NAAQS
PM ₁₀	24-hour	150 μg/m ³	120 μg/m³
PM _{2.5}	24-hour	35 μg/m ³	28 μg/m³
FIVI2.5	Annual average	12 µg/m ³	9.8 μg/m³

Conservatively using the 2017 to 2021 maximum values or design concentrations for all applicable NAAQS from Table AB-1, the probability that any monitor would exceed 80% of the NAAQS was computed.

Table AB-3. Probability Computations for Applicable NAAQS at PC

Pollutant & Averaging Time	Average (\overline{X}) 2017-2021	Standard Deviation (s)	Student's t value (<i>t</i>)	No. of values (n)	90% upper confidence interval	Is the result <80% of NAAQS?
PM ₁₀						
24-hour ¹	32 µg/m³	6.2	2.13	5	37.9	Yes <120 µg/m ³
24-hour ²	34 µg/m ³	6.3	2.13	5	40.0	Yes <120 µg/m ³
PM _{2.5}						
24-hour ³	9.4 μg/m ³	2.8	2.13	5	12.1	Yes <28 µg/m ³
Annual ³	3.5 µg/m ³	0.4	2.13	5	3.8	Yes <9.8 µg/m ³

¹ Max value

^a Equation used is from the EPA-454/D-07-001 document titled "Ambient Air Monitoring Network Assessment Guidance"

² Design concentration

³ Design Value

III. Continued Compliance with 40 CFR Part 58 Appendix D

Closing the PC air monitoring station will not affect compliance with the requirements of 40 CFR Part 58 Appendix D, "Network Design Criteria for Ambient Air Quality Monitoring."

PM₁₀ Design Criteria

One to two PM_{10} sites are required for a low concentration area with a population range of 500,000 to 1,000,000. The 2022 estimated census population for the Honolulu MSA was 995,638. With the closure of PC, two PM_{10} sites remain in the Honolulu MSA and the network would continue to meet PM_{10} design criteria.

PM_{2.5} Design Criteria

One PM_{2.5} site is required for a low concentration area with a population range of 500,000 to 1,000,000. The 2022 census population for the Honolulu MSA was 995,638. With the closure of PC, three PM_{2.5} sites remain in the Honolulu MSA and the network would continue to meet PM_{2.5} design criteria.

IV. Summary

Based on attainment with all applicable NAAQS in the past five or more years, a less than 10% probability of exceeding any NAAQS in the future, and continued compliance with network design criteria, closing the PC air monitoring station would meet the SLAMS discontinuance requirements of 40 CFR Part 58.

Appendix C

Request to Close the Kihei SLAMS Air Monitoring Station (150090006)

The State of Hawaii is requesting EPA approval to permanently discontinue the Kihei (KH) ambient air monitoring station (150090006). The station was established to monitor the impacts from sugar cane burning and started operating in 1999. The Hawaiian Commercial and Sugar Company shut down its sugar cane growing operations in 2016 after the last harvest. This site was shut down on March 30, 2022.

The most recent 3-year design values in the Maui MSA was less than 85% of any PM_{2.5} NAAQS. PM_{2.5} data for 2022 showed the Maui MSA to be a low concentration area, and with a population between 50,000 and 500,000, is not required to have any PM_{2.5} monitors. With this station closure, there will be one PM_{2.5} station remaining in the Maui MSA, which meets the minimum PM_{2.5} monitoring requirements. DOH is requesting approval from EPA to permanently shut down this station.

According to 40 CFR 58.14, the state may request for discontinuance of a SLAMS station if any of the stated criteria are met and if requirements of Appendix D to Part 58 continues to be met. The KH station meets the following requirement for shutdown:

Any criteria SLAMS monitor which has been in attainment during the previous five years, has a probability of less than 10 percent of exceeding 80 percent of the applicable NAAQS during the next three years, and which is not specifically required by an attainment or maintenance plan.

II. Data in Support of Discontinuing the Kihei Station

To comply with the removal requirements based on past and future expected attainment for all applicable NAAQS, the following tests must be met:

- 1) The PM_{2.5} monitor is currently in attainment and has been in attainment during the previous five years;
- The probability is less than 10% that the monitor will exceed 80% of the applicable NAAQS during the next three years based on past concentrations, trends, and variability;
- 3) The monitor is not required by an attainment or maintenance plan; and
- 4) The monitor is not the last monitor in a nonattainment or maintenance area plan.

The State of Hawaii is in attainment for all NAAQS and therefore, KH is not specifically required for any attainment, non-attainment, or maintenance plan.

The following data is presented in support of station shutdown based on past compliance with, and the expectation that the monitors would not exceed, all applicable NAAQS in the future.

Table AC-1. 2017-2021 Attainment of PM_{2.5} NAAQS at KH

	2017		2018		20	2019		2020		21
Pollutant Standard	Max	2 nd Max	Max	2 nd Max	Max	2 nd Max	Max	2 nd Max	Max	2 nd Max
PM _{2.5} 24-hr Ave. (<35 μg/m³)	29	26	13	12	85¹	46¹	14	13	15	7
PM _{2.5} Annual Ave. (<12 μg/m³)	4.	.2	4	.1	4.	2	3	.9	3.	.2

¹ Brush fire

To demonstrate a less than 10% probability that the monitors would exceed 80% of the applicable NAAQS, the following equation^a was applied:

$$\overline{X} + \frac{t * s}{\sqrt{n}} < 0.8 * NAAQS$$

Where: \bar{X} = the average design value for the last 5 years

t = student's t value for n-1 degrees of freedom at the 90%

confidence level

s = standard deviation of the design values

n = number of records

NAAQS = applicable standard

Table AC-2. Applicable NAAQS

Pollutant	Form of NAAQS	NAAQS	80% of NAAQS
PM _{2.5}	24-hour	35 μg/m³	28 μg/m³
	Annual average	12 μg/m³	9.8 µg/m³

Conservatively using the 2017 to 2021 design values for all applicable NAAQS from Table AC-1, the probability that any monitor would exceed 80% of the NAAQS was computed.

Table AC-3. Probability Computations for Applicable NAAQS at KH

	7 7 10 01 1 10					
Pollutant & Averaging Time	Average (\overline{X}) 2017-2021	Standard Deviation (s)	Student's t value (t)	No. of values (n)	90% upper confidence interval	Is the result <80% of NAAQS?
PM _{2.5}			0.40	_		.,
24-hour ¹	11.6 μg/m ³	1.1	2.13	5	12.7	Yes <28 μg/m ³
Annual ¹	3.9 µg/m ³	0.4	2.13	5	4.3	Yes <9.8 µg/m ³

¹ Design value

III. Continued Compliance with 40 CFR Part 58 Appendix D

Closing the KH air monitoring station will not affect compliance with the requirements of 40 CFR Part 58 Appendix D, "Network Design Criteria for Ambient Air Quality Monitoring."

^a Equation used is from the EPA-454/D-07-001 document titled "Ambient Air Monitoring Network Assessment Guidance"

PM_{2.5} Design Criteria

No PM_{2.5} site is required for a low concentration area with a population range of 50,000 to 500,000. The 2022 census population for the Maui MSA was 164,221. With the closure of KH, one PM_{2.5} site remains in the Maui MSA and the network would continue to meet PM_{2.5} design criteria.

IV. Summary

Based on attainment with all applicable NAAQS in the past five or more years, a less than 10% probability of exceeding any NAAQS in the future, and continued compliance with network design criteria, closing the KH air monitoring station would meet the SLAMS discontinuance requirements of 40 CFR Part 58.

Appendix D

Request to Discontinue PM_{2.5} and NO₂ Parameters at the Niumalu SPMS Air Monitoring Station (150070007)

The State of Hawaii is requesting EPA approval to permanently discontinue PM_{2.5} and NO₂ parameters at the Niumalu (NI) ambient air monitoring station (150070007). The station was initially established to monitor the impact of cruise ship emissions on nearby communities and started operating in April 2011. Sampling for PM_{2.5} and NO₂ was discontinued on March 31, 2022.

The Niumalu station is not located in an MSA and therefore no PM_{2.5} monitoring is required at this station. The PM_{2.5} concentrations at this station has historically been low.

The state currently has one SLAMS NO₂ station in the Honolulu MSA which meets the state's minimum requirement for NO₂ monitoring. The NI station is not located in an MSA and therefore no NO₂ monitoring is required at this station. The NO₂ concentrations at this station have also historically been low.

Although NI is designated an SPMS, it has been operating for more than two years and therefore the concentrations may be used for comparison with the NAAQS. DOH is requesting approval from EPA to permanently shut down the PM_{2.5} and NO₂ parameters at this station.

According to 40 CFR 58.14, the state may request for discontinuance of a SLAMS station if any of the stated criteria are met and if requirements of Appendix D to Part 58 continues to be met. The PM_{2.5} and NO₂ monitors at the NI station meet the following requirement for shutdown:

Any criteria SLAMS monitor which has been in attainment during the previous five years, has a probability of less than 10 percent of exceeding 80 percent of the applicable NAAQS during the next three years, and which is not specifically required by an attainment or maintenance plan.

II. Data in Support of Discontinuing PM_{2.5} and NO₂ Parameters at the NI Station

To comply with the removal requirements based on past and future expected attainment for all applicable NAAQS, the following tests must be met:

- 1) The PM_{2.5} and NO₂ monitors are currently in attainment and have been in attainment during the previous five years;
- 2) The probability is less than 10% that the monitors will exceed 80% of the applicable NAAQS during the next three years based on past concentrations, trends, and variability;
- 3) The monitors are not required by an attainment or maintenance plan; and
- 4) The monitors are not the last monitors in a nonattainment or maintenance area plan.

The State of Hawaii is in attainment for all NAAQS and therefore, NI is not specifically required for any attainment, non-attainment, or maintenance plan.

The following data is presented in support of station shutdown based on past compliance with, and the expectation that the monitors would not exceed, all applicable NAAQS in the future.

Table AD-1. 2017-2021 Attainment of PM_{2.5} and NO₂ NAAQS at NI

	20	2017		2018		2019		20	2021	
Pollutant Standard	Max	2 nd Max	Max	2 nd Max						
PM _{2.5} 24-hr Ave. (<35 µg/m³)	13	11	12	11	19	10	10	10	8	8
PM _{2.5} Annual Ave. (<12 μg/m³)	2.6		2.6		2.9		3.0		3.2	
NO ₂ 1-hr Ave. (<100 ppb)	38	35	47	47	46	43	41	41	19	18
NO ₂ Annual Ave. (<53 ppb)	1	.8.	4	.6	4	.3	3	.1	2.	.0

To demonstrate a less than 10% probability that the monitors would exceed 80% of the applicable NAAQS, the following equation^a was applied:

$$\overline{X} + \frac{t * s}{\sqrt{n}} < 0.8 * NAAQS$$

Where: \bar{X} = the average design value for the last 5 years

t = student's t value for n-1 degrees of freedom at the 90%

confidence level

s = standard deviation of the design values

n = number of records

NAAQS = applicable standard

Table AD-2. Applicable NAAQS

Pollutant	Form of NAAQS	NAAQS	80% of NAAQS	
DM	24-hour	35 μg/m ³	28 μg/m³	
PM _{2.5}	Annual average	12 μg/m ³	9.8 μg/m³	
NO-	1-hour	100 ppb	80 ppb	
NO ₂	Annual average	53 ppb	42.4 ppb	

Conservatively using the 2017 to 2021 maximum values or design concentrations for all applicable NAAQS from Table AD-1, the probability that any monitor would exceed 80% of the NAAQS was computed.

a Equation used is from the EPA-454/D-07-001 document titled "Ambient Air Monitoring Network Assessment Guidance"

Table AD-3. Probability Computations for Applicable NAAQS at NI

Pollutant & Averaging Time	Average (\overline{X}) 2017-2021	Standard Deviation (s)	Student's t value (t)	No. of values (n)	90% upper confidence interval	Is the result <80% of NAAQS?
PM _{2.5} 24-hour ¹	8 µg/m³	0.55	2.13	5	8.9	Yes <28 µg/m³
Annual ¹	2.9 μg/m ³	0.17	2.13	5	3.1	Yes <9.8 μg/m ³
NO ₂ 1-hour ¹	34 ppb	3.27	2.13	5	36.9	Yes <80 ppb
Annual ¹	3 ppb	1.3	2.13	5	4.4	Yes <42.4 ppb

Design value

III. Continued Compliance with 40 CFR Part 58 Appendix D

Discontinuing the PM_{2.5} and NO₂ parameters at the NI air monitoring station will not affect compliance with the requirements of 40 CFR Part 58 Appendix D, "Network Design Criteria for Ambient Air Quality Monitoring."

PM_{2.5} Design Criteria

Kauai is not a part of an MSA and therefore no PM_{2.5} monitor is required. With the discontinuation of PM_{2.5} parameter at NI, the network would continue to meet PM_{2.5} design criteria.

NO₂ Design Criteria

40 CFR Part 58, Appendix D Section 4.3.3 requires area wide NO₂ monitoring in the location of highest expected concentration in a CBSA with a population ≥1,000,000. The Honolulu MSA had a 2022 census population estimated at 995,638. Therefore, no NO₂ monitoring is currently required.

The state has one SLAMS NO₂ station remaining in the network, in the Honolulu MSA, which measures typical concentration in areas of high population density. With the discontinuation of NO₂ parameter at Niumalu, the network would continue to meet NO₂ design criteria.

IV. Summary

Based on attainment with all applicable NAAQS in the past five or more years, a less than 10% probability of exceeding any NAAQS in the future, and continued compliance with network design criteria, discontinuing the PM_{2.5} and NO₂ parameters at the NI air monitoring station would meet the SLAMS discontinuance requirements of 40 CFR Part 58.

Appendix E

Request to Discontinue CO and SO₂ Parameters at the Kapolei SLAMS Air Monitoring Station (150030010)

The State of Hawaii is requesting EPA approval to permanently discontinue CO and SO₂ parameters at the Kapolei (KA) ambient air monitoring station (150030010). The station is located in the Kapolei Business Park in the city of Kapolei. The area is a mix of business, commercial, and government activities surrounded by an ever-expanding residential community. The site is also approximately 1.25 km northeast (upwind) of the state's largest industrial park on the southwest coast of Oahu. The station has been operating as a SLAMS station since 2002. Sampling for CO was discontinued on March 31, 2022 and SO₂ on February 28, 2022.

On October 30, 2009, EPA approved the Kapolei station as the state's NCore site and in addition to the SLAMS parameters, the station began collecting the required NCore parameters on January 1, 2011. With trace CO and trace SO₂ being required parameters for NCore, the SLAMS CO and SO₂ monitors were shut down to reduce duplicative sampling and increase program efficiency. DOH is requesting approval from EPA to permanently shut down the CO and SO₂ parameters at the Kapolei SLAMS station.

According to 40 CFR 58.14, the state may request for discontinuance of a SLAMS station if any of the stated criteria are met and if requirements of Appendix D to Part 58 continues to be met. The CO and SO₂ monitors at the Kapolei station meet the following requirement for shutdown:

Any criteria SLAMS monitor which has been in attainment during the previous five years, has a probability of less than 10 percent of exceeding 80 percent of the applicable NAAQS during the next three years, and which is not specifically required by an attainment or maintenance plan.

II. Data in Support of Discontinuing CO and SO₂ Parameters at the Kapolei Station

To comply with the removal requirements based on past and future expected attainment for all applicable NAAQS, the following tests must be met:

- 1) The CO and SO₂ monitors are currently in attainment and have been in attainment during the previous five years;
- The probability is less than 10% that the monitors will exceed 80% of the applicable NAAQS during the next three years based on past concentrations, trends, and variability;
- 3) The monitors are not required by an attainment or maintenance plan; and
- 4) The monitors are not the last monitors in a nonattainment or maintenance area plan.

The State of Hawaii is in attainment for all NAAQS and therefore, the CO and SO₂ monitors at the Kapolei Station are not specifically required for any attainment, non-attainment, or maintenance plan.

The following data is presented in support of station shutdown based on past compliance with, and the expectation that the monitors would not exceed, all applicable NAAQS in the future.

Table AE-1. 2017-2021 Attainment of CO and SO₂ NAAQS at KA

	20	2017		2018		2019		20	2021	
Pollutant Standard	Max	2 nd Max	Max	2 nd Max						
CO 1-hr Ave. (<35 ppm)	1.7	1.7	3.2	3.2	0.9	0.5	1.2	0.6	0.8	0.6
CO 8-hr Ave. (<9 ppm)	1.1	1.0	2.5	2.5	0.3	0.3	0.4	0.3	0.4	0.3
SO ₂ 1-hr Ave. (<75 ppb)	12	10	13	7	15	13	9	8	4	4
SO ₂ 3-hr Ave. (<500 ppb)	6	6	10	6	13	8	5	5	3	2

To demonstrate a less than 10% probability that the monitors would exceed 80% of the applicable NAAQS, the following equation^a was applied:

$$\overline{X} + \frac{t * s}{\sqrt{n}} < 0.8 * NAAQS$$

Where:

 \overline{X} = the average design value for the last 5 years

t = student's t value for n-1 degrees of freedom at the 90%

confidence level

s = standard deviation of the design values

n = number of records

NAAQS = applicable standard

Table AE-2. Applicable NAAQS

Pollutant	Form of NAAQS	NAAQS	80% of NAAQS	
СО	1-hour	35 ppm	28 ppm	
	8-hour	9 ppm	7.2 ppm	
SO ₂	1-hour	75 ppb	60 ppb	
	3-hour	500 ppb	400 ppb	

Conservatively using the 2017 to 2021 maximum values or design concentrations for all applicable NAAQS from Table AE-1, the probability that any monitor would exceed 80% of the NAAQS was computed.

a Equation used is from the EPA-454/D-07-001 document titled "Ambient Air Monitoring Network Assessment Guidance"

Table AE-3. Probability Computations for Applicable NAAQS at KA

Pollutant & Averaging Time	Average (\(\overline{X} \) 2017-2021	Standard Deviation (s)	Student's t value (t)	No. of values (n)	90% upper confidence interval	Is the result <80% of NAAQS?
CO						
1-hour ¹	1.9 ppm	1.30	2.13	5	3.1	Yes <28 ppm
8-hour ¹	1.4 ppm	1.06	2.13	5	2.4	Yes <7.2 ppm
SO ₂						
1-hour ¹	9 ppb	1.34	2.13	5	9.9	Yes <60 ppb
3-hour ¹	5 ppb	0.92	2.13	5	5.9	Yes <400 ppb

¹ Design value

III. Continued Compliance with 40 CFR Part 58 Appendix D

Discontinuing the CO and SO₂ parameters at the Kapolei air monitoring station will not affect compliance with the requirements of 40 CFR Part 58 Appendix D, "Network Design Criteria for Ambient Air Quality Monitoring."

CO Design Criteria

40 CFR Part 58, Appendix D Section 4.2.2 requires one collocated CO monitor at near-road NO₂ sites in Core-Based Statistical Areas (CBSA) with populations ≥1,000,000. The Honolulu MSA had a 2022 census population estimated at 995,638 and therefore no CO monitor is currently required. There is currently one SLAMS CO monitor in addition to the required trace CO monitor at NCore. With the discontinuation of CO parameter at Kapolei, the network would continue to meet CO design criteria.

SO₂ Design Criteria

40 CFR Part 58, Appendix D Section 4.4.2, requires the use of the Population Weighted Emissions Index (PWEI) calculation to determine SO₂ monitoring requirements, and accordingly, Hawaii is currently required to operate one SO₂ monitor in the Honolulu MSA. The state currently has three SO₂ monitors in the Honolulu MSA, one SLAMS (DH), one SLAMS/DRR (KE), and one trace SO₂ monitor at the NCore station, which meets the minimum number of required SO₂ stations. With the discontinuation of SO₂ parameter at Kapolei, the network would continue to meet SO₂ design criteria.

IV. Summary

Based on attainment with all applicable NAAQS in the past five or more years, a less than 10% probability of exceeding any NAAQS in the future, and continued compliance with network design criteria, discontinuing the CO and SO₂ parameters at the Kapolei air monitoring station would meet the SLAMS discontinuance requirements of 40 CFR Part 58.

Appendix F

Request to Close the Honaunau SPMS Air Monitoring Station (150013032)

The State of Hawaii is requesting EPA approval to permanently discontinue the Honaunau (HN) ambient air monitoring station (150013032). This temporary SPMS site began collecting PM_{2.5} data in August 2018. The main purpose was to address air quality on the west side of Hawaii Island due to the 2018 LERZ Kilauea volcano eruption. Due to budgetary and personnel considerations, a decision was made to shut down the monitor on January 5, 2022 since there are four other PM_{2.5} monitors operating on the west side of Hawaii Island.

Hawaii Island is not a part of an MSA and therefore is not required to have any PM_{2.5} monitors. DOH is requesting approval from EPA to permanently shut down this station.

The HN station operated for more than three years and thus the concentrations may be used for NAAQS comparison. According to 40 CFR 58.14, the state may request for discontinuance of a SLAMS station if any of the stated criteria are met and if requirements of Appendix D to Part 58 continues to be met. The HN station meets the following requirement for shutdown:

Any criteria SLAMS monitor which has been in attainment during the previous five years, has a probability of less than 10 percent of exceeding 80 percent of the applicable NAAQS during the next three years, and which is not specifically required by an attainment or maintenance plan.

II. Data in Support of Discontinuing the Honaunau Station

To comply with the removal requirements based on past and future expected attainment for all applicable NAAQS, the following tests must be met:

- 1) The PM_{2.5} monitor is currently in attainment and has been in attainment during the previous five years;
- 2) The probability is less than 10% that the monitor will exceed 80% of the applicable NAAQS during the next three years based on past concentrations, trends, and variability;
- 3) The monitor is not required by an attainment or maintenance plan; and
- 4) The monitor is not the last monitor in a nonattainment or maintenance area plan.

The State of Hawaii is in attainment for all NAAQS and therefore, Honaunau is not specifically required for any attainment, non-attainment, or maintenance plan.

The following data is presented in support of station shutdown based on past compliance with, and the expectation that the monitors would not exceed, all applicable NAAQS in the future.

Table AF-1. 2017-2021 Attainment of PM_{2.5} NAAQS at HN

	2017		2018 ¹		2019		2020 ²		2021	
Pollutant Standard	Max	2 nd Max	Max	2 nd Max	Max	2 nd Max	Max	2 nd Max	Max	2 nd Max
PM _{2.5} 24-hr Ave. (<35 μg/m³)	n/a	n/a	n/a	n/a	11	5	14	12	14	12
PM _{2.5} Annual Ave. (<12 μg/m³)	n,	/a	n,	/a	2.	.4	2	.6	1.	.9

¹ Partial year, data not included, monitor began operating 8/16/18.

To demonstrate a less than 10% probability that the monitors would exceed 80% of the applicable NAAQS, the following equation^a was applied:

$$\overline{X} + \frac{t * s}{\sqrt{n}} < 0.8 * NAAQS$$

Where: \bar{X} = the average design value for the last 5 years

t = student's t value for n-1 degrees of freedom at the 90%

confidence level

s = standard deviation of the design values

n = number of records

NAAQS = applicable standard

Table AF-2. Applicable NAAQS

Pollutant	Form of NAAQS	NAAQS	80% of NAAQS
PM _{2.5}	24-hour	35 μg/m³	28 μg/m³
	Annual average	12 μg/m³	9.8 μg/m³

Conservatively using the 2019 to 2021 (only years with compete data available) design values for all applicable NAAQS from Table AC-1, the probability that any monitor would exceed 80% of the NAAQS was computed.

Table AF-3. Probability Computations for Applicable NAAQS at HN

Pollutant & Averaging	Average (\overline{X})	Standard	Student's t	No. of	90% upper confidence	Is the result <80% of
Time	2019-2021	Deviation (s)	value (t)	values (n)	interval	NAAQS?
PM _{2.5}						
24-hour ¹	5.8 μg/m ³	1.42	2.92	3	8.1	Yes <28 μg/m ³
Annual ¹	2.3 µg/m ³	0.12	2.92	3	2.5	Yes <9.8 µg/m ³

¹ Design value using 3 years of data from 2019 to 2021.

III. Continued Compliance with 40 CFR Part 58 Appendix D

Closing the HN air monitoring station will not affect compliance with the requirements of 40 CFR Part 58 Appendix D, "Network Design Criteria for Ambient Air Quality Monitoring."

² Data completeness <50% in Q3 and Q4.

^a Equation used is from the EPA-454/D-07-001 document titled "Ambient Air Monitoring Network Assessment Guidance"

PM_{2.5} Design Criteria

Hawaii Island is not a part of an MSA and therefore is not required to have any PM_{2.5} monitors. With the closure of Honaunau, thirteen PM_{2.5} sites remain in the state with nine on Hawaii Island alone, the network would continue to meet PM_{2.5} design criteria.

IV. Summary

Based on attainment with all applicable NAAQS in the past five or more years, a less than 10% probability of exceeding any NAAQS in the future, and continued compliance with network design criteria, closing the Honaunau air monitoring station would meet the SLAMS discontinuance requirements of 40 CFR Part 58.

Appendix G

AQS Reports in Support of Requests for Closures and Discontinuations

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

User ID: XGSWU MAXIMUM VALUES REPORT

Report Request ID: 2075943 Report Code: AMP440 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 2004

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS			SORT ORDER	
Option Type	Option Value	Order	Column	
AGENCY ROLE	PQAO	1	PARAMETER_CODE	_
EVENTS PROCESSING	REPORT ALL EVENT RECORDS	2	STATE_CODE	
MERGE PDF FILES	YES	3	DURATION_CODE	
		4	DATES	
		5	COUNTY_CODE	
		6	SITE_ID	
		7	POC	
		8	EDT_ID	

DATE CRITERIA

Start Date End Date

2017 2021

APPLICABLE STANDARDS

Standard Description

CO 8-hour 1971

Lead 3-Month 2009

Lead 3-Month PM10 Surrogate 2009

NO2 Annual 1971

Ozone 8-hour 2015

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

EXCEPTIONAL DATA TYPES

EDT	DESCRIPTION
0	NO EVENTS
1	EVENTS EXCLUDED
2	EVENTS INCLUDED
5	EVENTS WITH CONCURRENCE EXCLUDED

PM10 Total 0-10um STP (81102)

MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration: Year:	Hawaii 1 HOUR 2017						Maximum Valu	Sec	Primary: condary: Unit: Mic: (25	-	ubic met	er
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-003-2004	POC 3	City Name Honolulu	122	Methods	6th Max 125	7th Max 106	8th Max 99	9th Max 96	10th Max 74	Obs 8406	Exc	ID 0
		Pearl City			03/25:22	01/01:00	12/31:22	12/31:23	01/01:01			
					74	72	64	57	56			
					12/31:21	06/26:06	03/10:09	07/26:10	01/21:22			
					PM10 Total 0-	-10um STP (811	.02)					
State: Duration:	Hawaii 1 HOUR								Primary:	,		
Year:	2018						Maximum Valu	0 5	Unit: Mic: (25	=	ubic met	er
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-003-2004	POC 3	City Name Honolulu	122	Methods	6th Max 467	7th Max 64	8th Max 61	9th Max 56	10th Max 55	Obs 8501	Exc	ID 0
		Pearl City			01/01:00	04/20:12	11/18:22	11/28:14	02/15:13			
					55	54	54	54	53			
					12/26:12	02/27:08	07/27:13	10/15:20	05/19:10			
					PM10 Total 0-	-10um STP (811	.02)					
State: Duration:	Hawaii 1 HOUR 2019								Primary: condary: Unit: Mic:	rograms/g	ubic mot	or
Year:	2017						Maximum Valu	es	(25	=	abic met	CI

1st Max

6th Max

143

10/29:20

61

02/10:12

Methods

122

County Name

City Name

Honolulu

Pearl City

Site ID

15-003-2004

POC

3

2nd Max

7th Max

97

10/23:06

60

01/01:00

3rd Max

8th Max

80

06/17:13

59

03/17:12

4th Max

9th Max

69

04/08:06

57

01/26:01

5th Max

10th Max

67

04/01:06 57

02/09:12

Num

Obs

8620

Num

Exc

EDT

ID

0

UNITED STATES ENVIRONMENTAL PROCTECTION AGENCY

AIR QUALITY SUBSYSTEM MAXIMUM VALUES REPORT

Feb. 6, 2023

PM10 Total 0-10um STP (81102)

State: Duration:	Hawaii 1 HOUR								Primary:			
Year:	2020								Unit: Micr	ograms/c	ubic met	er
							Maximum Valu	es	(25	C)		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-2004	3	Honolulu	122		119	61	59	57	55	8470		0
		Pearl City			01/01:00	01/15:13	02/14:11	01/08:13	01/08:15			
					54	54	52	51	49			
					01/09:16	02/14:09	01/27:14	03/23:13	01/01:11			
					PM10 Total 0-	10um STP (81	102)					
State:	Hawaii								Primary:			
Duration:	1 HOUR								condary:			
Year:	2021								Unit: Micr	ograms/c	ubic met	er
							Maximum Valu	es	(25	C)		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-2004	3	Honolulu	122		74	69	57	42	42	8235		0
		Pearl City			02/04:10	02/26:12	01/01:00	03/21:14	10/22:09			
					40	40	40	39	39			
					11/17:10	11/19:09	11/23:09	03/02:11	03/21:12			
					PM10 Total 0-	10um STP (81	102)					
State: Duration:	Hawaii 24-HR BI	K AVG							Primary: 150 condary: 150			
Year:	2017								Unit: Micr	ograms/c	ubic met	er
							Maximum Valu	es	(25	C)		
-1		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-2004	3	Honolulu	122		39	38	36	35	34	350	0	0
		Pearl City			01/22:00	01/12:00	01/14:00	01/11:00	01/13:00			
					34	33	32	30	30			
					02/01:00	02/19:00	01/15:00	01/19:00	01/21:00			

MAXIMUM VALUES REPORT

Feb. 6, 2023

PM10 Total 0-10um STP (81102)

State: Duration: Year:	Hawaii 24-HR BI 2018	.K AVG					Maximum Valu	Sec	-	150 150 Micrograms (25 C)	/cubic met	er
-1		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	k Num	Num	EDT
Site ID 15-003-2004	POC 3	City Name Honolulu	122	Methods	6th Max 34	7th Max 31	8th Max 27	9th Max 23	10th Ma 23	x Obs 357	Exc 0	ID O
		Pearl City			01/01:00	02/27:00	02/28:00	10/29:00	12/05:0	0		
					22	22	22	22	22			
					01/05:00	02/09:00	05/20:00	08/01:00	11/18:0	0		
					PM10 Total 0-	-10um STP (81	102)					
State: Duration: Year:	Hawaii 24-HR BI 2019	LK AVG							-	150 150 Micrograms	/cubic met	er
ieai.							Maximum Valu	es		(25 C)		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	x Num	Num	EDT
Site ID 15-003-2004	POC 3	City Name Honolulu	122	Methods	6th Max 36	7th Max 29	8th Max 27	9th Max 26	10th Ma 26	x Obs 363	Exc 0	ID O
		Pearl City			03/11:00	04/13:00	04/14:00	01/26:00	01/28:0	0		
					26	25	24	23	23			
					03/17:00	04/12:00	11/26:00	02/09:00	04/11:0	0		
					PM10 Total 0-	-10um STP (81	102)					
State: Duration: Year:	Hawaii 24-HR BI 2020	LK AVG							-	150 150 Micrograms	/cubic met	er
ieai.							Maximum Valu	es		(25 C)		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	x Num	Num	EDT
Site ID 15-003-2004	POC 3	City Name Honolulu	122	Methods	6th Max 26	7th Max 24	8th Max 22	9th Max 22	10th Ma 20	.x Obs	Exc 0	ID 0
		Pearl City			01/13:00	01/08:00	01/15:00	02/14:00	01/07:0	0		
					20	20	20	20	20			
					01/09:00	01/21:00	02/09:00	03/01:00	06/13:0	0		

MAXIMUM VALUES REPORT

Feb. 6, 2023

PM10 Total 0-10um STP (81102)

State: Duration: Year:	Hawaii 24-HR BL 2021	K AVG							-	50 50 icrograms/c	ubic met	er
1001.							Maximum Valu	es	(25 C)		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-003-2004	POC 3	City Name Honolulu	122	Methods	6th Max 25	7th Max 24	8th Max 22	9th Max 22	10th Max 22	Obs 345	Exc 0	ID O
		Pearl City			03/21:00	03/22:00	02/26:00	03/01:00	10/09:00			
					20	20	20	19	19			
					03/02:00	03/19:00	12/09:00	01/26:00	02/23:00			
					PM2.5 - Local 0	Conditions (8	8101)					
State: Duration:	Hawaii 1 HOUR								Primary:			
Year:	2017									icrograms/c	ubic met	er
							Maximum Valu			LC)		
Site ID	POC	County Name		Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
15-003-2004	4	City Name Honolulu	170	Hechous	6th Max 79.0	7th Max 76.0	8th Max 71.0	9th Max 60.0	10th Max 54.0	Obs 8590	Exc	ID O
		Pearl City			12/31:22	01/01:00	12/31:23	12/31:21	01/01:01			
					41.0	37.0	28.0	26.0	25.0			
					09/21:16	12/31:20	03/13:20	01/12:00	03/13:15			
					PM2.5 - Local (Conditions (8	8101)					
State: Duration:	Hawaii 1 HOUR								Primary:			
Year:	2018									icrograms/c	ubic met	er
							Maximum Valu			LC)		
Site ID	POC	County Name		Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
15-003-2004	4	City Name Honolulu	170	110011040	6th Max 364.0	7th Max 32.0	8th Max 32.0	9th Max 27.0	10th Max 27.0	Obs 8381	Exc	ID O
		Pearl City			01/01:00	01/01:01	12/31:23	07/22:15	12/31:22			
					22.0	21.0	21.0	21.0	20.0			
					11/18:22	01/31:09	06/20:11	07/02:16	01/31:10			

MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration:	Hawaii 1 HOUR 2019							Primary: condary: Unit: Mic	rograms/c	ubic met	er
Year:	2013					Maximum Valu	es	(LC	-	u210 m00	01
Site ID	POC	County Name City Name	Methods	1st Max 6th Max	2nd Max 7th Max	3rd Max 8th Max	4th Max 9th Max	5th Max 10th Max	Num Obs	Num Exc	EDT ID
15-003-2004	4	Honolulu	209 170	42.0	33.0	30.0	21.0	21.0	8619		0
		Pearl City		01/01:00	12/18:17	10/29:20	03/11:08	03/11:09			
				20.0	20.0	20.0	18.0	18.0			
				03/11:06	03/11:10	04/12:18	03/17:12	12/31:23			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	1 HOUR							condary:			
Year:	2020							Unit: Mic	rograms/c	ubic met	er
						Maximum Valu	es	(LC)		
a.L. TD	500	County Name	26 1 1	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-2004	4	Honolulu	209	144.0	77.0	71.0	68.0	26.0	8269		0
		Pearl City		03/27:11	01/01:00	01/26:12	03/25:13	10/26:15			
				25.0	21.0	21.0	21.0	20.0			
				12/31:23	04/08:14	07/23:13	11/19:09	03/17:09			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	1 HOUR						Sec	condary:			
Year:	2021							Unit: Mic	rograms/c	ubic met	er
						Maximum Valu	es	(LC)		
Site ID	POC	County Name	Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
15-003-2004	4	City Name Honolulu	Methods 209	6th Max 43.0	7th Max 23.0	8th Max 23.0	9th Max 19.0	10th Max 19.0	Obs 8122	Exc	ID O
		Pearl City		01/01:00	06/17:08	12/31:23	03/15:12	04/27:09			
				19.0	19.0	19.0	18.0	18.0			
				05/21:07	05/24:07	08/16:14	06/22:07	07/14:08			

MAXIMUM VALUES REPORT

Feb. 6, 2023

PM2.5 - Local Conditions (88101)

State: Duration: Year:	Hawaii 24 HOUR 2020								Primary: condary: Unit: Mid	crograms/c	ubic met	er
ieai.							Maximum Valu	es	(LC	-		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-003-2004	POC 6	City Name Honolulu	142	Methods	6th Max 5.0	7th Max 5.0	8th Max 4.8	9th Max 4.6	10th Max 4.4	Obs 30	Exc	ID 0
		Pearl City			05/09:00	12/05:00	10/06:00	06/14:00	11/23:00			
					4.1	4.1	4.1	4.0	3.9			
					07/26:00	09/06:00	11/11:00	06/08:00	05/15:00			
					PM2.5 - Local (Conditions (8	8101)					
State:	Hawaii								Primary:			
Duration:	24 HOUR							Sec	condary:	,		
Year:	2021						Maximum Valu		Unit: Mic	-	ubic met	er
		G Name			1.1.26	0.1.						
Site ID	POC	County Name City Name		Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num Obs	Num Exc	EDT ID
15-003-2004	6	Honolulu	142		6th Max 5.7	7th Max 5.0	8th Max 5.0	9th Max 4.8	10th Max 4.6	54	EXC	0
10 000 2001	· ·	Pearl City			01/22:00	01/28:00	11/12:00	02/21:00	02/09:00	0.1		Ü
		rearr orey										
					4.6	4.5	4.5	4.3	4.0			
					12/06:00	03/29:00	11/24:00	07/27:00	02/15:00			
					PM2.5 - Local (Conditions (8	8101)					
State:	Hawaii								Primary:			
Duration:	24-HR BL	K AVG							condary:			
Year:	2017								Unit: Mid	crograms/c	ubic met	er
							Maximum Valu	es	(LC	C)		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-2004	4	Honolulu	170		18.2	16.2	16.1	15.6	15.3	358		0
		Pearl City			03/13:00	02/04:00	11/02:00	01/12:00	01/14:00			
					14.3	14.2	14.1	14.0	13.4			
					10/01:00	01/11:00	03/10:00	02/03:00	12/31:00			

Page 7 of 9

MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration:	Hawaii 24-HR B: 2018	LK AVG						Primary: condary: Unit: Mic:	mograma / s	ubia mot	
Year:	2010					Maximum Valu	es	(LC)		ubic mec	EI
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	, Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-2004	4	Honolulu	170	21.0	10.5	10.3	10.0	9.9	349		0
		Pearl City		01/01:00	02/13:00	06/16:00	04/10:00	04/11:00			
				9.8	9.1	8.8	8.2	7.9			
				04/09:00	04/01:00	08/01:00	03/30:00	01/27:00			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	24-HR B	LK AVG					Sec	condary: Unit: Mic:	roarams/c	ubic met	er
Year:	2013					Maximum Valu	es	(LC)		ubic mec	CI
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-2004	4	Honolulu	170 209	14.7	9.6	8.8	6.8	6.8	359		0
		Pearl City		03/11:00	04/13:00	03/17:00	04/12:00	04/14:00			
				6.6	6.5	6.3	6.3	6.2			
				04/11:00	01/26:00	04/05:00	12/24:00	04/23:00			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	24-HR B	LK AVG					Sec	condary:			
Year:	2020							Unit: Mic	rograms/c	ubic met	er
						Maximum Valu	es	(LC)	1		
Site ID	POC	County Name	Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
	4	City Name Honolulu	209	6th Max	7th Max 7.2	8th Max 7.0	9th Max 6.7	10th Max 6.6	Obs 344	Exc	ID 0
15-003-2004	4	Pearl City	209	10.7 03/27:00	10/08:00	03/25:00	10/13:00	12/31:00	344		U
				6.3	6.2	6.1	6.0	6.0			
				01/13:00	01/01:00	03/01:00	02/09:00	10/09:00			

MAXIMUM VALUES REPORT

Feb. 6, 2023

PM2.5 - Local Conditions (88101)

State: Hawaii Primary:

Duration: 24-HR BLK AVG Secondary:

Duration:	2 1 1111 2	ALIC 1110					50.	condary.			
Year:	2021							Unit: Mic	rograms/c	ubic met	er
						Maximum Valu	es	(LC)		
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-2004	4	Honolulu	209	8.0	6.7	6.5	6.4	6.2	338		0
		Pearl City		11/13:00	10/09:00	04/20:00	03/21:00	10/10:00			
				6.1	6.1	6.0	5.8	5.8			

01/15:00 03/22:00 01/14:00 01/22:00 01/27:00

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

User ID: XGSWU MAXIMUM VALUES REPORT

Report Request ID: 2076009 Report Code: AMP440 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 009 0006

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS	SELECTED OPTIONS						
Option Type	Option Value	Order	Column				
AGENCY ROLE	PQAO	1	PARAMETER_CODE				
EVENTS PROCESSING	REPORT ALL EVENT RECORDS	2	STATE_CODE				
MERGE PDF FILES	YES	3	DURATION_CODE				
		4	DATES				
		5	COUNTY_CODE				
		6	SITE_ID				
		7	POC				
		8	EDT_ID				

DATE CRITERIA

Start Date End Date

2017 2021

APPLICABLE STANDARDS

Standard Description

CO 8-hour 1971

Lead 3-Month 2009

Lead 3-Month PM10 Surrogate 2009

NO2 Annual 1971

Ozone 8-hour 2015

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

EXCEPTIONAL DATA TYPES

EDT	DESCRIPTION
0	NO EVENTS
1	EVENTS EXCLUDED
2	EVENTS INCLUDED
5	EVENTS WITH CONCURRENCE EXCLUDED

MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration:	Hawaii 1 HOUR							Primary:	,		
Year:	2017					Maximum Valu	0.0	Unit: Mic (LC	=	ubic met	er
				4	0 1 14						
Site ID	POC	County Name	Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num Exc	EDT
15-009-0006	2	City Name Maui	170	6th Max 119.0	7th Max 91.0	8th Max 82.0	9th Max 78.0	10th Max 71.0	Obs 8395	EXC	ID 0
		Kihei		06/29:15	01/21:23	06/29:13	06/29:16	06/29:12			
				69.0	68.0	66.0	65.0	65.0			
				01/21:14	01/22:00	06/30:14	06/29:11	06/29:14			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	1 HOUR 2018						560	condary: Unit: Mic	roaroma/a	ubia mot	or
Year:	2010					Maximum Valu	e s	(LC	=	ubic mec	eı
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	, Num	Num	EDT
Site ID	POC	City Name	Methods						Obs	Exc	ID
15-009-0006	2	Maui	170	6th Max 61.0	7th Max 47.0	8th Max 43.0	9th Max 40.0	10th Max 40.0	8129	EXC	0
		Kihei		07/03:17	03/06:13	05/20:13	05/22:14	05/22:15			
				38.0	37.0	33.0	31.0	31.0			
				07/03:15	03/06:14	05/22:12	01/17:15	07/04:19			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	1 HOUR							condary:			
Year:	2019							Unit: Mic	rograms/c	ubic met	er
icai.						Maximum Valu	es	(LC			
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-009-0006	2	Maui	209 170	506.0	481.0	410.0	200.0	185.0	8591		0
		Kihei		07/11:15	07/11:16	07/11:17	09/07:16	07/14:16			
				180.0	168.0	139.0	123.0	111.0			
				08/01:18	07/14:15	07/14:14	07/14:13	08/01:20			

MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration:	Hawaii 1 HOUR 2020								Primary:	mo anoma / a	ubia mat	
Year:	2020						Maximum Valu	A S	Unit: Mic: (LC)	-	ubic met	er
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	, Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-009-0006	2	Maui	209		58.0	7th Max 51.0	43.0	41.0	38.0	7962	2.10	0
		Kihei			06/01:06	01/07:11	01/07:12	01/07:15	01/08:14			
		111101										
					37.0	34.0	32.0	31.0	28.0			
					01/08:13	01/07:14	01/08:12	07/08:09	01/05:14			
					PM2.5 - Local 0	Conditions (8	8101)					
State:	Hawaii								Primary:			
Duration:	1 HOUR								condary:			
Year:	2021								Unit: Mic:	rograms/c	ubic met	er
ieai.							Maximum Valu	es	(LC)	=		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-009-0006	2	Maui	209		230.0	58.0	46.0	42.0	34.0	8482		0
		Kihei			12/31:20	12/31:22	07/04:20	10/09:14	06/28:10			
					33.0	29.0	23.0	22.0	21.0			
					08/19:16	07/04:21	06/11:14	10/09:13	01/02:15			
					PM2.5 - Local O	Conditions (8	8101)					
State:	Hawaii								Primary:			
Duration:	24-HR BI	K AVG							condary:			
Year:	2017								Unit: Mic	rograms/c	ubic met	er
							Maximum Valu	es	(LC))		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-009-0006	2	Maui	170		29.1	26.2	15.8	13.4	12.1	349		0
		Kihei			06/29:00	01/21:00	02/04:00	06/30:00	03/13:00			
					11.3	11.3	11.2	10.9	10.4			
					01/22:00	11/01:00	02/19:00	10/16:00	01/30:00			

MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration:	Hawaii 24-HR B 2018	LK AVG						Primary: condary: Unit: Mic	rograme/c	ubic met	or
Year:	2010					Maximum Valu	es	(LC	-	ubic mec	CI
Site ID	POC	County Name City Name	Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num Obs	Num Exc	EDT ID
15-009-0006	2	Maui	170	6th Max 12.7	7th Max 11.7	8th Max 11.6	9th Max 11.3	10th Max 11.0	339	EXC	0
		Kihei		02/13:00	07/04:00	06/16:00	07/03:00	04/01:00			
				10.9	10.6	10.2	9.8	9.7			
				05/22:00	03/06:00	07/02:00	03/31:00	07/15:00			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	24-HR B	LK AVG						condary:			
Year:	2019							Unit: Mic	=	ubic met	er
						Maximum Valu	es	(LC)		
Site ID	POC	County Name	Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
15-009-0006	2	City Name Maui	170 209	6th Max 84.5	7th Max 45.9	8th Max 40.5	9th Max 24.0	10th Max 23.6	0bs 357	Exc	ID O
		Kihei		07/11:00	07/14:00	08/01:00	07/13:00	09/07:00			
				19.3	18.8	16.9	16.2	13.2			
				07/31:00	11/30:00	07/15:00	07/25:00	07/19:00			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	24-HR B	LK AVG					Sec	condary:			
Year:	2020							Unit: Mic	-	ubic met	er
						Maximum Valu		(LC			
Site ID	POC	County Name	Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
15-009-0006	2	City Name Maui	209	6th Max 14.4	7th Max 13.0	8th Max 11.2	9th Max 10.3	10th Max 9.1	0bs 332	Exc	ID 0
		Kihei		01/07:00	01/08:00	07/09:00	07/08:00	01/09:00			
				8.5	7.2	6.9	6.5	6.3			
				01/06:00	01/05:00	08/30:00	10/08:00	01/13:00			

MAXIMUM VALUES REPORT

Feb. 6, 2023

PM2.5 - Local Conditions (88101)

State: Hawaii Primary:
Duration: 24-HR BLK AVG Secondary:

Year: 2021

Unit: Micrograms/cubic meter

					Maximum Values (LC)						
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-009-0006	2	Maui	209	15.4	6.7	6.6	6.4	6.1	355		0
		Kihei		12/31:00	10/09:00	03/25:00	04/20:00	03/26:00			
				5.7	5.7	5.7	5.6	5.4			
				01/15:00	02/15:00	07/04:00	04/21:00	02/22:00			

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

User ID: XGSWU MAXIMUM VALUES REPORT

2076010 Report Code: Feb. 6, 2023 Report Request ID: AMP 440

GEOGRAPHIC SELECTIONS

Tribal EPA

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 007 0007 42602

15 007 0007 88101

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

SELECTED OPTIONS

CRITERIA

2017

Option Type Option Value Order Column

AGENCY ROLE PQAO 1 PARAMETER_CODE

EVENTS PROCESSING REPORT ALL EVENT RECORDS 2 STATE_CODE

MERGE PDF FILES

3 DURATION_CODE

4 DATES

> 5 COUNTY_CODE

SORT ORDER

6 SITE_ID

7 POC

8 EDT_ID

DATE CRITERIA

2021

End Date Start Date Standard Description

Lead 3-Month 2009

Lead 3-Month PM10 Surrogate 2009

CO 8-hour 1971

APPLICABLE STANDARDS

NO2 Annual 1971

Ozone 8-hour 2015

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

EXCEPTIONAL DATA TYPES

EDT	DESCRIPTION
0	NO EVENTS
1	EVENTS EXCLUDED
2	EVENTS INCLUDED
5	EVENTS WITH CONCURRENCE EXCLUDED

MAXIMUM VALUES REPORT

Feb. 6, 2023

Nitrogen	dioxide	(NO2)	(42602)	

State: Duration:	Hawaii 1 HOUR							Primary:			
Year:	2017							Unit: Par	s per bi	llion	
						Maximum Valu	es				
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-007-0007	POC 1	City Name Kauai	Methods 099 212 186	6th Max 37.6	7th Max 35.3	8th Max 35.1	9th Max 33.1	10th Max 32.9	Obs 5979	Exc	ID O
		Not in a city		12/01:06	11/16:19	12/01:07	12/01:04	11/16:20			
				32.8	32.4	32.3	31.7	31.7			
				11/16:21	11/16:18	12/01:11	01/30:16	02/22:08			
				Nitrogen diox	ide (NO2) (42	602)					
State:	Hawaii							Primary:			
Duration:	1 HOUR						Sec	condary:			
Year:	2018							Unit: Par	s per bi	llion	
						Maximum Valu	es				
C'I. TD	Dog	County Name	Mat Davids	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-007-0007	POC 1	City Name Kauai	Methods 212	6th Max 46.7	7th Max 46.5	8th Max 45.1	9th Max 44.8	10th Max 44.6	Obs 7988	Exc	ID 0
		Not in a city		12/14:00	12/13:20	12/13:21	12/14:02	12/14:03			
				44.6	44.3	44.3	44.0	43.1			
				12/20:18	12/13:19	12/13:22	12/10:09	12/13:18			
				Nitrogen diox	ide (NO2) (42	602)					
State: Duration:	Hawaii 1 HOUR							Primary:			
Year:	2019							Unit: Par	s per bi	llion	
						Maximum Valu	es				
Site ID	POC	County Name	Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
15-007-0007	1	City Name Kauai	Methods 212	6th Max 46.2	7th Max 43.3	8th Max 43.2	9th Max 42.1	10th Max 41.7	Obs 8390	Exc	ID O
		Not in a city		04/15:08	03/07:18	03/07:08	03/07:19	04/13:08			
				41.0	40.8	40.6	40.0	39.9			
				03/08:02	03/07:17	03/08:08	01/03:19	03/08:04			

MAXIMUM VALUES REPORT

Feb. 6, 2023

Nitrogen dioxide (NO2) (42602)

State: Duration: Year:	Hawaii 1 HOUR 2020								Primary: condary: Unit: Par	ts per bi	llion	
							Maximum Valu	es				
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-007-0007	POC 1	City Name Kauai	212	Methods	6th Max 41.1	7th Max 40.7	8th Max 40.2	9th Max 38.8	10th Max 38.4	Obs 8528	Exc	ID 0
		Not in a city			02/21:00	03/06:03	03/06:05	03/06:04	02/26:16			
					38.1	37.9	37.9	37.4	37.0			
					02/26:09	01/20:09	02/28:06	01/09:08	03/06:07			
					Nitrogen diox:	ide (NO2) (42	602)					
State: Duration:	Hawaii 1 HOUR								Primary:			
Year:	2021						Maximum Valu	0.5	Unit: Part	s per bi	llion	
		Carrata Nama			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	NT	EDT
Site ID	POC	County Name City Name		Methods						Obs	Num Exc	ID
15-007-0007	1	Kauai	212		6th Max 18.9	7th Max 18.0	8th Max 17.0	9th Max 16.4	10th Max 16.2	8149	DAC	0
		Not in a city			02/21:07	10/07:07	12/18:20	12/18:16	12/18:17			
					15.5	15.4	14.8	14.6	13.8			
					04/05:08	12/18:18	12/18:21	03/27:06	05/07:19			
					PM2.5 - Local (Conditions (8	8101)					
State:	Hawaii								Primary:			
Duration:	1 HOUR								condary:			
Year:	2017								Unit: Mic:	rograms/c	ubic met	er
							Maximum Valu	es	(LC)	1		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-007-0007	POC 1	City Name Kauai	170	Methods	6th Max 108.0	7th Max 69.0	8th Max 24.0	9th Max 22.0	10th Max 20.0	Obs 8384	Exc	ID O
		Not in a city			07/04:20	01/01:00	07/04:21	12/31:22	12/05:22			
					19.0	19.0	18.0	18.0	17.0			
					12/03:06	12/31:21	03/14:15	03/14:16	01/12:00			

MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration:	Hawaii 1 HOUR							Primary:			
Year:	2018								crograms/c	ubic met	er
						Maximum Valu	es	(LO	2)		
-1		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-007-0007	POC 1	City Name Kauai	Methods 170	6th Max 28.0	7th Max 27.0	8th Max 26.0	9th Max 24.0	10th Max 23.0	Obs 7810	Exc	ID O
		Not in a city		12/31:21	03/30:20	03/30:17	03/30:18	01/01:02			
				23.0	22.0	22.0	21.0	21.0			
				08/30:19	03/30:19	07/04:19	03/30:16	03/31:17			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	1 HOUR						Sec	condary:			
Year:	2019								crograms/c	ubic met	er
						Maximum Valu	es	(LC	2)		
C:+- TD	DOG	County Name	Mathada	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-007-0007	1	Kauai	209 170	51.0	43.0	42.0	39.0	31.0	8210		0
		Not in a city		12/24:11	11/17:10	11/17:14	10/15:14	09/30:12			
				30.0	29.0	25.0	24.0	23.0			
				01/01:00	03/11:10	03/11:11	03/11:08	03/11:07			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	1 HOUR						Sec	condary:			
Year:	2020								crograms/c	ubic met	er
						Maximum Valu	es	(L(2)		
C'I - TD	Dog	County Name	M-11-1-	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-007-0007	POC 1	City Name Kauai	Methods 209	6th Max 26.0	7th Max 23.0	8th Max 19.0	9th Max 18.0	10th Max 18.0	Obs 7759	Exc	ID O
		Not in a city		07/26:07	03/06:17	08/04:01	02/29:11	03/18:11			
				17.0	17.0	17.0	17.0	16.0			
				03/24:09	03/24:13	05/07:09	07/09:11	01/09:19			

MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration:	Hawaii 1 HOUR								Primary:	,		
Year:	2021						Maximum Valu		Unit: Mic:	=	ubic met	er
		Great News			1.1.26.	0.1.					37	
Site ID	POC	County Name City Name		Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num Obs	Num Exc	EDT ID
15-007-0007	1	Kauai	209		6th Max 42.0	7th Max 20.0	8th Max 19.0	9th Max 17.0	10th Max 16.0	8193	EXC	0
		Not in a city			07/26:07	11/18:04	04/24:04	01/25:12	03/23:09			
					16.0	16.0	16.0	16.0	16.0			
					03/24:09	03/24:11	04/04:23	04/09:09	06/03:10			
					PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii 24-HR B	TH ANC							Primary: condary:			
Duration:	24-HR B 2017	LK AVG						Sec	condary: Unit: Mic:	roarams/a	ubic met	er
Year:	2017						Maximum Valu	es	(LC)	=	ubic mec	CI
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	, Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-007-0007	1	Kauai	170		13.2	11.2	11.1	10.2	10.0	350		0
		Not in a city			01/12:00	07/04:00	12/05:00	03/11:00	12/03:00			
					9.3	9.0	8.6	8.2	8.2			
					02/19:00	01/14:00	01/22:00	01/13:00	02/20:00			
					PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							:	Primary:			
Duration:	24-HR B	LK AVG						Sec	condary:			
Year:	2018								Unit: Mic:	_	ubic met	er
							Maximum Valu	es	(LC))		
Site ID	POC	County Name		Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
15-007-0007	1	City Name Kauai	170	Methods	6th Max 11.6	7th Max 11.3	8th Max 10.9	9th Max 10.0	10th Max 9.4	0bs 327	Exc	ID 0
		Not in a city			03/30:00	03/31:00	02/28:00	02/27:00	08/01:00			
					8.7	8.4	7.9	7.7	7.5			
					07/06:00	06/17:00	07/04:00	07/18:00	04/01:00			

UNITED STATES ENVIRONMENTAL PROCTECTION AGENCY

AIR QUALITY SUBSYSTEM

MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration:		BLK AVG						Primary:	,		
Year:	2019					Maximum Valu	0.5	Unit: Mic: (LC)		ubic met	er
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods						Obs	Exc	ID
15-007-0007	1	Kauai	170 209	6th Max 19.1	7th Max 9.6	8th Max 8.4	9th Max 8.1	10th Max 8.1	340	EAC	0
		Not in a city		03/11:00	03/17:00	02/09:00	01/26:00	12/21:00			
				7.9	7.5	7.5	7.4	6.9			
				01/29:00	11/23:00	12/24:00	03/10:00	12/17:00			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	24-HR	BLK AVG						condary:			
Year:	2020							Unit: Mic:	rograms/c	ubic met	er
						Maximum Valu	es	(LC))		
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-007-0007	1	Kauai	209	9.9	9.7	9.4	9.2	8.7	322		0
		Not in a city		01/13:00	01/09:00	02/14:00	01/15:00	03/01:00			
				8.4	8.3	7.7	7.6	7.5			
				01/12:00	01/10:00	01/08:00	05/08:00	01/14:00			
				PM2.5 - Local	Conditions (8	8101)					
State:	Hawaii							Primary:			
Duration:	24-HR	BLK AVG					Sec	condary:			
Year:	2021							Unit: Mic	rograms/c	ubic met	er
						Maximum Valu	es	(LC))		
-1		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-007-0007	1	Kauai	209	8.4	8.1	7.9	7.7	7.7	342		0
		Not in a city		02/27:00	02/22:00	02/23:00	02/26:00	03/01:00			
				7.7	7.2	7.1	7.1	7.0			
				03/21:00	02/28:00	01/26:00	01/27:00	03/22:00			

User ID: XGSWU MAXIMUM VALUES REPORT

2075946 Report Code: Feb. 6, 2023 Report Request ID: AMP 440

GEOGRAPHIC SELECTIONS

Tribal EPA

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 0010 42101 15 003 0010 42401

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

SELECTED OPTIONS

2021

CRITERIA

2017

Option Type Option Value Order Column

AGENCY ROLE PQAO 1 PARAMETER_CODE

EVENTS PROCESSING REPORT ALL EVENT RECORDS 2 STATE_CODE

3

MERGE PDF FILES

4 DATES 5 COUNTY_CODE

6 SITE_ID 7 POC

8 EDT_ID

DATE CRITERIA APPLICABLE STANDARDS

End Date Start Date Standard Description

Lead 3-Month 2009

Lead 3-Month PM10 Surrogate 2009

CO 8-hour 1971

SORT ORDER

DURATION_CODE

NO2 Annual 1971

Ozone 8-hour 2015

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

EXCEPTIONAL DATA TYPES

EDT	DESCRIPTION
0	NO EVENTS
1	EVENTS EXCLUDED
2	EVENTS INCLUDED
5	EVENTS WITH CONCURRENCE EXCLUDED

AIR QUALITY SUBSYSTEM MAXIMUM VALUES REPORT

Feb. 6, 2023

Carbon monoxide	(42101)
-----------------	---------

State: Duration: Year:	Hawaii 8-HR RU 2017	N AVG END HOUR					Maximum Value	Sec	Primary: 9 condary: 9 Unit: Part	is per mi	llion	
Site ID 15-003-0010	POC 1	County Name City Name Honolulu	093	Methods	1st Max 6th Max 1.1	2nd Max 7th Max 1.0	3rd Max 8th Max	4th Max 9th Max	5th Max 10th Max	Num Obs 7968	Num Exc 0	EDT ID 0
		Not in a city			12/31:15	12/27:01						
							Maximum Value	es				
O'L TD	DOG	County Name		ar	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-0010	2	Honolulu	593		.3	.3				7638	0	0
		Not in a city			01/05:08	01/09:08						
					Carbon mor	noxide (42101)						
State:	Hawaii								Primary: 9			
Duration:	8-HR RU	N AVG END HOUR						Sec	condary: 9			
Year:	2018								Unit: Part	s per mi	llion	
							Maximum Value	es				
a.,	200	County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-0010	1	Honolulu	093		2.5	2.5				8031	0	0
		Not in a city			04/03:07	05/19:23						

AIR QUALITY SUBSYSTEM

MAXIMUM VALUES REPORT

Feb. 6, 2023

					Carbon mor	noxide (42101)						
State: Duration: Year:	Hawaii 8-HR RUI 2018	N AVG END HOUR					Maximum Value	Sec	Primary: 9 condary: 9 Unit: Par	ts per mi	llion	
Site ID 15-003-0010	POC 2	County Name City Name Honolulu Not in a city	593	Methods	1st Max 6th Max .4 01/10:08	2nd Max 7th Max .3 01/10:13	3rd Max 8th Max	4th Max 9th Max	5th Max 10th Max	Num Obs 8118	Num Exc 0	EDT ID 0
					Carbon mor	noxide (42101)						
State: Duration: Year:	Hawaii 8-HR RUI 2019	N AVG END HOUR					Maximum Value	Sec	Primary: 9 condary: 9 Unit: Par	ts per mi	llion	
Site ID 15-003-0010	POC 1	County Name City Name Honolulu Not in a city	093	Methods	1st Max 6th Max .3 03/11:12	2nd Max 7th Max .3 03/20:06	3rd Max 8th Max	4th Max 9th Max	5th Max 10th Max	Num Obs 8327	Num Exc 0	EDT ID 0
Site ID 15-003-0010	POC 2	County Name City Name Honolulu Not in a city	593	Methods	1st Max 6th Max .3 01/07:07	2nd Max 7th Max .3 01/09:11	Maximum Value 3rd Max 8th Max	es 4th Max 9th Max	5th Max 10th Max	Num Obs 8091	Num Exc 0	EDT ID O
					Carbon mor	noxide (42101)						
State: Duration:	Hawaii 8-HR RUI	N AVG END HOUR							Primary: 9			

Unit: Parts per million

2020

Year:

AIR QUALITY SUBSYSTEM

MAXIMUM VALUES REPORT

Feb. 6, 2023

Carbon monoxide (42101)

State: Duration: Year:	Hawaii 8-HR RU 2020	N AVG END HOUR				Maximum Valu	Sec	Primary: 9 condary: 9 Unit: Part	s per mi	llion	
Site ID 15-003-0010	POC 1	County Name City Name Honolulu Not in a city	Method	1st Max 6th Max .4 03/04:06	2nd Max 7th Max .4 03/05:08	3rd Max 8th Max	4th Max 9th Max	5th Max 10th Max	Num Obs 8376	Num Exc O	EDT ID 0
Site ID 15-003-0010	POC 2	County Name City Name Honolulu Not in a city	Method 593	1st Max 6th Max .4 01/28:09	2nd Max 7th Max .3 01/22:07	Maximum Value 3rd Max 8th Max	es 4th Max 9th Max	5th Max 10th Max	Num Obs 8554	Num Exc 0	EDT ID 0
State: Duration: Year:	Hawaii 8-HR RU 2021	N AVG END HOUR			noxide (42101)	Maximum Valu	Sed	Primary: 9 condary: 9 Unit: Part	s per mi		
Site ID 15-003-0010	POC 1	County Name City Name Honolulu	Method	1st Max ds 6th Max .4	2nd Max 7th Max .4	3rd Max 8th Max	4th Max 9th Max	5th Max 10th Max	Num Obs 8298	Num Exc 0	EDT ID 0

11/17:08 12/02:11

Not in a city

AIR QUALITY SUBSYSTEM MAXIMUM VALUES REPORT

Feb. 6, 2023

Carbon monoxide (42101)

State: Duration: Year: Site ID 15-003-0010	Hawaii 8-HR RU 2021 POC 2	N AVG END HOUR County Name City Name Honolulu	593	Methods	1st Max 6th Max 2.0	2nd Max 7th Max 1.5	Maximum Valu 3rd Max 8th Max	Sec	Primary: 9 condary: 9 Unit: Part 5th Max 10th Max	s per mi Num Obs 8140	llion Num Exc 0	EDT ID 0
13-003-0010	2	Not in a city	393		08/24:20	08/24:16				8140	U	U
					Sulfur di	oxide (42401)						
State: Duration:	Hawaii 1 HOUR								Primary: 75			
Year:	2017								Unit: Par	s per bi	llion	
							Maximum Valu					
Site ID	POC	County Name		Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
15-003-0010	1	City Name Honolulu	060	noonodo	6th Max 12.4	7th Max 10.2	8th Max 8.6	9th Max 8.3	10th Max 7.0	Obs 8234	Exc 0	ID 0
		Not in a city			09/14:11	02/26:18	02/08:11	11/18:16	02/25:17			
					6.6	6.4	6.1	5.3	4.9			
					05/20:16	12/07:10	04/29:10	02/18:15	12/16:12			
							Maximum Valu	es				
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-003-0010	POC 2	City Name Honolulu	600	Methods	6th Max 18.3	7th Max 17.0	8th Max 10.6	9th Max 10.5	10th Max 8.9	Obs 7155	Exc 0	ID 0
		Not in a city			10/25:11	02/26:18	09/14:11	11/18:16	03/09:17			
					8.2	7.9	7.3	6.9	6.5			
					02/25:17	02/18:15	12/12:16	01/11:14	12/28:10			
					Sulfur di	oxide (42401)						
State: Duration: Year:	Hawaii 1 HOUR 2018								Primary: 75 condary: Unit: Par	s per bi	llion	

MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration: Year:	Hawaii 1 HOUR 2018						Maximum Valu	Sec	Primary: 75 condary: Unit: Part	is per bi	llion	
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-0010	1	Honolulu	060		12.9	6.6	6.3	6.2	6.2	8256	0	0
		Not in a city			06/20:13	05/03:14	04/28:15	04/05:08	09/19:12			
					4.9	4.9	4.8	4.6	3.9			
					02/24:12	10/14:11	03/28:11	07/02:14	01/10:13			
							Maximum Valu	es				
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-0010	2	Honolulu	600		21.5	12.9	12.8	9.6	9.4	8157	0	0
		Not in a city			06/20:13	05/03:13	01/29:17	02/24:11	09/19:12			
					9.3	8.0	7.7	7.4	7.0			
					10/14:11	05/05:09	01/27:13	05/04:09	11/23:16			
					Sulfur di	oxide (42401)						
QL all a									D. ' 75			
State:	Hawaii 1 HOUR								Primary: 75 condary:			
Duration: Year:	2019							500	Unit: Part	s per bi	llion	
icai.							Maximum Valu	es		-		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name		Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-0010	1	Honolulu	060		15.3	13.4	4.6	3.4	3.3	7762	0	0
		Not in a city			02/09:17	01/06:16	02/11:14	01/25:10	04/03:14			
					3.2	3.1	3.1	3.1	3.0			
					01/15:12	02/22:12	07/09:21	08/13:20	10/18:19			

AIR QUALITY SUBSYSTEM MAXIMUM VALUES REPORT

Feb. 6, 2023

2019							Primary: 75 condary: Unit: Part	s per bi	llion	
					Maximum Valu	es		F		
	County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
POC 2	City Name Honolulu	Methods 600	6th Max 15.8	7th Max 14.8	8th Max 11.2	9th Max 10.9	10th Max 8.3	Obs 8085	Exc 0	ID 0
	Not in a city		01/06:16	02/09:17	05/21:08	01/25:09	05/22:15			
			8.0	7.7	7.7	7.7	6.7			
			05/13:13	02/23:17	09/22:11	12/26:17	02/26:08			
			Sulfur di	oxide (42401)						
Hawaii 1 HOUR										
2020							=	s per bi	llion	
					Maximum Valu	es				
200	County Name	25 (1)	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
1 1	City Name Honolulu	Methods 060	6th Max 8.5	7th Max 8.3	8th Max 6.2	9th Max 5.8	10th Max 3.9	Obs 8262	Exc 0	ID O
	Not in a city		01/24:10	02/23:17	02/09:22	01/30:10	01/29:17			
			3.9	3.8	3.6	3.4	3.3			
			02/11:09	02/24:13	04/19:15	02/07:10	04/18:19			
					Maximum Valu	es				
	County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
POC 2	City Name Honolulu	Methods 560 600	6th Max 15.4	7th Max 15.4	8th Max 10.9	9th Max 8.9	10th Max 8.2	Obs 7843	Exc 0	ID O
	Not in a city		01/24:10	02/23:16	10/07:15	07/03:15	06/24:18			
			8.0	7.4	7.3	7.2	6.2			
			02/09:22	07/04:17	10/01:09	05/14:10	04/20:15			
			Sulfur di	oxide (42401)						
Hawaii 1 HOUR 2021							condary:	s per bi	llion	
	Hawaii HoUR 2020 POC 1 POC 2	County Name City Name Honolulu Not in a city County Name City Name City Name Honolulu Not in a city County Name City Name Honolulu Not in a city County Name City Name City Name Annolulu Not in a city Hawaii Hour	County Name POC City Name Methods POC City Name Methods Not in a city Hawaii HOUR POC City Name Methods Honolulu 060 Not in a city County Name Methods Honolulu 560 600 Not in a city Hawaii Hour Hawaii Hour	County Name	POC	County Name	County Name	County Name	County Name	County Name

MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration: Year:	Hawaii 1 HOUR 2021								Primary: 75 condary: Unit: Par	ts per bil	llion	
icai.							Maximum Valu	es		-		
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-003-0010	POC 1	City Name Honolulu	060	Methods	6th Max 4.0	7th Max 3.5	8th Max 2.8	9th Max 2.8	10th Max 2.3	Obs 5985	Exc 0	ID 0
		Not in a city			02/07:13	06/28:18	02/05:10	03/09:12	03/03:15			
					2.2	2.2	2.2	2.1	2.1			
					02/10:16	03/08:03	05/24:06	03/05:07	03/06:02			
							Maximum Valu	es				
		County Name			1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID 15-003-0010	POC 2	City Name Honolulu	560	Methods	6th Max 10.9	7th Max 9.8	8th Max 8.7	9th Max 5.8	10th Max 5.0	Obs 8354	Exc 0	ID O
		Not in a city			02/05:09	05/28:18	06/28:18	02/07:13	06/23:14			
					4.2	3.7	3.5	3.2	3.1			
					02/04:14	02/06:10	04/28:09	08/09:16	06/21:17			
					Sulfur di	oxide (42401)						
State:	Hawaii								Primary:			
Duration:	5 MINUT	∑							condary:			
Year:	2017								Unit: Par	ts per bil	lion	
							Maximum Valu	es				
Site ID	POC	County Name		Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
15-003-0010	7	City Name Honolulu	600	Methods	6th Max 28.2	7th Max 26.7	8th Max 26.6	9th Max 25.7	10th Max 25.0	Obs 94362	Exc	ID 0
		Not in a city			02/08:11	10/25:11	10/25:11	02/26:18	02/26:18			
					24.1	23.1	22.9	22.7	22.5			
					02/26:18	10/25:11	02/26:17	02/26:17	02/26:17			
					Sulfur di	oxide (42401)						
State:	Hawaii	_							Primary:			
Duration: Year:	5 MINUTI 2018	<u>s</u>						Sec	condary: Unit: Par	ts per bil	lion	

AIR QUALITY SUBSYSTEM MAXIMUM VALUES REPORT

Feb. 6, 2023

State: Duration: Year:	Hawaii 5 MINUTI 2018	Ξ					Sec	Primary: condary: Unit: Par	ts per bil	llion	
						Maximum Valu					
Site ID	POC	County Name	Methods	1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
15-003-0010	7	City Name Honolulu	600	6th Max 23.5	7th Max 23.3	8th Max 23.1	9th Max 22.9	10th Max 21.9	Obs 101275	Exc	ID 0
		Not in a city		06/20:13	06/20:13	06/20:13	06/20:13	06/20:13			
				21.6	21.2	20.7	20.6	19.8			
				06/20:13	06/20:13	06/20:13	06/20:13	06/20:13			
				Sulfur di	oxide (42401)						
State:	Hawaii							Primary:			
Duration:	5 MINUT	Ξ						condary:			
Year:	2019							Unit: Par	ts per bil	llion	
						Maximum Valu	es				
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-0010	7	Honolulu	600	27.6	27.0	24.9	24.2	22.8	104243		0
		Not in a city		01/06:16	01/06:16	01/06:16	01/06:16	01/25:10			
				21.6	21.4	20.7	20.5	20.3			
				01/06:17	02/09:18	01/25:09	01/25:09	01/25:09			
				Sulfur di	oxide (42401)						
State:	Hawaii							Primary:			
Duration:	5 MINUT	Ε						condary:			
Year:	2020							Unit: Par	ts per bi	llion	
						Maximum Valu	es				
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-0010	7	Honolulu	560 600	32.2	30.4	27.7	26.8	23.0	93923		0
		Not in a city		02/23:16	02/23:16	10/07:15	02/23:16	02/23:16			
				21.8	21.8	21.6	21.3	21.1			
				01/24:10	02/23:16	01/24:10	02/23:16	01/24:10			

MAXIMUM VALUES REPORT

Feb. 6, 2023

Sulfur dioxide (42401)

State: Hawaii Primary:
Duration: 5 MINUTE Secondary:

Year: 2021 Unit: Parts per billion

icai.									-		
						Maximum Valu	ies				
		County Name		1st Max	2nd Max	3rd Max	4th Max	5th Max	Num	Num	EDT
Site ID	POC	City Name	Methods	6th Max	7th Max	8th Max	9th Max	10th Max	Obs	Exc	ID
15-003-0010	7	Honolulu	560	57.4	57.1	56.5	55.8	54.2	76913		0
		Not in a city		06/23:11	06/23:11	06/23:11	06/23:11	06/23:11			
				36.9	33.8	33.4	25.3	24.1			
				06/23:11	06/28:18	06/23:11	06/28:18	02/05:09			

User ID: XJMYOSHIMOTO DESIGN VALUE REPORT

Report Request ID: 2075939 Report Code: AMP480 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 2004

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

DESIGN VALUE 81102

SELECTED OPTIONS

Option Type Option Value

WORKFILE DELIMITER

SINGLE EVENT PROCESSING EXCLUDE REGIONALLY CONCURRED EVENTS

QUARTERLY DATA IN WORKFILE NO
AGENCY ROLE PQAO

MODEL TODE

USER SITE METADATA STREET ADDRESS

MERGE PDF FILES YES
USE LINKED SITES YES

DATE CRITERIA

Start Date End Date

2017 2021 PM10 24-hour 2006

APPLICABLE STANDARDS

Standard Description

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

Report Date: Feb. 6, 2023

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Pollutant: PM10 Total 0-10um STP(81102) Design Value Year: 2017

Standard Units: Micrograms/cubic meter (25 C) (001) REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: PM10 24-hour 2006

Hawaii Statistic: Annual Estimated Days > Standard Level: 150 State Name: 2017 2016 2015 3 - Year Cert& Cert& Cert& | Estimated Validity #Comp #Comp Exceedances #Comp Exceedances Exceedances Estimated Count Quarter Eval Estimated Count Quarter _Eval | Estimated Count Quarter _Eval | Exceedances Site ID POC STREET ADDRESS Ind. 0 Y 15-003-2004 3 860 4TH ST, PEARL CITY Ω Ν 0

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Pollutant: PM10 Total 0-10um STP(81102) Design Value Year: 2018

Standard Units: Micrograms/cubic meter (25 C) (001) REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: PM10 24-hour 2006

Hawaii Statistic: Annual Estimated Days > Standard Level: 150 State Name: 2018 2017 2016 3 - Year Cert& Cert& Cert& | Estimated Validity #Comp #Comp Exceedances #Comp Exceedances Exceedances Estimated Count Quarter Eval Estimated Count Quarter _Eval | Estimated Count Quarter _Eval | Exceedances Site ID POC STREET ADDRESS Ind. 0 Y 15-003-2004 3 860 4TH ST, PEARL CITY Μ 0 Ν

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Pollutant: PM10 Total 0-10um STP(81102) Design Value Year: 2019

Standard Units: Micrograms/cubic meter (25 C) (001) REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: PM10 24-hour 2006

Hawaii Statistic: Annual Estimated Days > Standard Level: 150 State Name: 2019 2018 2017 3 - Year Cert& Cert& Cert& | Estimated Validity #Comp #Comp Exceedances #Comp Exceedances Exceedances Estimated Count Quarter Eval Estimated Count Quarter _Eval | Estimated Count Quarter _Eval | Exceedances Site ID POC STREET ADDRESS Ind. Y 15-003-2004 3 860 4TH ST, PEARL CITY 0 Ν Ω Μ 0

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Pollutant: PM10 Total 0-10um STP(81102) Design Value Year: 2020

Standard Units: Micrograms/cubic meter (25 C) (001) REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: PM10 24-hour 2006

Hawaii Statistic: Annual Estimated Days > Standard Level: 150 State Name: 2020 2019 2018 3 - Year Cert& Cert& Cert& | Estimated Validity #Comp #Comp Exceedances #Comp Exceedances Exceedances Estimated Count Quarter Eval Estimated Count Quarter _Eval | Estimated Count Quarter _Eval | Exceedances Site ID POC STREET ADDRESS Ind. 0 Y 15-003-2004 3 860 4TH ST, PEARL CITY Ν Ω Ν 0 Μ

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Pollutant: PM10 Total 0-10um STP(81102) Design Value Year: 2021

Standard Units: Micrograms/cubic meter (25 C) (001) REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: PM10 24-hour 2006

Hawaii Statistic: Annual Estimated Days > Standard Level: 150 State Name: 2021 2020 2019 3 - Year Cert& Cert& Cert& | Estimated Validity #Comp #Comp Exceedances #Comp Exceedances Exceedances Estimated Count Quarter Eval Estimated Count Quarter _Eval | Estimated Count Quarter _Eval | Exceedances Site ID POC STREET ADDRESS Ind. 0 Y 15-003-2004 3 860 4TH ST, PEARL CITY Ν Ω Ν 0 Ν

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

CERTIFICATION EVALUATION AND CONCURRENCE FLAG MEANINGS

FLAG	MEANING
M	The monitoring organization has revised data from this monitor since the
	most recent certification letter received from the state.
N	The certifying agency has submitted the certification letter and required
	summary reports, but the certifying agency and/or EPA has determined
	that issues regarding the quality of the ambient concentration data cannot
	be resolved due to data completeness, the lack of performed quality
	assurance checks or the results of uncertainty statistics shown in the
	AMP255 report or the certification and quality assurance report.
S	The certifying agency has submitted the certification letter and required
	summary reports. A value of "S" conveys no Regional assessment regarding
	data quality per se. This flag will remain until the Region provides an "N" or
	"Y" concurrence flag.
U	Uncertified. The certifying agency did not submit a required certification
	letter and summary reports for this monitor even though the due date has
	passed, or the state's certification letter specifically did not apply the
	certification to this monitor.
X	Certification is not required by 40 CFR 58.15 and no conditions apply to be
	the basis for assigning another flag value
Y	The certifying agency has submitted a certification letter, and EPA has no
	unresolved reservations about data quality (after reviewing the letter, the
	attached summary reports, the amount of quality assurance data
	submitted to AQS, the quality statistics, and the highest reported
	concentrations).

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

User ID: XJMYOSHIMOTO DESIGN VALUE REPORT

Report Request ID: 2075938 Report Code: AMP480 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 2004

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

DESIGN VALUE 88101

SELECTED OPTIONS

Option Type Option Value

WORKFILE DELIMITER

SINGLE EVENT PROCESSING EXCLUDE REGIONALLY CONCURRED EVENTS

QUARTERLY DATA IN WORKFILE NO

AGENCY ROLE PQAO
USER SITE METADATA STREET ADDRESS

MERGE PDF FILES YES

USE LINKED SITES YES

DATE CRITERIA

Start Date End Date

2017 2021 PM25 24-hour 2012 PM25 Annual 2012

APPLICABLE STANDARDS

Standard Description

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

Report Date: Feb. 6, 2023

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions (88101) Design Value Year: 2017

Standard Units: Micrograms/cubic meter (LC) (105)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean

Level: 12

Statistic: Annual 98th Percentile

Level: 35

State Name: Hawaii

2016 2017 2015 24-Hour Annual Site_ID / Cert& Cert& Cert& | Design Valid | Design Valid Wtd. Cred. Comp. 98th Wtd. Cred. Comp. 98th Wtd. Cred. Comp. 98th STREET ADDRESS <u>Eval</u> <u>Eval</u> Days Ortrs Perctil Mean Days Ortrs Perctil Mean Days Ortrs Perctil Mean Eval | Value Ind. | Value Ind. 15-003-2004 358 4 14.1 4.4 Ν 365 4 11.7 2.6 Ν 353 4 11.4 5.2 N 12 Y 4.1 Y

860 4TH ST, PEARL CITY

Notes: 1. Computed design values are a snapshot of the data at the time the report was run (may not be all data for year).

2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions(88101)

Design Value Year: 2018

Standard Units: Micrograms/cubic meter (LC) (105)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Report Date: Feb. 6, 2023

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12

State Name: Hawaii Statistic: Annual 98th Percentile Level: 35

	1		201	8		1		201	L 7		1		201	.6		24-н	our	Annu	ıal
Site_ID /	Cred.	Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Design	Valid	Design	Valid
STREET ADDRESS	Days	Qrtrs	<u>Perctil</u>	Mean	<u>Eval</u>	Days	Qrtrs	Perctil	Mean	_Eval	Days	Qrtrs	Perctil	<u>Mean</u>	Eval	Value	Ind.	<u>Value</u>	Ind.
15-003-2004	349	4	9.1	3.0	М	358	4	14.1	4.4	N	365	4	11.7	2.6	N	12	Y	3.3	Y

860 4TH ST, PEARL CITY

Notes: 1. Computed design values are a snapshot of the data at the time the report was run (may not be all data for year).

2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions(88101)

Design Value Year: 2019

Standard Units: Micrograms/cubic meter (LC) (105)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Report Date: Feb. 6, 2023

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

			201	.9				201	18				201	L 7		24-H	our	Annu	al
<pre>Site_ID /</pre>	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Design	Valid	Design	Valid
STREET ADDRESS	Days	Qrtrs	Perctil	Mean	<u>Eval</u>	Days	Qrtrs	Perctil	Mean	_Eval	Days	Qrtrs	Perctil	Mean	Eval	Value	Ind.	<u>Value</u>	Ind.
15-003-2004	359	4	6.3	3.3	N	349	4	9.1	3.0	М	358	4	14.1	4.4	N	10	Y	3.5	Y

860 4TH ST, PEARL CITY

Notes: 1. Computed design values are a snapshot of the data at the time the report was run (may not be all data for year).

2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

Report Date: Feb. 6, 2023

PRELIMINARY DESIGN VALUE REPORT

Design Value Year: 2020

Standard Units: Micrograms/cubic meter (LC) (105)

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Statistic: Annual Weighted Mean Level: 12

Pollutant: Site-LevelPM2.5 - Local Conditions(88101)

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

	- [2020	20	19	2018	24-Hour Annual
<pre>Site_ID /</pre>	Cred. Comp. 98th	Wtd. Cert&	Cred.Comp. 98th	Wtd. Cert&	Cred.Comp. 98th Wtd.	Cert& Design Valid Design Valid
STREET ADDRESS	Days Qrtrs Perct	<u>il Mean</u> Eval	Days Ortrs Perctil	<u>Mean</u> Eval	Days Ortrs Perctil Mean	
15-003-2004	345 4 6.	2 3.2 Y	359 4 6.3	3.3 N	349 4 9.1 3.	0 M 7 Y 3.2 Y

860 4TH ST, PEARL CITY

Notes: 1. Computed design values are a snapshot of the data at the time the report was run (may not be all data for year).

2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions(88101)

Design Value Year: 2021

Standard Units: Micrograms/cubic meter (LC) (105)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Report Date: Feb. 6, 2023

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

	1		202	1				202	20				201	L 9		24-H	our	Annu	ıal
<pre>Site_ID /</pre>	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Design	Valid	Design	Valid
STREET ADDRESS	Days	Qrtrs	Perctil	Mean	_Eval	Days	Qrtrs	Perctil	Mean	_Eval	Days	Qrtrs	Perctil	Mean	_Eval	Value	Ind.	<u>Value</u>	Ind.
15-003-2004	340	4	6.1	3.2	N	345	4	6.2	3.2	Y	359	4	6.3	3.3	N	6	Y	3.2	Y

860 4TH ST, PEARL CITY

Notes: 1. Computed design values are a snapshot of the data at the time the report was run (may not be all data for year).

2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

CERTIFICATION EVALUATION AND CONCURRENCE FLAG MEANINGS

FLAG	MEANING
M	The monitoring organization has revised data from this monitor since the
	most recent certification letter received from the state.
N	The certifying agency has submitted the certification letter and required
	summary reports, but the certifying agency and/or EPA has determined
	that issues regarding the quality of the ambient concentration data cannot
	be resolved due to data completeness, the lack of performed quality
	assurance checks or the results of uncertainty statistics shown in the
	AMP255 report or the certification and quality assurance report.
S	The certifying agency has submitted the certification letter and required
	summary reports. A value of "S" conveys no Regional assessment regarding
	data quality per se. This flag will remain until the Region provides an "N" or
	"Y" concurrence flag.
U	Uncertified. The certifying agency did not submit a required certification
	letter and summary reports for this monitor even though the due date has
	passed, or the state's certification letter specifically did not apply the
	certification to this monitor.
X	Certification is not required by 40 CFR 58.15 and no conditions apply to be
	the basis for assigning another flag value
Y	The certifying agency has submitted a certification letter, and EPA has no
	unresolved reservations about data quality (after reviewing the letter, the
	attached summary reports, the amount of quality assurance data
	submitted to AQS, the quality statistics, and the highest reported
	concentrations).

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

User ID: XJMYOSHIMOTO DESIGN VALUE REPORT

Report Request ID: 2075935 Report Code: AMP480 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal EPA

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 009 0006

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

DESIGN VALUE 88101

SELECTED OPTIONS

Option Type Option Value

WORKFILE DELIMITER

SINGLE EVENT PROCESSING EXCLUDE REGIONALLY CONCURRED EVENTS

QUARTERLY DATA IN WORKFILE NO

AGENCY ROLE PQAO

USER SITE METADATA STREET ADDRESS

MERGE PDF FILES YES
USE LINKED SITES YES

DATE CRITERIA

Start Date End Date

2017 2021 PM25 24-hour 2012 PM25 Annual 2012

APPLICABLE STANDARDS

Standard Description

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

Report Date: Feb. 6, 2023

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions(88101)

Design Value Year: 2017

Standard Units: Micrograms/cubic meter (LC) (105)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Report Date: Feb. 6, 2023

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

	1	017	201	.6	2015	24-Hour Annual
<pre>Site_ID /</pre>	Cred. Comp. 98th	Wtd. Cert&	Cred. Comp. 98th	Wtd. Cert&	Cred. Comp. 98th Wtd.	Cert& Design Valid Design Valid
STREET ADDRESS	Days Ortrs Perct	<u>il Mean</u> <u>Eval</u>	Days Ortrs Perctil	<u>Mean</u> Eval	Days Ortrs Perctil Mean	<u>Eval</u> <u>Value</u> <u>Ind.</u> <u>Value</u> <u>Ind.</u>
15-009-0006	349 4 11.	3 4.1 N	356 4 12.1	3.7 N	306 3 12.9* 4.8	* N 12 Y 4.2 Y

KAIHOI ST AND KAIOLOHIA ST

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

PRELIMINARY DESIGN VALUE REPORT

Standard Units: Micrograms/cubic meter (LC) (105)

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Pollutant: Site-LevelPM2.5 - Local Conditions(88101)

Statistic: Annual Weighted Mean Level: 12

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

			201	.8				201	L 7				201	.6		24-H	our	Annu	.al
<pre>Site_ID /</pre>	Cred	. Comp	. 98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Cred	Comp.	98th	Wtd.	Cert&	Design	Valid	Design	Valid
STREET ADDRESS	Days	Qrtrs	s Perctil	Mean	<u>Eval</u>	Days	Qrtrs	Perctil	Mean	_Eval	Days	Qrtrs	<u>Perctil</u>	Mean	_Eval	Value	Ind.	<u>Value</u>	Ind.
15-009-0006	339	4	10.6	4.5	M	349	4	11.3	4.1	N	356	4	12.1	3.7	N	11	Y	4.1	Y

Design Value Year: 2018

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

KAIHOI ST AND KAIOLOHIA ST

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions (88101) Design Value Year: 2019

Standard Units: Micrograms/cubic meter (LC) (105)

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

			201	.9				201	L8				201	L 7		24-H	our	Annu	ıal
Site_ID /	Cred	. Comp	. 98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Design	Valid	Design	Valid
STREET ADDRESS	Days	Qrtrs	s Perctil	Mean	<u>Eval</u>	Days	Qrtrs	Perctil	Mean	_Eval	Days	Qrtrs	Perctil	Mean	Eval	Value	Ind.	<u>Value</u>	Ind.
15-009-0006	357	4	16.9	4.1	N	339	4	10.6	4.5	М	349	4	11.3	4.1	N	13	Y	4.2	Y

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

KAIHOI ST AND KAIOLOHIA ST

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions(88101) Design Value Year: 2020

Standard Units: Micrograms/cubic meter (LC) (105)

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

	1		202	0				201	.9		1		201	.8		24-H	our	Annu	ıal
Site_ID /	Cred	. Comp.	98th	Wtd.	Cert&		_		Wtd.	Cert&	I crea	. Comp.	98th	Wtd.	Cert&	Design	Valid	Design	Valid
STREET ADDRESS	Days	Qrtrs	Perctil	Mean	<u>Eval</u>	Days	Qrtrs	<u>Perctil</u>	Mean	<u>Eval</u>	Days	<u>Qrtrs</u>	Perctil	Mean	<u>Eval</u>	<u>Value</u>	Ind.	<u>Value</u>	Ind.
15-009-0006	332	4	7.2	2.9	Y	357	4	16.9	4.1	N	339	4	10.6	4.5	M	12	Y	3.9	Y

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

KAIHOI ST AND KAIOLOHIA ST

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions(88101)

Design Value Year: 2021

Standard Units: Micrograms/cubic meter (LC) (105)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Report Date: Feb. 6, 2023

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

	1		202	1				202	20		1		201	.9		24-н	our	Annu	al
Site_ID /	Cred	. Comp.	98th	Wtd.	Cert&		-		Wtd.	Cert&	1 crea	. Comp.	98th	Wtd.	Cert&	Design	Valid	Design	Valid
STREET ADDRESS	Days	Qrtrs	Perctil	Mean	<u>Eval</u>	Days	Qrtrs	Perctil	Mean	<u>Eval</u>	Days	Qrtrs	Perctil	Mean	<u>Eval</u>	<u>Value</u>	Ind.	<u>Value</u>	Ind.
15-009-0006	355	4	5.7	2.5	N	332	4	7.2	2.9	Y	357	4	16.9	4.1	N	10	Y	3.2	Y

KAIHOI ST AND KAIOLOHIA ST

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

CERTIFICATION EVALUATION AND CONCURRENCE FLAG MEANINGS

FLAG	MEANING
M	The monitoring organization has revised data from this monitor since the
	most recent certification letter received from the state.
N	The certifying agency has submitted the certification letter and required
	summary reports, but the certifying agency and/or EPA has determined
	that issues regarding the quality of the ambient concentration data cannot
	be resolved due to data completeness, the lack of performed quality
	assurance checks or the results of uncertainty statistics shown in the
	AMP255 report or the certification and quality assurance report.
S	The certifying agency has submitted the certification letter and required
	summary reports. A value of "S" conveys no Regional assessment regarding
	data quality per se. This flag will remain until the Region provides an "N" or
	"Y" concurrence flag.
U	Uncertified. The certifying agency did not submit a required certification
	letter and summary reports for this monitor even though the due date has
	passed, or the state's certification letter specifically did not apply the
	certification to this monitor.
X	Certification is not required by 40 CFR 58.15 and no conditions apply to be
	the basis for assigning another flag value
Y	The certifying agency has submitted a certification letter, and EPA has no
	unresolved reservations about data quality (after reviewing the letter, the
	attached summary reports, the amount of quality assurance data
	submitted to AQS, the quality statistics, and the highest reported
	concentrations).

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

User ID: XGSWU DESIGN VALUE REPORT

Report Request ID: 2076102 Report Code: AMP480 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 007 0007

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

DESIGN VALUE 88101

SELECTED OPTIONS

Option Type Option Value

WORKFILE DELIMITER

SINGLE EVENT PROCESSING EXCLUDE REGIONALLY CONCURRED EVENTS

QUARTERLY DATA IN WORKFILE NO

AGENCY ROLE PQAO

USER SITE METADATA STREET ADDRESS
MERGE PDF FILES YES

USE LINKED SITES YES

DATE CRITERIA

Start Date End Date

2017 2021 PM25 24-hour 2012 PM25 Annual 2012

APPLICABLE STANDARDS

Standard Description

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

Report Date: Feb. 6, 2023

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions(88101)

Design Value Year: 2017

Standard Units: Micrograms/cubic meter (LC) (105)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Report Date: Feb. 6, 2023

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

	Site ID /							201	.6				201	.5		24-H	our	Annu	al
	Cred	. Comp	. 98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Design	Valid	Design	Valid
STREET ADDRESS	Days	Qrtrs	s Perctil	Mean	<u>Eval</u>	Days	Qrtrs	Perctil	Mean	_Eval	Days	Qrtrs	Perctil	Mean	_Eval	Value	Ind.	<u>Value</u>	Ind.
15-007-0007	350	4	9.0	2.6	N	350	4	9.0	3.5	N	338	4	10.1	3.2	N	9	Y	3.1	Y

2342 HULEMALU ROAD, KAUAI

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions(88101)

Design Value Year: 2018

Standard Units: Micrograms/cubic meter (LC) (105)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Report Date: Feb. 6, 2023

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

	1		201	.8				201	.7		1		201	.6		24-H	our	Annu	.al
<pre>Site_ID /</pre>	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Design	Valid	Design	Valid
STREET ADDRESS	Days	Qrtrs	Perctil	Mean	<u>Eval</u>	Days	Ortrs	Perctil	Mean	_Eval	Days	Qrtrs	Perctil	Mean	Eval	Value	Ind.	<u>Value</u>	Ind.
15-007-0007	327	4	8.4	2.5	М	350	4	9.0	2.6	N	350	4	9.0	3.5	N	9	Y	2.9	Y

2342 HULEMALU ROAD, KAUAI

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions(88101)

Design Value Year: 2019

Standard Units: Micrograms/cubic meter (LC) (105)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Report Date: Feb. 6, 2023

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

Site_ID / Cred. Comp. 98t				9				201	.8		1		201	.7		24-H	our	Annu	.al
<pre>Site_ID /</pre>	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Design	Valid	Design	Valid
STREET ADDRESS	<u>Days</u>	Qrtrs	<u>Perctil</u>	<u>Mean</u>	<u>Eval</u>	Days	Ortrs	Perctil	Mean	_Eval	Days	Qrtrs	Perctil	Mean	Eval	<u>Value</u>	Ind.	<u>Value</u>	Ind.
15-007-0007	340	4	7.5	2.9	N	327	4	8.4	2.5	М	350	4	9.0	2.6	N	8	Y	2.7	Y

2342 HULEMALU ROAD, KAUAI

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions(88101)

Design Value Year: 2020

Standard Units: Micrograms/cubic meter (LC) (105)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Report Date: Feb. 6, 2023

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12

Statistic: Annual 98th Percentile Level: 35 State Name: Hawaii

	Site ID / 10 10 10 10 10 10 10 10 10 10 10 10 10							201	L9				201	.8		24-H	our	Annu	al
	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Cred	. Comp.	98th	Wtd.	Cert&	Design	Valid	Design	Valid
STREET ADDRESS	Days	Qrtrs	Perctil	Mean	Eval	Days	Qrtrs	Perctil	Mean	_Eval	Days	Qrtrs	Perctil	Mean	_Eval	Value	Ind.	<u>Value</u>	Ind.
15-007-0007	322	3	8.3	3.2*	∀ Υ	340	4	7.5	2.9	N	327	4	8.4	2.5	М	8	Y	2.9	Y

2342 HULEMALU ROAD, KAUAI

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Site-LevelPM2.5 - Local Conditions (88101) Design Value Year: 2021

Standard Units: Micrograms/cubic meter (LC) (105)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: PM25 24-hour 2012 / PM25 Annual 2012

Statistic: Annual Weighted Mean Level: 12
Statistic: Annual 98th Percentile Level: 35
State Name: Hawaii

2020 2021 2019 24-Hour Annual Site_ID / Cert& Cert& Cert& | Design Valid | Design Valid Wtd. Cred. Comp. 98th Wtd. Cred. Comp. 98th Wtd. Cred. Comp. 98th STREET ADDRESS <u>Eval</u> <u>Eval</u> Days Ortrs Perctil Mean Days Ortrs Perctil Mean Days Ortrs Perctil Mean Eval | Value Ind. | Value Ind. 15-007-0007 342 4 7.2 3.2 Ν 322 3 8.3 3.2 * Y 340 4 7.5 2.9 Ν 8 Y 3.1 Y

2342 HULEMALU ROAD, KAUAI

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

CERTIFICATION EVALUATION AND CONCURRENCE FLAG MEANINGS

FLAG	MEANING
M	The monitoring organization has revised data from this monitor since the
	most recent certification letter received from the state.
N	The certifying agency has submitted the certification letter and required
	summary reports, but the certifying agency and/or EPA has determined
	that issues regarding the quality of the ambient concentration data cannot
	be resolved due to data completeness, the lack of performed quality
	assurance checks or the results of uncertainty statistics shown in the
	AMP255 report or the certification and quality assurance report.
S	The certifying agency has submitted the certification letter and required
	summary reports. A value of "S" conveys no Regional assessment regarding
	data quality per se. This flag will remain until the Region provides an "N" or
	"Y" concurrence flag.
U	Uncertified. The certifying agency did not submit a required certification
	letter and summary reports for this monitor even though the due date has
	passed, or the state's certification letter specifically did not apply the
	certification to this monitor.
X	Certification is not required by 40 CFR 58.15 and no conditions apply to be
	the basis for assigning another flag value
Y	The certifying agency has submitted a certification letter, and EPA has no
	unresolved reservations about data quality (after reviewing the letter, the
	attached summary reports, the amount of quality assurance data
	submitted to AQS, the quality statistics, and the highest reported
	concentrations).

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

User ID: XGSWU DESIGN VALUE REPORT

Report Request ID: 2076104 Report Code: AMP480 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal EPA

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 007 0007

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

DESIGN VALUE 42602

SELECTED OPTIONS

Option Type Option Value

WORKFILE DELIMITER

SINGLE EVENT PROCESSING EXCLUDE REGIONALLY CONCURRED EVENTS

QUARTERLY DATA IN WORKFILE NO
AGENCY ROLE POAC

AGENCY ROLE PQAO
USER SITE METADATA STREET ADDRESS

MERGE PDF FILES YES

USE LINKED SITES YES

DATE CRITERIA

Start Date End Date Standard Description

2017 2021 NO2 1-hour 2010

APPLICABLE STANDARDS

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

Report Date: Feb. 6, 2023

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

PRELIMINARY DESIGN VALUE REPORT

Design Value Year: 2017

Standard Units: Parts per billion(008)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: NO2 1-hour 2010

Pollutant: Nitrogen dioxide (NO2)

Statistic: Annual 98th Percentile Level: 100 State Name: Hawaii

		i	2017		I	2016	ı		2015		3−Y€	ear	1
		Comp.	98th	Cert&	Comp.	<u>98th</u>	Cert&	Comp.	<u>98th</u>	Cert&	Design	DV Validity	i
Site ID	STREET ADDRESS	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	Qtrs	<u>Percentile</u>	<u>Eval</u>	<u>Value</u>	<u>Indicator</u>	i
15-007-0007	2342 HULEMALU ROAD, KAUA	. 1	31.2	N	. 1	34.2	N	3	31.6	Y	32	N	

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Nitrogen dioxide (NO2)

Design Value Year: 2018

Standard Units: Parts per billion(008)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: NO2 1-hour 2010

Statistic: Annual 98th Percentile Level: 100 State Name: Hawaii

		ı	2018		I	2017	1		2016		3−Y∈	ar	1
		Comp.	<u>98th</u>	Cert&	Comp.	<u>98th</u>	Cert&	Comp.	<u>98th</u>	Cert&	Design	DV Validity	i
Site ID	STREET ADDRESS	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	<u>Value</u>	Indicator	i
15-007-0007	2342 HULEMALU ROAD, KAUA	• 4	39.3	M	1	31.2	N	1	34.2	N	' 35	N	'

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Design Value Year: 2019

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Pollutant: Nitrogen dioxide (NO2)

Standard Units: Parts per billion(008)

NAAQS Standard: NO2 1-hour 2010

Statistic: Annual 98th Percentile Level: 100 State Name: Hawaii

		I	2019		I	2018	ı	2017		3-Year	,
		Comp.	<u>98th</u>	Cert&	Comp.	<u>98th</u>	Cert&	Comp. 98th	Cert&	Design DV Validity	¦
Site ID	STREET ADDRESS	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	<u>Qtrs</u> <u>Percen</u>	tile <u>Eval</u>	<u> Value</u> <u>Indicator</u>	i
15-007-0007	2342 HULEMALU ROAD, KAU?	4	38.0	Y	4	39.3	M	1 31.2	N	. 36 Y	

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

DDELTMINADY DECICN VALUE DEDOD

PRELIMINARY DESIGN VALUE REPORT

Design Value Year: 2020

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Pollutant: Nitrogen dioxide (NO2)

Standard Units: Parts per billion(008)

NAAQS Standard: NO2 1-hour 2010

Statistic: Annual 98th Percentile Level: 100 State Name: Hawaii

		I	2020		1	2019	I		2018		3-Ye	ar	1
		Comp.	<u>98th</u>	Cert&	Comp.	<u>98th</u>	Cert&	Comp.	98th	Cert&	Design	DV Validity	i i
Site ID	STREET ADDRESS	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	Qtrs	<u>Percentile</u>	<u>Eval</u>	<u>Value</u>	Indicator	!
15-007-0007	2342 HULEMALU ROAD, KAU?	4	33.8	Y	4	38.0	Y	4	39.3	M	• 37	Y	•

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Design Value Year: 2021

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

Pollutant: Nitrogen dioxide (NO2)

Standard Units: Parts per billion(008)

NAAQS Standard: NO2 1-hour 2010

Statistic: Annual 98th Percentile Level: 100 State Name: Hawaii

		I	2021		Ī	2020	[2019		3−Ye	ar	1
		Comp.	<u>98th</u>	Cert&	Comp.	<u>98th</u>	Cert&	Comp.	<u>98th</u>	Cert&	<u>Design</u>	DV Validity	
Site ID	STREET ADDRESS	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	<u>Qtrs</u>	<u>Percentile</u>	<u>Eval</u>	<u>Value</u>	<u>Indicator</u>	i
15-007-0007	2342 HULEMALU ROAD, KAU?	4	13.8	N	4	33.8	Y	4	38.0	Y	29	Y	•

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

CERTIFICATION EVALUATION AND CONCURRENCE FLAG MEANINGS

FLAG	MEANING
M	The monitoring organization has revised data from this monitor since the
	most recent certification letter received from the state.
N	The certifying agency has submitted the certification letter and required
	summary reports, but the certifying agency and/or EPA has determined
	that issues regarding the quality of the ambient concentration data cannot
	be resolved due to data completeness, the lack of performed quality
	assurance checks or the results of uncertainty statistics shown in the
	AMP255 report or the certification and quality assurance report.
S	The certifying agency has submitted the certification letter and required
	summary reports. A value of "S" conveys no Regional assessment regarding
	data quality per se. This flag will remain until the Region provides an "N" or
	"Y" concurrence flag.
U	Uncertified. The certifying agency did not submit a required certification
	letter and summary reports for this monitor even though the due date has
	passed, or the state's certification letter specifically did not apply the
	certification to this monitor.
X	Certification is not required by 40 CFR 58.15 and no conditions apply to be
	the basis for assigning another flag value
Y	The certifying agency has submitted a certification letter, and EPA has no
	unresolved reservations about data quality (after reviewing the letter, the
	attached summary reports, the amount of quality assurance data
	submitted to AQS, the quality statistics, and the highest reported
	concentrations).

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

User ID: XJMYOSHIMOTO DESIGN VALUE REPORT

Report Request ID: 2075933 Report Code: AMP480 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

APPLICABLE STANDARDS

Standard Description

15 003 0010

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

DESIGN VALUE 42401

SELECTED OPTIONS

Option Type Option Value

WORKFILE DELIMITER

SINGLE EVENT PROCESSING EXCLUDE REGIONALLY CONCURRED EVENTS

QUARTERLY DATA IN WORKFILE NO
AGENCY ROLE PQAO

USER SITE METADATA STREET ADDRESS

MERGE PDF FILES YES

USE LINKED SITES YES

DATE CRITERIA

Start Date End Date

2017 2021 SO2 1-hour 2010

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

Report Date: Feb. 6, 2023

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Sulfur dioxide (42401)

Design Value Year: 2017

Standard Units: Parts per billion(008)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: SO2 1-hour 2010

Statistic: Annual 99th Percentile Level: 75 State Name: Hawaii

		I	2017		ı	2016		I	2015		_l 3–	Year	ı
		Comp.	99th	Cert&	Comp.	99th	Cert&	Comp.	99th	Cert&	Design	Valid	i
Site ID	STREET ADDRESS	Ortrs	<u>Percentile</u>	Eval	<u>Qrtrs</u>	<u>Percentile</u>	Eval	Qrtrs	<u>Percentile</u>	<u>Eval</u>	<u>Value</u>	Ind.	i
15-003-0010	2052 LAUWILIWILI ST	4	8.3	Y	4	8.4	Y	4	15.0	Y	11	Y	•

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Sulfur dioxide (42401)

Design Value Year: 2018

Standard Units: Parts per billion(008)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: SO2 1-hour 2010

Statistic: Annual 99th Percentile Level: 75 State Name: Hawaii

		ı	2018		I	2017		I	2016		_l 3–	Year	ı
		Comp.	99th	Cert&	Comp.	99th	Cert&	Comp.	99th	Cert&	Design	Valid	i
Site ID	STREET ADDRESS	Qrtrs	<u>Percentile</u>	<u>Eval</u>	<u>Qrtrs</u>	<u>Percentile</u>	Eval	Qrtrs	<u>Percentile</u>	Eval	<u>Value</u>	Ind.	i
15-003-0010	2052 LAUWILIWILI ST	4	6.2	М	4	8.3	Y	4	8.4	Y	8	Y	•

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Sulfur dioxide (42401) Design Value Year: 2019

Standard Units: Parts per billion(008)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: SO2 1-hour 2010

Statistic: Annual 99th Percentile Level: 75 State Name: Hawaii

		1	2019		1	2018		I	2017		_l 3–	Year	ı
		Comp.	99th	Cert&	Comp. 9	9th	Cert&	Comp.	99th	Cert&	 Design	Valid	i
Site ID	STREET ADDRESS	<u>Qrtrs</u>	<u>Percentile</u>	Eval	Ortrs P	Percentile	Eval	Qrtrs	<u>Percentile</u>	<u>Eval</u>	<u>Value</u>	Ind.	i
15-003-0010	2052 LAUWILIWILI ST	4	10.9	Y	4	6.2	М	4	8.3	Y	. 8	Y	•

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

AIR QUALITY SYSTEM

PRELIMINARY DESIGN VALUE REPORT

Pollutant: Sulfur dioxide (42401)

Design Value Year: 2020

Standard Units: Parts per billion(008)

REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: SO2 1-hour 2010

Statistic: Annual 99th Percentile Level: 75 State Name: Hawaii

		1	2020		I	2019			2018		3-	Year	1
		Comp.	99th	Cert&	Comp.	99th	Cert&	Comp.	99th	Cert&	 Design	Valid	i
Site ID	STREET ADDRESS	<u>Qrtrs</u>	<u>Percentile</u>	Eval	Qrtrs	<u>Percentile</u>	Eval	Qrtrs	<u>Percentile</u>	Eval	<u>Value</u>	Ind.	i
15-003-0010	2052 LAUWILIWILI ST	4	5.8	Y	4	10.9	Y	4	6.2	М	. 8	Y	

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

Report Date: Feb. 6, 2023

PRELIMINARY DESIGN VALUE REPORT

Design Value Year: 2021 Pollutant: Sulfur dioxide (42401)

Standard Units: Parts per billion(008) REPORT EXCLUDES MEASUREMENTS WITH REGIONALLY CONCURRED EVENT FLAGS.

NAAQS Standard: SO2 1-hour 2010

Statistic: Annual 99th Percentile Level: 75 State Name: Hawaii

		1	2021		I	2020		I	2019		J 3-	Year	1
		Comp.	99th	Cert&	Comp.	99th	Cert&	Comp.	99th	Cert&	Design	Valid	i
Site ID	STREET ADDRESS	Ortrs	<u>Percentile</u>	Eval	<u>Qrtrs</u>	<u>Percentile</u>	Eval	Qrtrs	<u>Percentile</u>	<u>Eval</u>	<u>Value</u>	Ind.	i
15-003-0010	2052 LAUWILIWILI ST	4	5.8	N	4	5.8	Y	4	10.9	Y	8	Y	•

^{2.} Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.

^{3.} Annual Values not meeting completeness criteria are marked with an asterisk ('*').

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM PRELIMINARY DESIGN VALUE REPORT

CERTIFICATION EVALUATION AND CONCURRENCE FLAG MEANINGS

FLAG	MEANING
M	The monitoring organization has revised data from this monitor since the
	most recent certification letter received from the state.
N	The certifying agency has submitted the certification letter and required
	summary reports, but the certifying agency and/or EPA has determined
	that issues regarding the quality of the ambient concentration data cannot
	be resolved due to data completeness, the lack of performed quality
	assurance checks or the results of uncertainty statistics shown in the
	AMP255 report or the certification and quality assurance report.
S	The certifying agency has submitted the certification letter and required
	summary reports. A value of "S" conveys no Regional assessment regarding
	data quality per se. This flag will remain until the Region provides an "N" or
	"Y" concurrence flag.
U	Uncertified. The certifying agency did not submit a required certification
	letter and summary reports for this monitor even though the due date has
	passed, or the state's certification letter specifically did not apply the
	certification to this monitor.
X	Certification is not required by 40 CFR 58.15 and no conditions apply to be
	the basis for assigning another flag value
Y	The certifying agency has submitted a certification letter, and EPA has no
	unresolved reservations about data quality (after reviewing the letter, the
	attached summary reports, the amount of quality assurance data
	submitted to AQS, the quality statistics, and the highest reported
	concentrations).

- 2. Some PM2.5 24-hour DVs for incomplete data that are marked invalid here may be marked valid in the Official report due to additional analysis.
- 3. Annual Values not meeting completeness criteria are marked with an asterisk ('*').

User ID: XGSWU DATA COMPLETENESS REPORT

Report Request ID: 2076018 Report Code: AMP430 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 2004

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS	SELECTED OPTIONS					
Option Type	Option Value	Order	Column			
AGENCY ROLE	REPORTING	1	EPA_REGION			
OZONE EVALUATION	SEASONAL-HOURLY	2	STATE_CODE			
MERGE PDF FILES	YES	3	MONITOR_TYPE			
		4	COUNTY_CODE			
		5	SITE_ID			
		6	PARAMETER_CODE			
		7	POC			

DATE CRITERIA

Start Date End Date

2017 01 2017 12

APPLICABLE STANDARDS

Standard Description

CO 1-hour 1971

Lead 3-Month 2009

Lead 3-Month PM10 Surrogate 2009

NO2 Annual 1971

Ozone 1-hour 1979

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS NOT REPORTING

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2017 THRU DEC. 31, 2017

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii MONITOR TYPE: SLAMS

SITE ID CITY	PARAMETER	POC	DURATION METHOD						OBSERVA' NUMBI		RCENT					
ADDRESS				JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR
15-003-2004	81102 PM10 Total 0-10um STP	3	1	736	669	729	704	734	596	676	735	712	658	715	742	8406
Pearl City			122	99%	100%	98%	98%	99%	83%	91%	99%	99%	888	99%	100%	96%
860 4TH ST,	PEARL CITY															
15-003-2004	88101 PM2.5 - Local Conditions	4	1	739	666	742	719	741	717	740	731	691	742	620	742	8590
Pearl City			170	99%	99%	100%	100%	100%	100%	99%	98%	96%	100%	86%	100%	98%
860 4TH ST,	PEARL CITY															

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

REPORT SUMMARY

DATE RANGE: JAN. 01, 2017 THRU DEC. 31, 2017

REGION: (09) SAN FRANCISCO

STATE: Hawaii

REP ORG: Hawaii State Department Of Health

MONITOR TYPE: SLAMS

PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
81102 PM10 Total 0-10um STP	1	0	1	96.0%
88101 PM2.5 - Local Conditions	1	0	1	98.0%
MT SUMMARY: SLAMS	2	0	2	97.0%
RO SUMMARY: Hawaii State Department Of Health	2	0	2	97.0%
STATE SUMMARY: Hawaii	2	0	2	97.0%
REGION SUMMARY: (09) SAN FRANCISCO	2	0	2	97.0%
REPORT SUMMARY:	2	0	2	97.0%

User ID: XGSWU DATA COMPLETENESS REPORT

Report Request ID: 2076032 Report Code: AMP430 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 2004

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS			SORT ORDER
Option Type	Option Value	Order	Column
AGENCY ROLE	REPORTING	1	EPA_REGION
OZONE EVALUATION	SEASONAL-HOURLY	2	STATE_CODE
MERGE PDF FILES	YES	3	MONITOR_TYPE
		4	COUNTY_CODE
		5	SITE_ID
		6	PARAMETER_CODE
		7	POC

DATE CRITERIA

Start Date End Date

2018 01 2018 12

APPLICABLE STANDARDS

Standard Description

CO 1-hour 1971

Lead 3-Month 2009

Lead 3-Month PM10 Surrogate 2009

NO2 Annual 1971

Ozone 1-hour 1979

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS NOT REPORTING

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2018 THRU DEC. 31, 2018

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii MONITOR TYPE: SLAMS

SITE ID CITY	PARAMETER	POC	DURATION METHOD					C	BSERVA: NUMBI		 RCENT					
ADDRESS				JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR
15-003-2004	81102 PM10 Total 0-10um STP	3	1	730	660	738	711	733	713	737	622	711	697	715	734	8501
Pearl City			122	98%	98%	99%	99%	99%	99%	99%	84%	99%	94%	99%	99%	97%
860 4TH ST, I	PEARL CITY															
15-003-2004	88101 PM2.5 - Local Conditions	4	1	729	666	739	717	731	714	724	621	699	707	658	676	8381
Pearl City			170	98%	99%	99%	100%	98%	99%	97%	83%	97%	95%	91%	91%	96%
860 4TH ST, E	PEARL CITY															

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

REPORT SUMMARY

DATE RANGE: JAN. 01, 2018 THRU DEC. 31, 2018

REGION: (09) SAN FRANCISCO

STATE: Hawaii

REP ORG: Hawaii State Department Of Health

MONITOR TYPE: SLAMS

PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
81102 PM10 Total 0-10um STP	1	0	1	97.0%
88101 PM2.5 - Local Conditions	1	0	1	96.0%
MT SUMMARY: SLAMS	2	0	2	96.5%
RO SUMMARY: Hawaii State Department Of Health	2	0	2	96.5%
STATE SUMMARY: Hawaii	2	0	2	96.5%
REGION SUMMARY: (09) SAN FRANCISCO	2	0	2	96.5%
REPORT SUMMARY:	2	0	2	96.5%

User ID: XGSWU DATA COMPLETENESS REPORT

Report Request ID: 2076044 Report Code: AMP430 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal EPA

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 2004

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS			SORT ORDER
Option Type	Option Value	Order	Column
AGENCY ROLE	REPORTING	1	EPA_REGION
OZONE EVALUATION	SEASONAL-HOURLY	2	STATE_CODE
MERGE PDF FILES	YES	3	MONITOR_TYPE
		4	COUNTY_CODE
		5	SITE_ID
		6	PARAMETER_CODE
		7	POC

DATE CRITERIA End Date Start Date 2019 12 2019 01

APPLICABLE STANDARDS

Standard Description

CO 1-hour 1971

Lead 3-Month 2009

Lead 3-Month PM10 Surrogate 2009

NO2 Annual 1971

Ozone 1-hour 1979

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS NOT REPORTING

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2019 THRU DEC. 31, 2019

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii MONITOR TYPE: SLAMS

SITE ID CITY	PARAMETER	POC	DURATION METHOD					C	BSERVA: NUMBI		 RCENT					
ADDRESS				JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR
15-003-2004	81102 PM10 Total 0-10um STP	3	1	715	656	737	717	738	709	735	728	708	735	711	731	8620
Pearl City			122	96%	98%	99%	100%	99%	98%	99%	98%	98%	99%	99%	98%	98%
860 4TH ST,	PEARL CITY															
15-003-2004	88101 PM2.5 - Local Conditions	4	1	741	653	741	718	730	715	740	738	646	742	716	739	8619
Pearl City			000	100%	97%	100%	100%	98%	99%	99%	99%	90%	100%	99%	99%	98%
860 4TH ST,	PEARL CITY															

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

REPORT SUMMARY

DATE RANGE: JAN. 01, 2019 THRU DEC. 31, 2019

REGION: (09) SAN FRANCISCO

STATE: Hawaii

REP ORG: Hawaii State Department Of Health

MONITOR TYPE: SLAMS

PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
81102 PM10 Total 0-10um STP	1	0	1	98.0%
88101 PM2.5 - Local Conditions	1	0	1	98.0%
MT SUMMARY: SLAMS	2	0	2	98.0%
RO SUMMARY: Hawaii State Department Of Health	2	0	2	98.0%
STATE SUMMARY: Hawaii	2	0	2	98.0%
REGION SUMMARY: (09) SAN FRANCISCO	2	0	2	98.0%
REPORT SUMMARY:	2	0	2	98.0%

User ID: XGSWU DATA COMPLETENESS REPORT

Report Request ID: 2076047 Report Code: AMP430 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 2004

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS			SORT ORDER
Option Type	Option Value	Order	Column
AGENCY ROLE	REPORTING	1	EPA_REGION
OZONE EVALUATION	SEASONAL-HOURLY	2	STATE_CODE
MERGE PDF FILES	YES	3	MONITOR_TYPE
		4	COUNTY_CODE
		5	SITE_ID
		6	PARAMETER_CODE
		7	POC

DATE CRITERIA

Start Date End Date

2020 01 2020 12

APPLICABLE STANDARDS

Standard Description

CO 1-hour 1971

Lead 3-Month 2009

Lead 3-Month PM10 Surrogate 2009

NO2 Annual 1971

Ozone 1-hour 1979

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS NOT REPORTING

DATE RANGE: JAN. 01, 2020 THRU DEC. 31, 2020

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii MONITOR TYPE: SLAMS

SITE ID	PARAME		POC	CITY	ADDRESS
15-003-2004	88101	PM2.5 - Local Conditions	5	Pearl City	860 4TH ST, PEARL CITY

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2020 THRU DEC. 31, 2020

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii MONITOR TYPE: SLAMS

SITE ID CITY	PARAMETER	POC	DURATION METHOD					C	BSERVA' NUMBI		 RCENT					
ADDRESS				JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR
15-003-2004	81102 PM10 Total 0-10um STP	3	1	739	686	730	692	632	679	728	733	703	704	711	733	8470
Pearl City			122	99%	99%	98%	96%	85%	94%	98%	99%	98%	95%	99%	99%	96%
860 4TH ST,	PEARL CITY															
15-003-2004	88101 PM2.5 - Local Conditions	4	1	712	351	737	711	734	714	735	739	713	741	658	724	8269
Pearl City			209	96%	50%	99%	99%	99%	99%	99%	99%	99%	100%	91%	97%	94%
860 4TH ST,	PEARL CITY															
15-003-2004	88101 PM2.5 - Local Conditions	6	7				0	4	4	4	2	5	4	5	2	30
Pearl City			142				0%	80%	80%	80%	33%	100%	80%	100%	40%	65%
860 4TH ST,	PEARL CITY															

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

REPORT SUMMARY

DATE RANGE: JAN. 01, 2020 THRU DEC. 31, 2020

REGION: (09) SAN FRANCISCO

STATE: Hawaii

REP ORG: Hawaii State Department Of Health

PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
81102 PM10 Total 0-10um STP	1	0	1	96.0%
88101 PM2.5 - Local Conditions	3	1	1	53.0%
MT SUMMARY: SLAMS	4	1	2	63.8%
RO SUMMARY: Hawaii State Department Of Health	4	1	2	63.8%
STATE SUMMARY: Hawaii	4	1	2	63.8%
REGION SUMMARY: (09) SAN FRANCISCO	4	1	2	63.8%
REPORT SUMMARY:	4	1	2	63.8%

User ID: XGSWU DATA COMPLETENESS REPORT

Report Request ID: 2076048 Report Code: AMP430 Feb. 6, 2023

GEOGRAPHIC SELECTIONS

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 2004

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS			SORT ORDER
Option Type	Option Value	Order	Column
AGENCY ROLE	REPORTING	1	EPA_REGION
OZONE EVALUATION	SEASONAL-HOURLY	2	STATE_CODE
MERGE PDF FILES	YES	3	MONITOR_TYPE
		4	COUNTY_CODE
		5	SITE_ID
		6	PARAMETER_CODE
		7	POC

DATE CRITERIA

Start Date End Date

2021 01 2021 12

APPLICABLE STANDARDS

Standard Description

CO 1-hour 1971

Lead 3-Month 2009

Lead 3-Month PM10 Surrogate 2009

NO2 Annual 1971

Ozone 1-hour 1979

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS NOT REPORTING

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2021 THRU DEC. 31, 2021

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii MONITOR TYPE: SLAMS

SITE ID CITY	PARAMETER	POC	DURATION METHOD					C	BSERVA NUMB		ERCENT							
ADDRESS				JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR		
15-003-2004	81102 PM10 Total 0-10um STP	3	1	735	662	589	713	736	701	737	726	700	725	710	501	8235		
Pearl City			122	99%	99%	79%	99%	99%	97%	99%	98%	97%	97%	99%	67%	94%		
860 4TH ST,	PEARL CITY																	
15-003-2004	88101 PM2.5 - Local Conditions	4	1	742	601	541	716	741	712	738	741	718	741	393	738	8122		
Pearl City			209	100%	89%	73%	99%	100%	99%	99%	100%	100%	100%	55%	99%	93%		
860 4TH ST,	PEARL CITY																	
15-003-2004	88101 PM2.5 - Local Conditions	6	7	3	4	4	3	5	4	5	5	5	6	5	5	54		
Pearl City			142	60%	80%	80%	60%	100%	80%	100%	100%	100%	100%	100%	100%	89%		
860 4TH ST,	PEARL CITY																	

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

REPORT SUMMARY

DATE RANGE: JAN. 01, 2021 THRU DEC. 31, 2021

REGION: (09) SAN FRANCISCO

STATE: Hawaii

REP ORG: Hawaii State Department Of Health

PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
81102 PM10 Total 0-10um STP	1	0	1	94.0%
88101 PM2.5 - Local Conditions	2	0	2	91.0%
MT SUMMARY: SLAMS	3	0	3	92.0%
RO SUMMARY: Hawaii State Department Of Health	3	0	3	92.0%
STATE SUMMARY: Hawaii	3	0	3	92.0%
REGION SUMMARY: (09) SAN FRANCISCO	3	0	3	92.0%
REPORT SUMMARY:	3	0	3	92.0%

User ID: XGSWU DATA COMPLETENESS REPORT

Report Request ID: 2076083 Report Code: AMP430 Feb. 6, 2023

GEOGRAPHIC SELECTIONS	

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 0010 42101

15 003 0010 42101 15 003 0010 42401 15 009 0006 88101 15 007 0007 42602 15 007 0007 88101

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS SORT ORDER Option Value Order Column Option Type AGENCY ROLE REPORTING 1 EPA_REGION OZONE EVALUATION SEASONAL-HOURLY 2 STATE_CODE MERGE PDF FILES YES MONITOR_TYPE 3 4 COUNTY_CODE 5 SITE_ID 6 PARAMETER_CODE

DATE CRITERIA

Start Date
End Date

Standard Description

2017 01 2017 12

CO 1-hour 1971

7

Lead 3-Month 2009 Lead 3-Month PM10 Surrogate 2009 NO2 Annual 1971

POC

PM10 24-hour 2006 PM25 Annual 2012 SO2 1-hour 2010

Ozone 1-hour 1979

Selection Criteria Page 1

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS NOT REPORTING

AIR OUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2017 THRU DEC. 31, 2017

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

7 H

2 1

600

170

STATE: Hawaii MONITOR TYPE: SLAMS -----OBSERVATIONS -----SITE ID PARAMETER POC DURATION NUMBER / PERCENT CITY METHOD ADDRESS JAN FEB MAR APR MAY SEP OCT NOV DEC YEAR JUN JUL AUG 1 1 15-003-0010 42101 Carbon monoxide 705 8207 640 704 640 708 676 705 706 688 655 681 699 093 95% 95% 95% 89% 95% 94% 95% 95% 96% 888 95% 94% 94% 2052 LAUWILIWILI ST 15-003-0010 42101 Carbon monoxide 2 1 733 450 727 133 665 701 683 739 652 721 713 736 7653 87% 593 99% 67% 98% 18% 89% 97% 92% 99% 91% 97% 99% 99% 2052 LAUWILIWILI ST 15-003-0010 42401 Sulfur dioxide 1 1 8234 693 640 704 672 708 680 705 704 688 655 681 704 93% 060 95% 95% 93% 95% 94% 95% 95% 96% 888 95% 95% 94% 2052 LAUWILIWILI ST 726 712 15-003-0010 42401 Sulfur dioxide 2 1 695 734 7155 273 726 154 631 548 661 597 698 600 93% 41% 98% 21% 85% 76% 89% 80% 97% 98% 99% 82% 2052 LAUWILIWILI ST

8028

100%

653

97%

8726

98%

728

98%

4790

55%

668

93%

7762

87%

738

99%

8532

99%

715

99%

8207

92%

735

99%

8296

93%

739

99%

8412

97%

575

80%

8728

98%

726

8566

99%

719

98% 100%

8829

99%

662

89%

94362

90%

8395

96%

5486

61%

737

99%

KAIHOI ST AND KAIOLOHIA ST

2052 LAUWILIWILI ST

Kihei

15-003-0010 42401 Sulfur dioxide

15-009-0006 88101 PM2.5 - Local Conditions

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2017 THRU DEC. 31, 2017

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii MONITOR TYPE: SPM

SITE ID CITY	PARAMETER	POC	DURATION METHOD	N OBSERVATIONS NUMBER / PERCENT													
ADDRESS				JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR	
15-007-0007	42602 Nitrogen dioxide (NO2)	1	1	710	495		258	415	711	533	734	684	59	642	738	5979	
			000	95%	74%		36%	56%	99%	72%	99%	95%	8%	89%	99%	68%	
2342 HULEMAL	U ROAD, KAUAI																
15-007-0007	88101 PM2.5 - Local Conditions	1	1	738	658	741	606	737	571	720	713	704	741	714	741	8384	
			170	99%	98%	100%	84%	99%	79%	97%	96%	98%	100%	99%	100%	96%	

2342 HULEMALU ROAD, KAUAI

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

REPORT SUMMARY

DATE RANGE: JAN. 01, 2017 THRU DEC. 31, 2017

REGION: (09) SAN FRANCISCO

STATE: Hawaii

REP ORG: Hawaii State Department Of Health

PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
42101 Carbon monoxide	2	0	2	90.5%
42401 Sulfur dioxide	3	0	3	88.7%
88101 PM2.5 - Local Conditions	1	0	1	96.0%
MT SUMMARY: SLAMS	6	0	6	90.5%
MONITOR TYPE: SPM				
PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
42602 Nitrogen dioxide (NO2)	1	0	0	68.0%
88101 PM2.5 - Local Conditions	1	0	1	96.0%
MT SUMMARY: SPM	2	0	1	82.0%
RO SUMMARY: Hawaii State Department Of Health	8	0	7	88.4%
STATE SUMMARY: Hawaii	8	0	7	88.4%
REGION SUMMARY: (09) SAN FRANCISCO	8	0	7	88.4%
REPORT SUMMARY:	8	0	7	88.4%

User ID: XGSWU DATA COMPLETENESS REPORT

Report Request ID: 2076079 Report Code: AMP430 Feb. 6, 2023

GEOGRAPHIC SE	LECTIONS		

POC

Tribal

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 0010 42101

15 003 0010 42401 15 009 0006 88101 15 007 0007 42602 15 007 0007 88101

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS SORT ORDER Option Value Order Column Option Type AGENCY ROLE REPORTING 1 EPA_REGION OZONE EVALUATION SEASONAL-HOURLY 2 STATE_CODE MERGE PDF FILES YES MONITOR_TYPE 3 4 COUNTY_CODE 5 SITE_ID 6 PARAMETER_CODE

DATE CRITERIA

Start Date

End Date

2018 01 2018 12

APPLICABLE STANDARDS

Standard Description

CO 1-hour 1971

7

Lead 3-Month 2009 Lead 3-Month PM10 Surrogate 2009 NO2 Annual 1971

> Ozone 1-hour 1979 PM10 24-hour 2006 PM25 Annual 2012 SO2 1-hour 2010

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS NOT REPORTING

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

MONITOR TYPE: SLAMS

DATE RANGE: JAN. 01, 2018 THRU DEC. 31, 2018

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii

omil. namer															
SITE ID PARAMETER CITY	POC	DURATION METHOD						OBSERVA NUMB	TIONS - ER / PE						
ADDRESS			JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR
15-003-0010 42101 Carbon monoxide	1	1	713	486	689	679	708	706	730	582	686	671	693	715	8058
		093	96%	72%	93%	94%	95%	98%	98%	78%	95%	90%	96%	96%	92%
2052 LAUWILIWILI ST															
15-003-0010 42101 Carbon monoxide	2	1	738	665	651	713	691	715	713	623	702	579	703	712	8205
		593	99%	99%	88%	99%	93%	99%	96%	84%	98%	78%	98%	96%	94%
2052 LAUWILIWILI ST															
15-003-0010 42401 Sulfur dioxide	1	1	715	645	689	703	724	706	730	582	686	668	693	715	8256
		060	96%	96%	93%	98%	97%	98%	98%	78%	95%	90%	96%	96%	94%
2052 LAUWILIWILI ST															
15-003-0010 42401 Sulfur dioxide	2	1	736	661	727	710	690	712	597	624	703	583	702	712	8157
		600	99%	98%	98%	99%	93%	99%	80%	84%	98%	78%	98%	96%	93%
2052 LAUWILIWILI ST															
15-003-0010 42401 Sulfur dioxide	7	Н	8857	7964	8744	8544	8858	8567	8845	7504	8450	7642	8445	8855	101275
		600	99%	99%	98%	99%	99%	99%	99%	84%	98%	86%	98%	99%	96%
2052 LAUWILIWILI ST															
15-009-0006 88101 PM2.5 - Local Conditions	2	1	533	582	742	718	741	718	581	727	714	731	709	633	8129
Kihei		170	72%	87%	100%	100%	100%	100%	78%	98%	99%	98%	98%	85%	93%
KAIHOI ST AND KAIOLOHIA ST															

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2018 THRU DEC. 31, 2018

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii MONITOR TYPE: SPM

SITE ID CITY	PARAMETER	POC	DURATION METHOD					(OBSERVAT NUMBE		 RCENT												
ADDRESS				JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR							
15-007-0007	42602 Nitrogen dioxide (NO2)	1	1	702	657	644	700	726	691	722	728	682	624	548	564	7988							
			212	94%	98%	87%	97%	98%	96%	97%	98%	95%	84%	76%	76%	91%							
2342 HULEMAL	U ROAD, KAUAI																						
15-007-0007	88101 PM2.5 - Local Conditions	1	1	412	664	737	544	738	717	619	736	720	714	568	641	7810							
			170	55%	99%	99%	76%	99%	100%	83%	99%	100%	96%	79%	86%	89%							

2342 HULEMALU ROAD, KAUAI

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

REPORT SUMMARY

DATE RANGE: JAN. 01, 2018 THRU DEC. 31, 2018

REGION: (09) SAN FRANCISCO

STATE: Hawaii

REP ORG: Hawaii State Department Of Health

PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
42101 Carbon monoxide	2	0	2	93.0%
42401 Sulfur dioxide	3	0	3	94.3%
88101 PM2.5 - Local Conditions	1	0	1	93.0%
MT SUMMARY: SLAMS	6	0	6	93.7%
MONITOR TYPE: SPM				
PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
42602 Nitrogen dioxide (NO2)	1	0	1	91.0%
88101 PM2.5 - Local Conditions	1	0	1	89.0%
MT SUMMARY: SPM	2	0	2	90.0%
RO SUMMARY: Hawaii State Department Of Health	8	0	8	92.8%
STATE SUMMARY: Hawaii	8	0	8	92.8%
REGION SUMMARY: (09) SAN FRANCISCO	8	0	8	92.8%
REPORT SUMMARY:	8	0	8	92.8%

User ID: XGSWU DATA COMPLETENESS REPORT

2076057 Report Code: Feb. 6, 2023 Report Request ID: AMP430

GEOGRAPHIC SELECTIONS

5

Tribal EPA Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 0010 42101 15 003 0010 42401 15 009 0006 88101 15 007 0007 42602

007

0007

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS SORT ORDER Option Value Order Column Option Type AGENCY ROLE REPORTING 1 EPA_REGION OZONE EVALUATION SEASONAL-HOURLY 2 STATE_CODE MERGE PDF FILES YES MONITOR_TYPE 3

88101

4 COUNTY_CODE

> 6 PARAMETER_CODE POC

SITE_ID

7

DATE CRITERIA APPLICABLE STANDARDS Start Date End Date Standard Description 2019 12 CO 1-hour 1971

2019 01 Lead 3-Month 2009

Lead 3-Month PM10 Surrogate 2009

NO2 Annual 1971

Ozone 1-hour 1979

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS NOT REPORTING

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2019 THRU DEC. 31, 2019

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii

STATE: Hawaii				MONITOR	TYPE:	SLAMS										
SITE ID PARAM	ETER I	POC	DURATION METHOD					(OBSERVA NUMB	TIONS - ER / PE						
ADDRESS				JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR
15-003-0010 42101	Carbon monoxide	1	1	718	646	725	696	728	699	719	715	695	718	690	721	8470
			093	97%	96%	97%	97%	98%	97%	97%	96%	97%	97%	96%	97%	97%
2052 LAUWILIWILI ST	1															
15-003-0010 42101	Carbon monoxide	2	1	728	642	685	711	711	694	716	720	712	695	381	734	8129
			593	98%	96%	92%	99%	96%	96%	96%	97%	99%	93%	53%	99%	93%
2052 LAUWILIWILI ST	1															
15-003-0010 42401	Sulfur dioxide	1	1	718	558	488	696	728	699	719	715	692	553	480	716	7762
			060	97%	83%	66%	97%	98%	97%	97%	96%	96%	74%	67%	96%	89%
2052 LAUWILIWILI ST	1															
15-003-0010 42401	Sulfur dioxide	2	1	727	644	714	711	712	672	723	728	715	673	331	735	8085
			600	98%	96%	96%	99%	96%	93%	97%	98%	99%	90%	46%	99%	92%
2052 LAUWILIWILI ST																
15-003-0010 42401	Sulfur dioxide	7	Н	8856	7980	8856	8545	8832	8595	8825	8866	8590	8888	8563	8847	104243
			600	99%	99%	99%	99%	99%	99%	99%	99%	99%	100%	99%	99%	99%
2052 LAUWILIWILI ST																
15-009-0006 88101	PM2.5 - Local Conditions	2	1	711	632	743	718	741	669	724	742	717	741	715	738	8591
Kihei			000	96%	94%	100%	100%	100%	93%	97%	100%	100%	100%	99%	99%	98%
KAIHOI ST AND KAIOI	LOHIA ST															

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2019 THRU DEC. 31, 2019

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawa	aii		MONITOR TYPE: SPM													
SITE ID CITY	PARAMETER	POC	DURATION OBSERVATIONS METHOD NUMBER / PERCENT													
ADDRESS				JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR
15-007-0007	42602 Nitrogen dioxide (NO2)	1	1	724	651	730	696	722	675	705	718	693	706	679	691	8390
			212	97%	97%	98%	97%	97%	94%	95%	97%	96%	95%	94%	93%	96%
2342 HULEMAL	U ROAD, KAUAI															
15-007-0007	88101 PM2.5 - Local Conditions	1	1	741	668	630	370	741	716	738	739	712	736	712	707	8210
			000	100%	99%	85%	51%	100%	99%	99%	99%	99%	99%	99%	95%	94%

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

REPORT SUMMARY

Feb. 6, 2023

DATE RANGE: JAN. 01, 2019 THRU DEC. 31, 2019

REGION: (09) SAN FRANCISCO

STATE: Hawaii

REP ORG: Hawaii State Department Of Health

PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
42101 Carbon monoxide	2	0	2	95.0%
42401 Sulfur dioxide	3	0	3	93.3%
88101 PM2.5 - Local Conditions	1	0	1	98.0%
MT SUMMARY: SLAMS	6	0	6	94.7%
MONITOR TYPE: SPM				
PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
42602 Nitrogen dioxide (NO2)	1	0	1	96.0%
88101 PM2.5 - Local Conditions	1	0	1	94.0%
MT SUMMARY: SPM	2	0	2	95.0%
RO SUMMARY: Hawaii State Department Of Health	8	0	8	94.8%
STATE SUMMARY: Hawaii	8	0	8	94.8%
REGION SUMMARY: (09) SAN FRANCISCO	8	0	8	94.8%
REPORT SUMMARY:	8	0	8	94.8%

User ID: XGSWU DATA COMPLETENESS REPORT

2076056 Report Code: Feb. 6, 2023 Report Request ID: AMP430

GEOGRAPHIC SELECTIONS		

PARAMETER_CODE

POC

EPA

6

7

Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 0010 42101 15 003 0010 42401 15 009 0006 88101 15 007 0007 42602

0007

88101

007

PROTOCOL SELECTIONS

Tribal

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS SORT ORDER Option Value Order Column Option Type AGENCY ROLE REPORTING 1 EPA_REGION OZONE EVALUATION SEASONAL-HOURLY 2 STATE_CODE MERGE PDF FILES YES MONITOR_TYPE 3 4 COUNTY_CODE 5 SITE_ID

DATE CRITERIA APPLICABLE STANDARDS Start Date End Date

Standard Description 2020 12 CO 1-hour 1971 2020 01

> Lead 3-Month 2009 Lead 3-Month PM10 Surrogate 2009

NO2 Annual 1971

Ozone 1-hour 1979

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS NOT REPORTING

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2020 THRU DEC. 31, 2020

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii

STATE: Hawall			MONITOR	TYPE:	SLAMS										
SITE ID PARAMETER	POC	DURATION METHOD						OBSERVA NUMB	TIONS - ER / PE						
ADDRESS			JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR
15-003-0010 42101 Carbon mo	noxide 1	1	726	678	715	695	727	697	728	724	693	719	693	720	8515
		093	98%	97%	96%	97%	98%	97%	98%	97%	96%	97%	96%	97%	97%
2052 LAUWILIWILI ST															
15-003-0010 42101 Carbon mo	noxide 2	1	694	692	739	712	735	715	712	739	713	737	665	715	8568
		593	93%	99%	99%	99%	99%	99%	96%	99%	99%	99%	92%	96%	98%
2052 LAUWILIWILI ST															
15-003-0010 42401 Sulfur di	oxide 1	1	720	678	713	692	723	697	728	724	468	713	690	716	8262
		060	97%	97%	96%	96%	97%	97%	98%	97%	65%	96%	96%	96%	94%
2052 LAUWILIWILI ST															
15-003-0010 42401 Sulfur di	oxide 2	1	712	691	716	701	734	714	734	601	131	737	640	732	7843
		000	96%	99%	96%	97%	99%	99%	99%	81%	18%	99%	89%	98%	89%
2052 LAUWILIWILI ST															
15-003-0010 42401 Sulfur di	oxide 7	Н	8837	8308	7359	8238	8855	8579	8826	7194	1574	8852	8496	8805	93923
		000	99%	99%	82%	95%	99%	99%	99%	81%	18%	99%	98%	99%	89%
2052 LAUWILIWILI ST															
15-009-0006 88101 PM2.5 - L	ocal Conditions 2	1	741	310	740	718	736	709	628	737	714	654	536	739	7962
Kihei		209	100%	45%	99%	100%	99%	98%	84%	99%	99%	88%	74%	99%	91%
KAIHOI ST AND KAIOLOHIA ST															

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2020 THRU DEC. 31, 2020

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii MONITOR TYPE: SPM

SITE ID CITY	PARAMETER	POC	DURATION METHOD	OBSERVATIONS NUMBER / PERCENT												
ADDRESS				JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR
15-007-0007	42602 Nitrogen dioxide (NO2)	1	1	728	675	719	701	728	696	728	721	697	728	697	710	8528
			212	98%	97%	97%	97%	98%	97%	98%	97%	97%	98%	97%	95%	97%
2342 HULEMAL	U ROAD, KAUAI															
15-007-0007	88101 PM2.5 - Local Conditions	1	1	716	615	741	714	738	715	735	720	60	554	715	736	7759
			209	96%	888	100%	99%	99%	99%	99%	97%	8%	74%	99%	99%	888

2342 HULEMALU ROAD, KAUAI

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

REPORT SUMMARY

DATE RANGE: JAN. 01, 2020 THRU DEC. 31, 2020

REGION: (09) SAN FRANCISCO

STATE: Hawaii

REP ORG: Hawaii State Department Of Health

PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
42101 Carbon monoxide	2	0	2	97.5%
42401 Sulfur dioxide	3	0	3	90.7%
88101 PM2.5 - Local Conditions	1	0	1	91.0%
MT SUMMARY: SLAMS	6	0	6	93.0%
MONITOR TYPE: SPM				
PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
42602 Nitrogen dioxide (NO2)	1	0	1	97.0%
88101 PM2.5 - Local Conditions	1	0	1	88.0%
MT SUMMARY: SPM	2	0	2	92.5%
RO SUMMARY: Hawaii State Department Of Health	8	0	8	92.9%
STATE SUMMARY: Hawaii	8	0	8	92.9%
REGION SUMMARY: (09) SAN FRANCISCO	8	0	8	92.9%
REPORT SUMMARY:	8	0	8	92.9%

User ID: XGSWU DATA COMPLETENESS REPORT

2076055 Report Code: Feb. 6, 2023 Report Request ID: AMP430

GEOGRAPHIC SELECTIONS

SORT ORDER

COUNTY_CODE

SITE_ID

PARAMETER_CODE

POC

4

5

6

7

Tribal EPA Code State County Site Parameter POC City AQCR UAR CBSA CSA Region

15 003 0010 42101 15 003 0010 42401 15 009 0006 88101

15 007 0007 42602 007 0007 88101

PROTOCOL SELECTIONS

Parameter

Classification Parameter Method Duration

CRITERIA

SELECTED OPTIONS

Option Value Order Column Option Type AGENCY ROLE REPORTING 1 EPA_REGION OZONE EVALUATION SEASONAL-HOURLY 2 STATE_CODE MERGE PDF FILES YES MONITOR_TYPE 3

DATE CRITERIA

Start Date End Date

2021 12 2021 01

APPLICABLE STANDARDS

Standard Description

CO 1-hour 1971 Lead 3-Month 2009

Lead 3-Month PM10 Surrogate 2009

NO2 Annual 1971

Ozone 1-hour 1979

PM10 24-hour 2006

PM25 Annual 2012

SO2 1-hour 2010

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY AIR QUALITY SYSTEM DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS NOT REPORTING

AIR OUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2021 THRU DEC. 31, 2021

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

209

STATE: Hawaii

Kihei

KAIHOI ST AND KAIOLOHIA ST

MONITOR TYPE: SLAMS -----OBSERVATIONS -----SITE ID PARAMETER POC DURATION NUMBER / PERCENT CITY METHOD ADDRESS JAN FEB MAR APR MAY SEP OCT NOV DEC YEAR JUN JUL AUG 1 1 15-003-0010 42101 Carbon monoxide 726 728 8453 724 704 717 700 724 681 724 694 675 656 093 97% 97% 98% 98% 98% 96% 98% 97% 95% 97% 96% 91% 96% 2052 LAUWILIWILI ST 15-003-0010 42101 Carbon monoxide 2 1 697 504 700 700 704 677 736 738 650 743 720 675 8244 593 94% 75% 94% 97% 95% 94% 99% 99% 90% 100% 100% 91% 94% 2052 LAUWILIWILI ST 15-003-0010 42401 Sulfur dioxide 1 1 275 197 5985 560 656 724 704 717 700 728 724 75% 060 98% 97% 98% 96% 97% 98% 97% 38% 26% 68% 2052 LAUWILIWILI ST 15-003-0010 42401 Sulfur dioxide 2 1 702 726 734 709 710 698 8354 649 678 679 689 738 642 560 94% 97% 91% 94% 98% 96% 99% 99% 98% 86% 99% 94% 95% 2052 LAUWILIWILI ST 15-003-0010 42401 Sulfur dioxide 7 H 8842 7995 8847 8538 8862 8563 531 18 16 7729 8537 8435 76913 560 99% 99% 99% 99% 99% 99% 6% 0 응 0 응 87% 99% 94% 73% 2052 LAUWILIWILI ST 737 15-009-0006 88101 PM2.5 - Local Conditions 2 1 666 740 710 728 711 733 736 714 565 713 729 8482

99%

99%

99%

99%

98%

99%

99%

99%

99%

76%

99%

98%

97%

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

MONITORS REPORTING

DATE RANGE: JAN. 01, 2021 THRU DEC. 31, 2021

REGION: (09) SAN FRANCISCO REP ORG: Hawaii State Department Of Health

STATE: Hawaii MONITOR TYPE: SPM

SITE ID CITY	PARAMETER	POC	POC DURATION OBSERVATIONS METHOD NUMBER / PERCENT													
ADDRESS				JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	YEAR
15-007-0007	42602 Nitrogen dioxide (NO2)	1	1	728	618	708	703	717	704	674	692	475	720	695	715	8149
			212	98%	92%	95%	98%	96%	98%	91%	93%	66%	97%	97%	96%	93%
2342 HULEMAL	U ROAD, KAUAI															
15-007-0007	88101 PM2.5 - Local Conditions	1	1	736	526	736	713	737	712	737	734	716	404	709	733	8193
			209	99%	78%	99%	99%	99%	99%	99%	99%	99%	54%	98%	99%	94%

2342 HULEMALU ROAD, KAUAI

AIR QUALITY SYSTEM

DATA COMPLETENESS REPORT

Feb. 6, 2023

REPORT SUMMARY

DATE RANGE: JAN. 01, 2021 THRU DEC. 31, 2021

REGION: (09) SAN FRANCISCO

STATE: Hawaii

REP ORG: Hawaii State Department Of Health

PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
42101 Carbon monoxide	2	0	2	95.0%
42401 Sulfur dioxide	3	0	1	78.7%
88101 PM2.5 - Local Conditions	1	0	1	97.0%
MT SUMMARY: SLAMS	6	0	4	87.2%
MONITOR TYPE: SPM				
PARAMETER	ACTIVE MONITORS	# NOT REPORTING	# MONITORS > 75%	MONITORS AVG COMPLETENESS
42602 Nitrogen dioxide (NO2)	1	0	1	93.0%
88101 PM2.5 - Local Conditions	1	0	1	94.0%
MT SUMMARY: SPM	2	0	2	93.5%
RO SUMMARY: Hawaii State Department Of Health	8	0	6	88.8%
STATE SUMMARY: Hawaii	8	0	6	88.8%
REGION SUMMARY: (09) SAN FRANCISCO	8	0	6	88.8%
REPORT SUMMARY:	8	0	6	88.8%